

Package ‘PlaneGeometry’

August 9, 2023

Type Package

Title Plane Geometry

Version 1.6.0

Author Stéphane Laurent

Maintainer Stéphane Laurent <laurent_step@outlook.fr>

Description An extensive set of plane geometry routines. Provides R6 classes representing triangles, circles, circular arcs, ellipses, elliptical arcs, lines, hyperbolae, and their plot methods. Also provides R6 classes representing transformations: rotations, reflections, homotheties, scalings, general affine transformations, inversions, Möbius transformations.

License GPL-3

URL <https://github.com/stla/PlaneGeometry>

BugReports <https://github.com/stla/PlaneGeometry/issues>

Imports Carlson, CVXR, fitConic, graphics, methods, R6, rcdd, sdpt3r, stringr, uniformly

Suggests ellipse, elliptic, freegroup, knitr, rgl, rmarkdown, sets, testthat, viridisLite

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.2.3

NeedsCompilation no

Repository CRAN

Date/Publication 2023-08-09 21:40:02 UTC

R topics documented:

| | |
|------------------------------|---|
| Affine | 3 |
| AffineMappingEllipse2Ellipse | 5 |
| AffineMappingThreePoints | 5 |

| | |
|--------------------------------|----|
| Arc | 6 |
| Circle | 8 |
| CircleAB | 15 |
| CircleOA | 16 |
| crossRatio | 16 |
| draw | 17 |
| Ellipse | 18 |
| EllipseEquationFromFivePoints | 27 |
| EllipseFromCenterAndMatrix | 28 |
| EllipseFromEquation | 28 |
| EllipseFromFivePoints | 29 |
| EllipseFromFociAndOnePoint | 30 |
| EllipseFromThreeBoundaryPoints | 30 |
| EllipticalArc | 31 |
| fitEllipse | 33 |
| GaussianEllipse | 34 |
| Homothety | 34 |
| Hyperbola | 36 |
| HyperbolaFromEquation | 40 |
| intersectionCircleCircle | 41 |
| intersectionCircleLine | 41 |
| intersectionEllipseLine | 42 |
| intersectionLineLine | 43 |
| Inversion | 43 |
| inversionFixingThreeCircles | 47 |
| inversionFixingTwoCircles | 48 |
| inversionFromCircle | 48 |
| inversionKeepingCircle | 49 |
| inversionSwappingTwoCircles | 49 |
| Line | 50 |
| LineFromEquation | 54 |
| LineFromInterceptAndSlope | 55 |
| LownerJohnEllipse | 55 |
| maxAreaInscribedCircle | 56 |
| maxAreaInscribedEllipse | 57 |
| midCircles | 58 |
| Mobius | 59 |
| MobiusMappingCircle | 62 |
| MobiusMappingThreePoints | 63 |
| MobiusSwappingTwoPoints | 64 |
| Projection | 64 |
| radicalCenter | 67 |
| Reflection | 67 |
| Rotation | 70 |
| Scaling | 73 |
| ScalingXY | 75 |
| Shear | 77 |
| soddyCircle | 80 |

| | |
|------------------------------|-----------|
| <i>Affine</i> | 3 |
| SteinerChain | 80 |
| Translation | 81 |
| Triangle | 83 |
| TriangleThreeLines | 98 |
| unitCircle | 98 |
| Index | 99 |

Affine *R6 class representing an affine map.*

Description

An affine map is given by a 2x2 matrix (a linear transformation) and a vector (the "intercept").

Active bindings

- A get or set the matrix A
- b get or set the vector b

Methods

Public methods:

- `Affine$new()`
- `Affine$print()`
- `Affine$get3x3matrix()`
- `Affine$inverse()`
- `Affine$compose()`
- `Affine$transform()`
- `Affine$transformLine()`
- `Affine$transformEllipse()`
- `Affine$clone()`

Method `new()`: Create a new Affine object.

Usage:

`Affine$new(A, b)`

Arguments:

- A the 2x2 matrix of the affine map
- b the shift vector of the affine map

Returns: A new Affine object.

Method `print()`: Show instance of an Affine object.

Usage:

`Affine$print(...)`

Arguments:

... ignored

Examples:

```
Affine$new(rbind(c(3.5,2),c(0,4)), c(-1, 1.25))
```

Method `get3x3matrix()`: The 3x3 matrix representing the affine map.

Usage:

```
Affine$get3x3matrix()
```

Method `inverse()`: The inverse affine transformation, if it exists.

Usage:

```
Affine$inverse()
```

Method `compose()`: Compose the reference affine map with another affine map.

Usage:

```
Affine$compose(transfo, left = TRUE)
```

Arguments:

transfo an Affine object

left logical, whether to compose at left or at right (i.e. returns $f_1 \circ f_0$ or $f_0 \circ f_1$)

Returns: An Affine object.

Method `transform()`: Transform a point or several points by the reference affine map.

Usage:

```
Affine$transform(M)
```

Arguments:

M a point or a two-column matrix of points, one point per row

Method `transformLine()`: Transform a line by the reference affine transformation (only for invertible affine maps).

Usage:

```
Affine$transformLine(line)
```

Arguments:

line a Line object

Returns: A Line object.

Method `transformEllipse()`: Transform an ellipse by the reference affine transformation (only for an invertible affine map). The result is an ellipse.

Usage:

```
Affine$transformEllipse(ell)
```

Arguments:

ell an Ellipse object or a Circle object

Returns: An Ellipse object.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Affine$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `Affine$print`
## -----
Affine$new(rbind(c(3.5,2),c(0,4)), c(-1, 1.25))
```

AffineMappingEllipse2Ellipse*Affine transformation mapping a given ellipse to a given ellipse***Description**

Return the affine transformation which transforms ell1 to ell2.

Usage

```
AffineMappingEllipse2Ellipse(ell1, ell2)
```

Arguments

ell1, ell2 Ellipse or Circle objects

Value

An Affine object.

Examples

```
ell1 <- Ellipse$new(c(1,1), 5, 1, 30)
( ell2 <- Ellipse$new(c(4,-1), 3, 2, 50) )
f <- AffineMappingEllipse2Ellipse(ell1, ell2)
f$transformEllipse(ell1) # should be ell2
```

AffineMappingThreePoints*Affine transformation mapping three given points to three given points***Description**

Return the affine transformation which sends P1 to Q1, P2 to Q2 and P3 to Q3.

Usage

```
AffineMappingThreePoints(P1, P2, P3, Q1, Q2, Q3)
```

Arguments

| | |
|------------|----------------------------|
| P1, P2, P3 | three non-collinear points |
| Q1, Q2, Q3 | three non-collinear points |

Value

An Affine object.

Arc

R6 class representing a circular arc

Description

An arc is given by a center, a radius, a starting angle and an ending angle. They are respectively named center, radius, alpha1 and alpha2.

Active bindings

- center get or set the center
- radius get or set the radius
- alpha1 get or set the starting angle
- alpha2 get or set the ending angle
- degrees get or set the degrees field

Methods**Public methods:**

- [Arc\\$new\(\)](#)
- [Arc\\$print\(\)](#)
- [Arc\\$startingPoint\(\)](#)
- [Arc\\$endingPoint\(\)](#)
- [Arc\\$isEqual\(\)](#)
- [Arc\\$complementaryArc\(\)](#)
- [Arc\\$path\(\)](#)
- [Arc\\$clone\(\)](#)

Method `new()`: Create a new Arc object.

Usage:

```
Arc$new(center, radius, alpha1, alpha2, degrees = TRUE)
```

Arguments:

center the center

radius the radius

alpha1 the starting angle

alpha2 the ending angle
degrees logical, whether alpha1 and alpha2 are given in degrees

Returns: A new Arc object.

Examples:

```
arc <- Arc$new(c(1,1), 1, 45, 90)
arc
arc$center
arc$center <- c(0,0)
arc
```

Method print(): Show instance of an Arc object.

Usage:

```
Arc$print(...)
```

Arguments:

... ignored

Examples:

```
Arc$new(c(0,0), 2, pi/4, pi/2, FALSE)
```

Method startingPoint(): Starting point of the reference arc.

Usage:

```
Arc$startingPoint()
```

Method endingPoint(): Ending point of the reference arc.

Usage:

```
Arc$endingPoint()
```

Method isEqual(): Check whether the reference arc equals another arc.

Usage:

```
Arc$isEqual(arc)
```

Arguments:

arc an Arc object

Method complementaryArc(): Complementary arc of the reference arc.

Usage:

```
Arc$complementaryArc()
```

Examples:

```
arc <- Arc$new(c(0,0), 1, 30, 60)
plot(NULL, type = "n", asp = 1, xlim = c(-1,1), ylim = c(-1,1),
      xlab = NA, ylab = NA)
draw(arc, lwd = 3, col = "red")
draw(arc$complementaryArc(), lwd = 3, col = "green")
```

Method path(): The reference arc as a path.

Usage:

```
Arc$path(npoints = 100L)
```

Arguments:

npoints number of points of the path

Returns: A matrix with two columns x and y of length npoints. See "Filling the lapping area of two circles" in the vignette for an example.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
Arc$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `Arc$new`
## -----  
  

arc <- Arc$new(c(1,1), 1, 45, 90)
arc
arc$center
arc$center <- c(0,0)
arc  
  

## -----
## Method `Arc$print`
## -----  
  

Arc$new(c(0,0), 2, pi/4, pi/2, FALSE)  
  

## -----
## Method `Arc$complementaryArc`
## -----  
  

arc <- Arc$new(c(0,0), 1, 30, 60)
plot(NULL, type = "n", asp = 1, xlim = c(-1,1), ylim = c(-1,1),
      xlab = NA, ylab = NA)
draw(arc, lwd = 3, col = "red")
draw(arc$complementaryArc(), lwd = 3, col = "green")
```

Description

A circle is given by a center and a radius, named `center` and `radius`.

Active bindings

center get or set the center
radius get or set the radius

Methods

Public methods:

- `Circle$new()`
- `Circle$print()`
- `Circle$pointFromAngle()`
- `Circle$diameter()`
- `Circle$tangent()`
- `Circle$tangentsThroughExternalPoint()`
- `Circle$isEqual()`
- `Circle$isDifferent()`
- `Circle$isOrthogonal()`
- `Circle$angle()`
- `Circle$includes()`
- `Circle$orthogonalThroughTwoPointsOnCircle()`
- `Circle$orthogonalThroughTwoPointsWithinCircle()`
- `Circle$power()`
- `Circle$radicalCenter()`
- `Circle$radicalAxis()`
- `Circle$rotate()`
- `Circle$translate()`
- `Circle$invert()`
- `Circle$asEllipse()`
- `Circle$randomPoints()`
- `Circle$clone()`

Method new(): Create a new Circle object.

Usage:

`Circle$new(center, radius)`

Arguments:

center the center

radius the radius

Returns: A new Circle object.

Examples:

```
circ <- Circle$new(c(1,1), 1)
circ
circ$center
circ$center <- c(0,0)
circ
```

Method `print()`: Show instance of a circle object.

Usage:

```
Circle$print(...)
```

Arguments:

... ignored

Examples:

```
Circle$new(c(0,0), 2)
```

Method `pointFromAngle()`: Get a point on the reference circle from its polar angle.

Usage:

```
Circle$pointFromAngle(alpha, degrees = TRUE)
```

Arguments:

`alpha` a number, the angle

`degrees` logical, whether `alpha` is given in degrees

Returns: The point on the circle with polar angle `alpha`.

Method `diameter()`: Diameter of the reference circle for a given polar angle.

Usage:

```
Circle$diameter(alpha)
```

Arguments:

`alpha` an angle in radians, there is one diameter for each value of `alpha` modulo π

Returns: A segment (Line object).

Examples:

```
circ <- Circle$new(c(1,1), 5)
diams <- lapply(c(0, pi/3, 2*pi/3), circ$diameter)
plot(NULL, type="n", asp=1, xlim = c(-4,6), ylim = c(-5,7),
      xlab = NA, ylab = NA)
draw(circ, lwd = 2, col = "yellow")
invisible(lapply(diams, draw, col = "blue"))
```

Method `tangent()`: Tangent of the reference circle at a given polar angle.

Usage:

```
Circle$tangent(alpha)
```

Arguments:

`alpha` an angle in radians, there is one tangent for each value of `alpha` modulo 2π

Examples:

```
circ <- Circle$new(c(1,1), 5)
tangents <- lapply(c(0, pi/3, 2*pi/3, pi, 4*pi/3, 5*pi/3), circ$tangent)
plot(NULL, type="n", asp=1, xlim = c(-4,6), ylim = c(-5,7),
      xlab = NA, ylab = NA)
draw(circ, lwd = 2, col = "yellow")
invisible(lapply(tangents, draw, col = "blue"))
```

Method `tangentsThroughExternalPoint()`: Return the two tangents of the reference circle passing through an external point.

Usage:

```
Circle$tangentsThroughExternalPoint(P)
```

Arguments:

P a point external to the reference circle

Returns: A list of two Line objects, the two tangents; the tangency points are in the B field of the lines.

Method `isEqual()`: Check whether the reference circle equals another circle.

Usage:

```
Circle$isEqual(circ)
```

Arguments:

circ a Circle object

Method `isDifferent()`: Check whether the reference circle differs from another circle.

Usage:

```
Circle$isDifferent(circ)
```

Arguments:

circ a Circle object

Method `isOrthogonal()`: Check whether the reference circle is orthogonal to a given circle.

Usage:

```
Circle$isOrthogonal(circ)
```

Arguments:

circ a Circle object

Method `angle()`: Angle between the reference circle and a given circle, if they intersect.

Usage:

```
Circle$angle(circ)
```

Arguments:

circ a Circle object

Method `includes()`: Check whether a point belongs to the reference circle.

Usage:

```
Circle$includes(M)
```

Arguments:

M a point

Method `orthogonalThroughTwoPointsOnCircle()`: Orthogonal circle passing through two points on the reference circle.

Usage:

```
Circle$orthogonalThroughTwoPointsOnCircle(alpha1, alpha2, arc = FALSE)
```

Arguments:

alpha1, alpha2 two angles defining two points on the reference circle

arc logical, whether to return only the arc at the interior of the reference circle

Returns: A Circle object if arc=FALSE, an Arc object if arc=TRUE, or a Line object: the diameter of the reference circle defined by the two points in case when the two angles differ by pi.

Examples:

```
# hyperbolic triangle
circ <- Circle$new(c(5,5), 3)
arc1 <- circ$orthogonalThroughTwoPointsOnCircle(0, 2*pi/3, arc = TRUE)
arc2 <- circ$orthogonalThroughTwoPointsOnCircle(2*pi/3, 4*pi/3, arc = TRUE)
arc3 <- circ$orthogonalThroughTwoPointsOnCircle(4*pi/3, 0, arc = TRUE)
opar <- par(mar = c(0,0,0,0))
plot(0, 0, type = "n", asp = 1, xlim = c(2,8), ylim = c(2,8))
draw(circ)
draw(arc1, col = "red", lwd = 2)
draw(arc2, col = "green", lwd = 2)
draw(arc3, col = "blue", lwd = 2)
par(opar)
```

Method orthogonalThroughTwoPointsWithinCircle(): Orthogonal circle passing through two points within the reference circle.

Usage:

```
Circle$orthogonalThroughTwoPointsWithinCircle(P1, P2, arc = FALSE)
```

Arguments:

P1, P2 two distinct points in the interior of the reference circle

arc logical, whether to return the arc joining the two points instead of the circle

Returns: A Circle object or an Arc object, or a Line object if the two points are on a diameter.

Examples:

```
circ <- Circle$new(c(0,0),3)
P1 <- c(1,1); P2 <- c(1, 2)
ocirc <- circ$orthogonalThroughTwoPointsWithinCircle(P1, P2)
arc <- circ$orthogonalThroughTwoPointsWithinCircle(P1, P2, arc = TRUE)
plot(0, 0, type = "n", asp = 1, xlab = NA, ylab = NA,
     xlim = c(-3, 4), ylim = c(-3, 4))
draw(circ, lwd = 2)
draw(ocirc, lty = "dashed", lwd = 2)
draw(arc, lwd = 3, col = "blue")
```

Method power(): Power of a point with respect to the reference circle.

Usage:

```
Circle$power(M)
```

Arguments:

M point

Returns: A number.

Method radicalCenter(): Radical center of two circles.

Usage:

Circle\$radicalCenter(circ2)

Arguments:

circ2 a Circle object

Method radicalAxis(): Radical axis of two circles.

Usage:

Circle\$radicalAxis(circ2)

Arguments:

circ2 a Circle object

Returns: A Line object.

Method rotate(): Rotate the reference circle.

Usage:

Circle\$rotate(alpha, 0, degrees = TRUE)

Arguments:

alpha angle of rotation

0 center of rotation

degrees logical, whether alpha is given in degrees

Returns: A Circle object.

Method translate(): Translate the reference circle.

Usage:

Circle\$translate(v)

Arguments:

v the vector of translation

Returns: A Circle object.

Method invert(): Invert the reference circle.

Usage:

Circle\$invert(inversion)

Arguments:

inversion an Inversion object

Returns: A Circle object or a Line object.

Method asEllipse(): Convert the reference circle to an Ellipse object.

Usage:

Circle\$asEllipse()

Method `randomPoints()`: Random points on or in the reference circle.

Usage:

```
Circle$randomPoints(n, where = "in")
```

Arguments:

`n` an integer, the desired number of points

`where` "in" to generate inside the circle, "on" to generate on the circle

Returns: The generated points in a two columns matrix with `n` rows.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Circle$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

[radicalCenter](#) for the radical center of three circles.

Examples

```
## -----
## Method `Circle$new`
## -----  
  

circ <- Circle$new(c(1,1), 1)
circ
circ$center
circ$center <- c(0,0)
circ  
  

## -----
## Method `Circle$print`
## -----  
  

Circle$new(c(0,0), 2)  
  

## -----
## Method `Circle$diameter`
## -----  
  

circ <- Circle$new(c(1,1), 5)
diams <- lapply(c(0, pi/3, 2*pi/3), circ$diameter)
plot(NULL, type="n", asp=1, xlim = c(-4,6), ylim = c(-5,7),
     xlab = NA, ylab = NA)
draw(circ, lwd = 2, col = "yellow")
invisible(lapply(diams, draw, col = "blue"))  
  

## -----
```

```

## Method `Circle$tangent`
## ----

circ <- Circle$new(c(1,1), 5)
tangents <- lapply(c(0, pi/3, 2*pi/3, pi, 4*pi/3, 5*pi/3), circ$tangent)
plot(NULL, type="n", asp=1, xlim = c(-4,6), ylim = c(-5,7),
     xlab = NA, ylab = NA)
draw(circ, lwd = 2, col = "yellow")
invisible(lapply(tangents, draw, col = "blue"))

## -----
## Method `Circle$orthogonalThroughTwoPointsOnCircle`
## ----

# hyperbolic triangle
circ <- Circle$new(c(5,5), 3)
arc1 <- circ$orthogonalThroughTwoPointsOnCircle(0, 2*pi/3, arc = TRUE)
arc2 <- circ$orthogonalThroughTwoPointsOnCircle(2*pi/3, 4*pi/3, arc = TRUE)
arc3 <- circ$orthogonalThroughTwoPointsOnCircle(4*pi/3, 0, arc = TRUE)
opar <- par(mar = c(0,0,0,0))
plot(0, 0, type = "n", asp = 1, xlim = c(2,8), ylim = c(2,8))
draw(circ)
draw(arc1, col = "red", lwd = 2)
draw(arc2, col = "green", lwd = 2)
draw(arc3, col = "blue", lwd = 2)
par(opar)

## -----
## Method `Circle$orthogonalThroughTwoPointsWithinCircle`
## ----

circ <- Circle$new(c(0,0),3)
P1 <- c(1,1); P2 <- c(1, 2)
ocirc <- circ$orthogonalThroughTwoPointsWithinCircle(P1, P2)
arc <- circ$orthogonalThroughTwoPointsWithinCircle(P1, P2, arc = TRUE)
plot(0, 0, type = "n", asp = 1, xlab = NA, ylab = NA,
     xlim = c(-3, 4), ylim = c(-3, 4))
draw(circ, lwd = 2)
draw(ocirc, lty = "dashed", lwd = 2)
draw(arc, lwd = 3, col = "blue")

```

CircleAB

*Circle given by a diameter***Description**

Return the circle given by a diameter

Usage

```
CircleAB(A, B)
```

Arguments

A, B the endpoints of the diameter

Value

A Circle object.

`Circle0A`

Circle given by its center and a point

Description

Return the circle given by its center and a point it passes through.

Usage

`Circle0A(0, A)`

Arguments

0 the center of the circle
A a point of the circle

Value

A Circle object.

`crossRatio`

Cross ratio

Description

The cross ratio of four points.

Usage

`crossRatio(A, B, C, D)`

Arguments

A, B, C, D four distinct points

Value

A complex number. It is real if and only if the four points lie on a generalized circle (that is a circle or a line).

Examples

```
c <- Circle$new(c(0, 0), 1)
A <- c$pointFromAngle(0)
B <- c$pointFromAngle(90)
C <- c$pointFromAngle(180)
D <- c$pointFromAngle(270)
crossRatio(A, B, C, D) # should be real
Mob <- Mobius$new(rbind(c(1+1i,2),c(0,3-2i)))
MA <- Mob$transform(A)
MB <- Mob$transform(B)
MC <- Mob$transform(C)
MD <- Mob$transform(D)
crossRatio(MA, MB, MC, MD) # should be identical to `crossRatio(A, B, C, D)`
```

| | |
|------|--------------------------------|
| draw | <i>Draw a geometric object</i> |
|------|--------------------------------|

Description

Draw a geometric object on the current plot.

Usage

```
draw(x, ...)

## S3 method for class 'Triangle'
draw(x, ...)

## S3 method for class 'Circle'
draw(x, npoints = 100L, ...)

## S3 method for class 'Arc'
draw(x, npoints = 100L, ...)

## S3 method for class 'Ellipse'
draw(x, npoints = 100L, ...)

## S3 method for class 'EllipticalArc'
draw(x, npoints = 100L, ...)

## S3 method for class 'Line'
draw(x, ...)
```

Arguments

| | |
|---|--|
| x | geometric object (Triangle, Circle, Line, Ellipse, Arc, EllipticalArc) |
|---|--|

... arguments passed to `lines` for a `Triangle` object, an `Arc` object or an `EllipticalArc` object, to `polypath` for a `Circle` object or an `Ellipse` object, general graphical parameters for a `Line` object, passed to `lines`, `curve`, or `abline`.
`npoints` integer, the number of points of the path

Examples

```
# open new plot window
plot(0, 0, type="n", asp = 1, xlim = c(0,2.5), ylim = c(0,2.5),
      xlab = NA, ylab = NA)
grid()
# draw a triangle
t <- Triangle$new(c(0,0), c(1,0), c(0.5,sqrt(3)/2))
draw(t, col = "blue", lwd = 2)
draw(t$rotate(90, t$C), col = "green", lwd = 2)
# draw a circle
circ <- t$incircle()
draw(circ, col = "orange", border = "brown", lwd = 2)
# draw an ellipse
S <- Scaling$new(circ$center, direction = c(2,1), scale = 2)
draw(S$scaleCircle(circ), border = "grey", lwd = 2)
# draw a line
l <- Line$new(c(1,1), c(1.5,1.5), FALSE, TRUE)
draw(l, col = "red", lwd = 2)
perp <- l$perpendicular(c(2,1))
draw(perp, col = "yellow", lwd = 2)
```

Ellipse

R6 class representing an ellipse

Description

An ellipse is given by a center, two radii (`rmajor` and `rminor`), and the angle (`alpha`) between the major axis and the horizontal direction.

Active bindings

- `center` get or set the center
- `rmajor` get or set the major radius of the ellipse
- `rminor` get or set the minor radius of the ellipse
- `alpha` get or set the angle of the ellipse
- `degrees` get or set the degrees field

Methods

Public methods:

- `Ellipse$new()`
- `Ellipse$print()`
- `Ellipse$isEqual()`
- `Ellipse$equation()`
- `Ellipse$includes()`
- `Ellipse$contains()`
- `Ellipse$matrix()`
- `Ellipse$path()`
- `Ellipse$diameter()`
- `Ellipse$perimeter()`
- `Ellipse$pointFromAngle()`
- `Ellipse$pointFromEccentricAngle()`
- `Ellipse$semiMajorAxis()`
- `Ellipse$semiMinorAxis()`
- `Ellipse$foci()`
- `Ellipse$tangent()`
- `Ellipse$normal()`
- `Ellipse$theta2t()`
- `Ellipse$regressionLines()`
- `Ellipse$boundingbox()`
- `Ellipse$randomPoints()`
- `Ellipse$clone()`

Method `new():` Create a new Ellipse object.

Usage:

```
Ellipse$new(center, rmajor, rminor, alpha, degrees = TRUE)
```

Arguments:

`center` a point, the center of the rotation

`rmajor` positive number, the major radius

`rminor` positive number, the minor radius

`alpha` a number, the angle between the major axis and the horizontal direction

`degrees` logical, whether alpha is given in degrees

Returns: A new Ellipse object.

Examples:

```
Ellipse$new(c(1,1), 3, 2, 30)
```

Method `print():` Show instance of an Ellipse object.

Usage:

```
Ellipse$print(...)
```

Arguments:

... ignored

Method `isEqual()`: Check whether the reference ellipse equals an ellipse.

Usage:

`Ellipse$isEqual(ell)`

Arguments:

`ell` An Ellipse object.

Method `equation()`: The coefficients of the implicit equation of the ellipse.

Usage:

`Ellipse$equation()`

Details: The implicit equation of the ellipse is $Ax^2 + Bxy + Cy^2 + Dx + Ey + F = 0$. This method returns A, B, C, D, E and F.

Returns: A named numeric vector.

Method `includes()`: Check whether a point lies on the reference ellipse.

Usage:

`Ellipse$includes(M)`

Arguments:

`M` a point

Method `contains()`: Check whether a point is contained in the reference ellipse.

Usage:

`Ellipse$contains(M)`

Arguments:

`M` a point

Method `matrix()`: Returns the 2x2 matrix S associated to the reference ellipse. The equation of the ellipse is $t(M-O) \%*\% S \%*\% (M-O) = 1$.

Usage:

`Ellipse$matrix()`

Examples:

```
ell <- Ellipse$new(c(1,1), 5, 1, 30)
S <- ell$matrix()
O <- ell$center
pts <- ell$path(4L) # four points on the ellipse
apply(pts, 1L, function(M) t(M-O) \%*\% S \%*\% (M-O))
```

Method `path()`: Path that forms the reference ellipse.

Usage:

`Ellipse$path(npoints = 100L, closed = FALSE, outer = FALSE)`

Arguments:

`npoints` number of points of the path
`closed` Boolean, whether to return a closed path; you don't need a closed path if you want to plot it with `polygon`
`outer` Boolean; if TRUE, the ellipse will be contained inside the path, otherwise it will contain the path

Returns: A matrix with two columns `x` and `y` of length `npoints`.

Examples:

```
library(PlaneGeometry)
ell <- Ellipse$new(c(1, -1), rmajor = 3, rminor = 2, alpha = 30)
innerPath <- ell$path(npoints = 10)
outerPath <- ell$path(npoints = 10, outer = TRUE)
bbox <- ell$boundingbox()
plot(NULL, asp = 1, xlim = bbox$x, ylim = bbox$y, xlab = NA, ylab = NA)
draw(ell, border = "red", lty = "dashed")
polygon(innerPath, border = "blue", lwd = 2)
polygon(outerPath, border = "green", lwd = 2)
```

Method `diameter()`: Diameter and conjugate diameter of the reference ellipse.

Usage:

```
Ellipse$diameter(t, conjugate = FALSE)
```

Arguments:

`t` a number, the diameter only depends on `t` modulo pi; the axes correspond to `t=0` and `t=pi/2`
`conjugate` logical, whether to return the conjugate diameter as well

Returns: A Line object or a list of two Line objects if `conjugate = TRUE`.

Examples:

```
ell <- Ellipse$new(c(1,1), 5, 2, 30)
diameters <- lapply(c(0, pi/3, 2*pi/3), ell$diameter)
plot(NULL, asp = 1, xlim = c(-4,6), ylim = c(-2,4),
     xlab = NA, ylab = NA)
draw(ell)
invisible(lapply(diameters, draw))
```

Method `perimeter()`: Perimeter of the reference ellipse.

Usage:

```
Ellipse$perimeter()
```

Method `pointFromAngle()`: Intersection point of the ellipse with the half-line starting at the ellipse center and forming angle theta with the major axis.

Usage:

```
Ellipse$pointFromAngle(theta, degrees = TRUE)
```

Arguments:

`theta` a number, the angle, or a numeric vector
`degrees` logical, whether theta is given in degrees

Returns: A point of the ellipse if `length(theta)==1` or a two-column matrix of points of the ellipse if `length(theta) > 1` (one point per row).

Method `pointFromEccentricAngle()`: Point of the ellipse with given eccentric angle.

Usage:

```
Ellipse$pointFromEccentricAngle(t)
```

Arguments:

`t` a number, the eccentric angle in radians, or a numeric vector

Returns: A point of the ellipse if `length(t)==1` or a two-column matrix of points of the ellipse if `length(t) > 1` (one point per row).

Method `semiMajorAxis()`: Semi-major axis of the ellipse.

Usage:

```
Ellipse$semiMajorAxis()
```

Returns: A segment (Line object).

Method `semiMinorAxis()`: Semi-minor axis of the ellipse.

Usage:

```
Ellipse$semiMinorAxis()
```

Returns: A segment (Line object).

Method `foci()`: Foci of the reference ellipse.

Usage:

```
Ellipse$foci()
```

Returns: A list with the two foci.

Method `tangent()`: Tangents of the reference ellipse at a point given by its eccentric angle.

Usage:

```
Ellipse$tangent(t)
```

Arguments:

`t` eccentric angle, there is one tangent for each value of `t` modulo 2π ; for $t = 0, \pi/2, \pi, -\pi/2$, these are the tangents at the vertices of the ellipse

Examples:

```
ell <- Ellipse$new(c(1,1), 5, 2, 30)
tangents <- lapply(c(0, pi/3, 2*pi/3, pi, 4*pi/3, 5*pi/3), ell$tangent)
plot(NULL, asp = 1, xlim = c(-4, 6), ylim = c(-2, 4),
      xlab = NA, ylab = NA)
draw(ell, col = "yellow")
invisible(lapply(tangents, draw, col = "blue"))
```

Method `normal()`: Normal unit vector to the ellipse.

Usage:

```
Ellipse$normal(t)
```

Arguments:

`t` a number, the eccentric angle in radians of the point of the ellipse at which we want the normal unit vector

Returns: The normal unit vector to the ellipse at the point given by eccentric angle `t`.

Examples:

```
ell <- Ellipse$new(c(1,1), 5, 2, 30)
t_ <- seq(0, 2*pi, length.out = 13)[-1]
plot(NULL, asp = 1, xlim = c(-5,7), ylim = c(-3,5),
      xlab = NA, ylab = NA)
draw(ell, col = "magenta")
for(i in 1:length(t_)){
  t <- t_[i]
  P <- ell$pointFromEccentricAngle(t)
  v <- ell$normal(t)
  draw(Line$new(P, P+v, FALSE, FALSE))
}
```

Method `theta2t()`: Convert angle to eccentric angle.

Usage:

```
Ellipse$theta2t(theta, degrees = TRUE)
```

Arguments:

`theta` angle between the major axis and the half-line starting at the center of the ellipse and passing through the point of interest on the ellipse

`degrees` logical, whether `theta` is given in degrees

Returns: The eccentric angle of the point of interest on the ellipse, in radians.

Examples:

```
0 <- c(1, 1)
ell <- Ellipse$new(0, 5, 2, 30)
theta <- 20
P <- ell$pointFromAngle(theta)
t <- ell$theta2t(theta)
tg <- ell$tangent(t)
OP <- Line$new(0, P, FALSE, FALSE)
plot(NULL, asp = 1, xlim = c(-4,6), ylim = c(-2,5),
      xlab = NA, ylab = NA)
draw(ell, col = "antiquewhite")
points(P[1], P[2], pch = 19)
draw(tg, col = "red")
draw(OP)
draw(ell$semiMajorAxis())
text(t(0+c(1,0.9)), expression(theta))
```

Method `regressionLines()`: Regression lines. The regression line of `y` on `x` intersects the ellipse at its rightmost point and its leftmost point. The tangents at these points are vertical. The regression line of `x` on `y` intersects the ellipse at its topmost point and its bottommost point. The tangents at these points are horizontal.

Usage:

```
Ellipse$regressionLines()
```

Returns: A list with two Line objects: the regression line of y on x and the regression line of x on y.

Examples:

```
ell <- Ellipse$new(c(1,1), 5, 2, 30)
reglines <- ell$regressionLines()
plot(NULL, asp = 1, xlim = c(-4,6), ylim = c(-2,4),
      xlab = NA, ylab = NA)
draw(ell, lwd = 2)
draw(reglines$YonX, lwd = 2, col = "blue")
draw(reglines$XonY, lwd = 2, col = "green")
```

Method boundingbox(): Return the smallest rectangle parallel to the axes which contains the reference ellipse.

Usage:

```
Ellipse$boundingbox()
```

Returns: A list with two components: the x-limits in x and the y-limits in y.

Examples:

```
ell <- Ellipse$new(c(2,2), 5, 3, 40)
box <- ell$boundingbox()
plot(NULL, asp = 1, xlim = box$x, ylim = box$y, xlab = NA, ylab = NA)
draw(ell, col = "seaShell", border = "blue")
abline(v = box$x, lty = 2); abline(h = box$y, lty = 2)
```

Method randomPoints(): Random points on or in the reference ellipse.

Usage:

```
Ellipse$randomPoints(n, where = "in")
```

Arguments:

n an integer, the desired number of points

where "in" to generate inside the ellipse, "on" to generate on the ellipse

Returns: The generated points in a two columns matrix with n rows.

Examples:

```
ell <- Ellipse$new(c(1,1), 5, 2, 30)
pts <- ell$randomPoints(100)
plot(NULL, type="n", asp=1, xlim = c(-4,6), ylim = c(-2,4),
      xlab = NA, ylab = NA)
draw(ell, lwd = 2)
points(pts, pch = 19, col = "blue")
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
Ellipse$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```

## -----
## Method `Ellipse$new`
## -----


Ellipse$new(c(1,1), 3, 2, 30)

## -----
## Method `Ellipse$matrix`
## -----


ell <- Ellipse$new(c(1,1), 5, 1, 30)
S <- ell$matrix()
O <- ell$center
pts <- ell$path(4L) # four points on the ellipse
apply(pts, 1L, function(M) t(M-O) %*% S %*% (M-O))

## -----
## Method `Ellipse$path`
## -----


library(PlaneGeometry)
ell <- Ellipse$new(c(1, -1), rmajor = 3, rminor = 2, alpha = 30)
innerPath <- ell$path(npoints = 10)
outerPath <- ell$path(npoints = 10, outer = TRUE)
bbox <- ell$boundingbox()
plot(NULL, asp = 1, xlim = bbox$x, ylim = bbox$y, xlab = NA, ylab = NA)
draw(ell, border = "red", lty = "dashed")
polygon(innerPath, border = "blue", lwd = 2)
polygon(outerPath, border = "green", lwd = 2)

## -----
## Method `Ellipse$diameter`
## -----


ell <- Ellipse$new(c(1,1), 5, 2, 30)
diameters <- lapply(c(0, pi/3, 2*pi/3), ell$diameter)
plot(NULL, asp = 1, xlim = c(-4,6), ylim = c(-2,4),
     xlab = NA, ylab = NA)
draw(ell)
invisible(lapply(diameters, draw))

## -----
## Method `Ellipse$tangent`
## -----


ell <- Ellipse$new(c(1,1), 5, 2, 30)
tangents <- lapply(c(0, pi/3, 2*pi/3, pi, 4*pi/3, 5*pi/3), ell$tangent)
plot(NULL, asp = 1, xlim = c(-4,6), ylim = c(-2,4),
     xlab = NA, ylab = NA)
draw(ell, col = "yellow")

```

```

invisible(lapply(tangents, draw, col = "blue"))

## -----
## Method `Ellipse$normal`
## -----


ell <- Ellipse$new(c(1,1), 5, 2, 30)
t_ <- seq(0, 2*pi, length.out = 13)[-1]
plot(NULL, asp = 1, xlim = c(-5,7), ylim = c(-3,5),
     xlab = NA, ylab = NA)
draw(ell, col = "magenta")
for(i in 1:length(t_)){
  t <- t_[i]
  P <- ell$pointFromEccentricAngle(t)
  v <- ell$normal(t)
  draw(Line$new(P, P+v, FALSE, FALSE))
}

## -----
## Method `Ellipse$theta2t`
## -----


O <- c(1, 1)
ell <- Ellipse$new(O, 5, 2, 30)
theta <- 20
P <- ell$pointFromAngle(theta)
t <- ell$theta2t(theta)
tg <- ell$tangent(t)
OP <- Line$new(O, P, FALSE, FALSE)
plot(NULL, asp = 1, xlim = c(-4,6), ylim = c(-2,5),
      xlab = NA, ylab = NA)
draw(ell, col = "antiquewhite")
points(P[1], P[2], pch = 19)
draw(tg, col = "red")
draw(OP)
draw(ell$semiMajorAxis())
text(t(0+c(1,0.9)), expression(theta))

## -----
## Method `Ellipse$regressionLines`
## -----


ell <- Ellipse$new(c(1,1), 5, 2, 30)
reglines <- ell$regressionLines()
plot(NULL, asp = 1, xlim = c(-4,6), ylim = c(-2,4),
     xlab = NA, ylab = NA)
draw(ell, lwd = 2)
draw(reglines$YonX, lwd = 2, col = "blue")
draw(reglines$XonY, lwd = 2, col = "green")

## -----
## Method `Ellipse$boundingbox`
## -----

```

```

ell <- Ellipse$new(c(2,2), 5, 3, 40)
box <- ell$boundingbox()
plot(NULL, asp = 1, xlim = box$x, ylim = box$y, xlab = NA, ylab = NA)
draw(ell, col = "seaShell", border = "blue")
abline(v = box$x, lty = 2); abline(h = box$y, lty = 2)

## -----
## Method `Ellipse$randomPoints`
## -----


ell <- Ellipse$new(c(1,1), 5, 2, 30)
pts <- ell$randomPoints(100)
plot(NULL, type="n", asp=1, xlim = c(-4,6), ylim = c(-2,4),
      xlab = NA, ylab = NA)
draw(ell, lwd = 2)
points(pts, pch = 19, col = "blue")

```

EllipseEquationFromFivePoints*Ellipse equation from five points***Description**

The coefficients of the implicit equation of an ellipse from five points on this ellipse.

Usage

```
EllipseEquationFromFivePoints(P1, P2, P3, P4, P5)
```

Arguments

P1, P2, P3, P4, P5
the five points

Details

The implicit equation of the ellipse is $Ax^2 + Bxy + Cy^2 + Dx + Ey + F = 0$. This function returns A, B, C, D, E and F.

Value

A named numeric vector.

Examples

```
ell <- Ellipse$new(c(2,3), 5, 4, 30)
set.seed(666)
pts <- ell$randomPoints(5, "on")
cf1 <- EllipseEquationFromFivePoints(pts[1,],pts[2,],pts[3,],pts[4,],pts[5,])
cf2 <- ell$equation() # should be the same up to a multiplicative factor
all.equal(cf1/cf1["F"], cf2/cf2["F"])
```

EllipseFromCenterAndMatrix

Ellipse from center and matrix

Description

Returns the ellipse of equation $t(X\text{-center}) \%*\% S \%*\% (X\text{-center}) = 1$.

Usage

```
EllipseFromCenterAndMatrix(center, S)
```

Arguments

| | |
|--------|------------------------------------|
| center | a point, the center of the ellipse |
| S | a positive symmetric matrix |

Value

An `Ellipse` object.

Examples

```
ell <- Ellipse$new(c(2,3), 4, 2, 20)
S <- ell$matrix()
EllipseFromCenterAndMatrix(ell$center, S)
```

EllipseFromEquation *Ellipse from its implicit equation*

Description

Return an ellipse from the coefficients of its implicit equation.

Usage

```
EllipseFromEquation(A, B, C, D, E, F)
```

Arguments

A, B, C, D, E, F the coefficients of the equation

Details

The implicit equation of the ellipse is $Ax^2 + Bxy + Cy^2 + Dx + Ey + F = 0$. This function returns the ellipse given A, B, C, D, E and F.

Value

An Ellipse object.

Examples

```
ell <- Ellipse$new(c(2,3), 5, 4, 30)
cf <- ell$equation()
ell2 <- EllipseFromEquation(cf[1], cf[2], cf[3], cf[4], cf[5], cf[6])
ell$isEqual(ell2)
```

EllipseFromFivePoints *Ellipse from five points*

Description

Return an ellipse from five given points on this ellipse.

Usage

`EllipseFromFivePoints(P1, P2, P3, P4, P5)`

Arguments

P1, P2, P3, P4, P5
the five points

Value

An Ellipse object.

Examples

```
ell <- Ellipse$new(c(2,3), 5, 4, 30)
set.seed(666)
pts <- ell$randomPoints(5, "on")
ell2 <- EllipseFromFivePoints(pts[1,], pts[2,], pts[3,], pts[4,], pts[5,])
ell$isEqual(ell2)
```

EllipseFromFociAndOnePoint*Ellipse from foci and one point***Description**

Derive the ellipse with given foci and one point on the boundary.

Usage

```
EllipseFromFociAndOnePoint(F1, F2, P)
```

Arguments

| | |
|--------|--|
| F1, F2 | points, the foci |
| P | a point on the boundary of the ellipse |

Value

An Ellipse object.

EllipseFromThreeBoundaryPoints*Smallest ellipse that passes through three boundary points***Description**

Returns the smallest area ellipse which passes through three given boundary points.

Usage

```
EllipseFromThreeBoundaryPoints(P1, P2, P3)
```

Arguments

| | |
|------------|----------------------------|
| P1, P2, P3 | three non-collinear points |
|------------|----------------------------|

Value

An Ellipse object.

Examples

```
P1 <- c(-1,0); P2 <- c(0, 2); P3 <- c(3,0)
ell <- EllipseFromThreeBoundaryPoints(P1, P2, P3)
ell$includes(P1); ell$includes(P2); ell$includes(P3)
```

EllipticalArc *R6 class representing an elliptical arc*

Description

An arc is given by an ellipse (Ellipse object), a starting angle and an ending angle. They are respectively named ell, alpha1 and alpha2.

Active bindings

ell get or set the ellipse
alpha1 get or set the starting angle
alpha2 get or set the ending angle
degrees get or set the degrees field

Methods

Public methods:

- [EllipticalArc\\$new\(\)](#)
- [EllipticalArc\\$print\(\)](#)
- [EllipticalArc\\$startingPoint\(\)](#)
- [EllipticalArc\\$endingPoint\(\)](#)
- [EllipticalArc\\$isEqual\(\)](#)
- [EllipticalArc\\$complementaryArc\(\)](#)
- [EllipticalArc\\$path\(\)](#)
- [EllipticalArc\\$length\(\)](#)
- [EllipticalArc\\$clone\(\)](#)

Method new(): Create a new EllipticalArc object.

Usage:

```
EllipticalArc$new(ell, alpha1, alpha2, degrees = TRUE)
```

Arguments:

ell the ellipse
alpha1 the starting angle
alpha2 the ending angle
degrees logical, whether alpha1 and alpha2 are given in degrees

Returns: A new EllipticalArc object.

Examples:

```
ell <- Ellipse$new(c(-4,0), 4, 2.5, 140)  
EllipticalArc$new(ell, 45, 90)
```

Method print(): Show instance of an EllipticalArc object.

Usage:

`EllipticalArc$print(...)`

Arguments:

... ignored

Method `startingPoint()`: Starting point of the reference elliptical arc.

Usage:

`EllipticalArc$startingPoint()`

Method `endingPoint()`: Ending point of the reference elliptical arc.

Usage:

`EllipticalArc$endingPoint()`

Method `isEqual()`: Check whether the reference elliptical arc equals another elliptical arc.

Usage:

`EllipticalArc$isEqual(arc)`

Arguments:

`arc` an `EllipticalArc` object

Method `complementaryArc()`: Complementary elliptical arc of the reference elliptical arc.

Usage:

`EllipticalArc$complementaryArc()`

Examples:

```
ell <- Ellipse$new(c(-4,0), 4, 2.5, 140)
arc <- EllipticalArc$new(ell, 30, 60)
plot(NULL, type = "n", asp = 1, xlim = c(-8,0), ylim = c(-3.2,3.2),
      xlab = NA, ylab = NA)
draw(arc, lwd = 3, col = "red")
draw(arc$complementaryArc(), lwd = 3, col = "green")
```

Method `path()`: The reference elliptical arc as a path.

Usage:

`EllipticalArc$path(npoints = 100L)`

Arguments:

`npoints` number of points of the path

Returns: A matrix with two columns `x` and `y` of length `npoints`.

Method `length()`: The length of the elliptical arc.

Usage:

`EllipticalArc$length()`

Returns: A number, the arc length.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`EllipticalArc$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Examples

```
## -----
## Method `EllipticalArc$new`
## -----

ell <- Ellipse$new(c(-4,0), 4, 2.5, 140)
EllipticalArc$new(ell, 45, 90)

## -----
## Method `EllipticalArc$complementaryArc`
## -----

ell <- Ellipse$new(c(-4,0), 4, 2.5, 140)
arc <- EllipticalArc$new(ell, 30, 60)
plot(NULL, type = "n", asp = 1, xlim = c(-8,0), ylim = c(-3.2,3.2),
     xlab = NA, ylab = NA)
draw(arc, lwd = 3, col = "red")
draw(arc$complementaryArc(), lwd = 3, col = "green")
```

fitEllipse

Fit an ellipse

Description

Fit an ellipse to a set of points.

Usage

```
fitEllipse(points)
```

Arguments

| | |
|--------|--|
| points | numeric matrix with two columns, one point per row |
|--------|--|

Value

An `Ellipse` object representing the fitted ellipse. The residual sum of squares is given in the `RSS` attribute.

Examples

```
library(PlaneGeometry)
# We add some noise to 30 points on an ellipse:
ell <- Ellipse$new(c(1, 1), 3, 2, 30)
set.seed(666L)
points <- ell$randomPoints(30, "on") + matrix(rnorm(30*2, sd = 0.2), ncol = 2)
# Now we fit an ellipse to these points:
ellFitted <- fitEllipse(points)
```

```
# let's draw all this stuff:
box <- ell$boundingbox()
plot(NULL, asp = 1, xlim = box$x, ylim = box$y, xlab = NA, ylab = NA)
draw(ell, border = "blue", lwd = 2)
points(points, pch = 19)
draw(ellFitted, border = "green", lwd = 2)
```

GaussianEllipse

*Gaussian ellipse***Description**

Return the ellipse equal to the highest *pdf* region of a bivariate Gaussian distribution with a given probability.

Usage

```
GaussianEllipse(mean, Sigma, p)
```

Arguments

| | |
|--------------------|--|
| <code>mean</code> | numeric vector of length 2, the mean of the bivariate Gaussian distribution; this is the center of the ellipse |
| <code>Sigma</code> | covariance matrix of the bivariate Gaussian distribution |
| <code>p</code> | desired probability level, a number between 0 and 1 (strictly) |

Value

An Ellipse object.

Homothety

*R6 class representing a homothety***Description**

A homothety is given by a center and a scale factor.

Active bindings

```
center  get or set the center
scale   get or set the scale factor of the homothety
```

Methods

Public methods:

- `Homothety$new()`
- `Homothety$print()`
- `Homothety$transform()`
- `Homothety$transformCircle()`
- `Homothety$getMatrix()`
- `Homothety$asAffine()`
- `Homothety$clone()`

Method `new()`: Create a new Homothety object.

Usage:

```
Homothety$new(center, scale)
```

Arguments:

`center` a point, the center of the homothety
`scale` a number, the scale factor of the homothety

Returns: A new Homothety object.

Examples:

```
Homothety$new(c(1,1), 2)
```

Method `print()`: Show instance of a Homothety object.

Usage:

```
Homothety$print(...)
```

Arguments:

... ignored

Method `transform()`: Transform a point or several points by the reference homothety.

Usage:

```
Homothety$transform(M)
```

Arguments:

`M` a point or a two-column matrix of points, one point per row

Method `transformCircle()`: Transform a circle by the reference homothety.

Usage:

```
Homothety$transformCircle(circ)
```

Arguments:

`circ` a Circle object

Returns: A Circle object.

Method `getMatrix()`: Augmented matrix of the homothety.

Usage:

```
Homothety$getMatrix()
```

Returns: A 3x3 matrix.

Examples:

```
H <- Homothety$new(c(1,1), 2)
P <- c(1,5)
H$transform(P)
H$getMatrix() %*% c(P,1)
```

Method `asAffine()`: Convert the reference homothety to an Affine object.

Usage:

```
Homothety$asAffine()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Homothety$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
## -----
## Method `Homothety$new`
## -----
Homothety$new(c(1,1), 2)

## -----
## Method `Homothety$getMatrix`
## -----
H <- Homothety$new(c(1,1), 2)
P <- c(1,5)
H$transform(P)
H$getMatrix() %*% c(P,1)
```

Description

A hyperbola is given by two intersecting asymptotes, named `L1` and `L2`, and a point on this hyperbola, named `M`.

Active bindings

- L1 get or set the asymptote L1
- L2 get or set the asymptote L2
- M get or set the point M

Methods

Public methods:

- Hyperbola\$new()
- Hyperbola\$center()
- Hyperbola\$OAB()
- Hyperbola\$vertices()
- Hyperbola\$abce()
- Hyperbola\$foci()
- Hyperbola\$plot()
- Hyperbola\$includes()
- Hyperbola\$equation()
- Hyperbola\$clone()

Method new(): Create a new Hyperbola object.

Usage:

```
Hyperbola$new(L1, L2, M)
```

Arguments:

L1, L2 two intersecting lines given as Line objects, the asymptotes

M a point on the hyperbola

Returns: A new Hyperbola object.

Method center(): Center of the hyperbola.

Usage:

```
Hyperbola$center()
```

Returns: The center of the hyperbola, i.e. the point where the two asymptotes meet each other.

Method OAB(): Parametric equation $O \pm \cosh(t)A + \sinh(t)B$ representing the hyperbola.

Usage:

```
Hyperbola$OAB()
```

Returns: The point O and the two vectors A and B in a list.

Examples:

```
L1 <- LineFromInterceptAndSlope(0, 2)
L2 <- LineFromInterceptAndSlope(-2, -0.5)
M <- c(4, 3)
hyperbola <- Hyperbola$new(L1, L2, M)
hyperbola$OAB()
```

Method vertices(): Vertices of the hyperbola.

Usage:

```
Hyperbola$vertices()
```

Returns: The two vertices V1 and V2 in a list.

Method abce(): The numbers a (semi-major axis, i.e. distance from center to vertex), b (semi-minor axis), c (linear eccentricity) and e (eccentricity) associated to the hyperbola.

Usage:

```
Hyperbola$abce()
```

Returns: The four numbers a, b, c and e in a list.

Method foci(): Foci of the hyperbola.

Usage:

```
Hyperbola$foci()
```

Returns: The two foci F1 and F2 in a list.

Method plot(): Plot hyperbola.

Usage:

```
Hyperbola$plot(add = FALSE, ...)
```

Arguments:

add Boolean, whether to add this plot to the current plot

... named arguments passed to `lines`

Returns: Nothing, called for plotting.

Examples:

```
L1 <- LineFromInterceptAndSlope(0, 2)
L2 <- LineFromInterceptAndSlope(-2, -0.5)
M <- c(4, 3)
hyperbola <- Hyperbola$new(L1, L2, M)
plot(hyperbola, lwd = 2)
points(t(M), pch = 19, col = "blue")
O <- hyperbola$center()
points(t(O), pch = 19)
draw(L1, col = "red")
draw(L2, col = "red")
vertices <- hyperbola$vertices()
points(rbind(vertices$V1, vertices$V2), pch = 19)
majorAxis <- Line$new(vertices$V1, vertices$V2)
draw(majorAxis, lty = "dashed")
foci <- hyperbola$foci()
points(rbind(foci$F1, foci$F2), pch = 19, col = "green")
```

Method includes(): Whether a point belongs to the hyperbola.

Usage:

```
Hyperbola$includes(P)
```

Arguments:

P a point

Returns: A Boolean value.

Examples:

```
L1 <- LineFromInterceptAndSlope(0, 2)
L2 <- LineFromInterceptAndSlope(-2, -0.5)
M <- c(4, 3)
hyperbola <- Hyperbola$new(L1, L2, M)
hyperbola$includes(M)
```

Method equation(): Implicit quadratic equation of the hyperbola $A_{xx}x^2 + 2A_{xy}xy + A_{yy}y^2 + 2B_x x + 2B_y y + C = 0$

Usage:

```
Hyperbola$equation()
```

Returns: The coefficients of the equation in a named list.

Examples:

```
L1 <- LineFromInterceptAndSlope(0, 2)
L2 <- LineFromInterceptAndSlope(-2, -0.5)
M <- c(4, 3)
hyperbola <- Hyperbola$new(L1, L2, M)
eq <- hyperbola$equation()
x <- M[1]; y <- M[2]
with(eq, Axx*x^2 + 2*Axy*x*y + Ayy*y^2 + 2*Bx*x + 2*By*y + C)
V1 <- hyperbola$vertices()$V1
x <- V1[1]; y <- V1[2]
with(eq, Axx*x^2 + 2*Axy*x*y + Ayy*y^2 + 2*Bx*x + 2*By*y + C)
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
Hyperbola$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `Hyperbola$OAB`
## -----
L1 <- LineFromInterceptAndSlope(0, 2)
L2 <- LineFromInterceptAndSlope(-2, -0.5)
M <- c(4, 3)
hyperbola <- Hyperbola$new(L1, L2, M)
hyperbola$OAB()
```

```

## -----
## Method `Hyperbola$plot`
## -----


L1 <- LineFromInterceptAndSlope(0, 2)
L2 <- LineFromInterceptAndSlope(-2, -0.5)
M <- c(4, 3)
hyperbola <- Hyperbola$new(L1, L2, M)
plot(hyperbola, lwd = 2)
points(t(M), pch = 19, col = "blue")
O <- hyperbola$center()
points(t(O), pch = 19)
draw(L1, col = "red")
draw(L2, col = "red")
vertices <- hyperbola$vertices()
points(rbind(vertices$V1, vertices$V2), pch = 19)
majorAxis <- Line$new(vertices$V1, vertices$V2)
draw(majorAxis, lty = "dashed")
foci <- hyperbola$foci()
points(rbind(foci$F1, foci$F2), pch = 19, col = "green")

## -----
## Method `Hyperbola$includes`
## -----


L1 <- LineFromInterceptAndSlope(0, 2)
L2 <- LineFromInterceptAndSlope(-2, -0.5)
M <- c(4, 3)
hyperbola <- Hyperbola$new(L1, L2, M)
hyperbola$includes(M)

## -----
## Method `Hyperbola$equation`
## -----


L1 <- LineFromInterceptAndSlope(0, 2)
L2 <- LineFromInterceptAndSlope(-2, -0.5)
M <- c(4, 3)
hyperbola <- Hyperbola$new(L1, L2, M)
eq <- hyperbola$equation()
x <- M[1]; y <- M[2]
with(eq, Axx*x^2 + 2*Axy*x*y + Ayy*y^2 + 2*Bx*x + 2*By*y + C)
V1 <- hyperbola$vertices()$V1
x <- V1[1]; y <- V1[2]
with(eq, Axx*x^2 + 2*Axy*x*y + Ayy*y^2 + 2*Bx*x + 2*By*y + C)

```

`HyperbolaFromEquation` *Hyperbola object from the hyperbola equation.*

Description

Create the `Hyperbola` object representing the hyperbola with the given implicit equation.

Usage

```
HyperbolaFromEquation(eq)
```

Arguments

eq named vector or list of the six parameters Axx, Axy, Ayy, Bx, By, C

Value

A Hyperbola object.

intersectionCircleCircle

Intersection of two circles

Description

Return the intersection of two circles.

Usage

```
intersectionCircleCircle(circ1, circ2, epsilon = sqrt(.Machine$double.eps))
```

Arguments

circ1, circ2 two Circle objects

epsilon a small positive number used for the numerical accuracy

Value

NULL if there is no intersection, a point if the circles touch, a list of two points if the circles meet at two points, a circle if the two circles are identical.

intersectionCircleLine

Intersection of a circle and a line

Description

Return the intersection of a circle and a line.

Usage

```
intersectionCircleLine(circ, line, strict = FALSE)
```

Arguments

| | |
|---------------------|---|
| <code>circ</code> | a Circle object |
| <code>line</code> | a Line object |
| <code>strict</code> | logical, whether to take into account <code>line\$extendA</code> and <code>line\$extendB</code> if they are not both TRUE |

Value

NULL if there is no intersection; a point if the infinite line is tangent to the circle, or NULL if `strict=TRUE` and the point is not on the line (segment or half-line); a list of two points if the circle and the infinite line meet at two points, when `strict=FALSE`; if `strict=TRUE` and the line is a segment or a half-line, this can return NULL or a single point.

Examples

```
circ <- Circle$new(c(1,1), 2)
line <- Line$new(c(2,-2), c(1,2), FALSE, FALSE)
intersectionCircleLine(circ, line)
intersectionCircleLine(circ, line, strict = TRUE)
```

intersectionEllipseLine

Intersection of an ellipse and a line

Description

Return the intersection of an ellipse and a line.

Usage

```
intersectionEllipseLine(ell, line, strict = FALSE)
```

Arguments

| | |
|---------------------|---|
| <code>ell</code> | an Ellipse object or a Circle object |
| <code>line</code> | a Line object |
| <code>strict</code> | logical, whether to take into account <code>line\$extendA</code> and <code>line\$extendB</code> if they are not both TRUE |

Value

NULL if there is no intersection; a point if the infinite line is tangent to the ellipse, or NULL if `strict=TRUE` and the point is not on the line (segment or half-line); a list of two points if the ellipse and the infinite line meet at two points, when `strict=FALSE`; if `strict=TRUE` and the line is a segment or a half-line, this can return NULL or a single point.

Examples

```
ell <- Ellipse$new(c(1,1), 5, 1, 30)
line <- Line$new(c(2,-2), c(0,4))
( Is <- intersectionEllipseLine(ell, line) )
ell$includes(Is$I1); ell$includes(Is$I2)
```

`intersectionLineLine` *Intersection of two lines*

Description

Return the intersection of two lines.

Usage

```
intersectionLineLine(line1, line2, strict = FALSE)
```

Arguments

| | |
|---------------------------|---|
| <code>line1, line2</code> | two <code>Line</code> objects |
| <code>strict</code> | logical, whether to take into account the extensions of the lines (<code>extendA</code> and <code>extendB</code>) |

Value

If `strict = FALSE` this returns either a point, or `NULL` if the lines are parallel, or a bi-infinite line if the two lines coincide. If `strict = TRUE`, this can also return a half-infinite line or a segment.

`Inversion`

R6 class representing an inversion

Description

An inversion is given by a pole (a point) and a power (a number, possibly negative, but not zero).

Active bindings

| | |
|--------------------|----------------------|
| <code>pole</code> | get or set the pole |
| <code>power</code> | get or set the power |

Methods

Public methods:

- `Inversion$new()`
- `Inversion$print()`
- `Inversion$invert()`
- `Inversion$transform()`
- `Inversion$invertCircle()`
- `Inversion$transformCircle()`
- `Inversion$invertLine()`
- `Inversion$transformLine()`
- `Inversion$invertGcircle()`
- `Inversion$compose()`
- `Inversion$clone()`

Method `new()`: Create a new Inversion object.

Usage:

`Inversion$new(pole, power)`

Arguments:

`pole` the pole

`power` the power

Returns: A new Inversion object.

Method `print()`: Show instance of an inversion object.

Usage:

`Inversion$print(...)`

Arguments:

`...` ignored

Examples:

`Inversion$new(c(0,0), 2)`

Method `invert()`: Inversion of a point.

Usage:

`Inversion$invert(M)`

Arguments:

`M` a point or Inf

Returns: A point or Inf, the image of M.

Method `transform()`: An alias of invert.

Usage:

`Inversion$transform(M)`

Arguments:

`M` a point or `Inf`

Returns: A point or `Inf`, the image of `M`.

Method `invertCircle()`: Inversion of a circle.

Usage:

`Inversion$invertCircle(circ)`

Arguments:

`circ` a `Circle` object

Returns: A `Circle` object or a `Line` object.

Examples:

```
# A Pappus chain
# https://www.cut-the-knot.org/Curriculum/Geometry/InversionInArbelos.shtml
opar <- par(mar = c(0,0,0,0))
plot(0, 0, type = "n", asp = 1, xlim = c(0,6), ylim = c(-4,4),
     xlab = NA, ylab = NA, axes = FALSE)
A <- c(0,0); B <- c(6,0)
ABsqr <- c(crossprod(A-B))
iota <- Inversion$new(A, ABsqr)
C <- iota$invert(c(8,0))
Sigma1 <- Circle$new((A+B)/2, sqrt(ABsqr)/2)
Sigma2 <- Circle$new((A+C)/2, sqrt(c(crossprod(A-C)))/2)
draw(Sigma1); draw(Sigma2)
circ0 <- Circle$new(c(7,0), 1)
iotacirc0 <- iota$invertCircle(circ0)
draw(iotacirc0)
for(i in 1:6){
  circ <- circ0$translate(c(0,2*i))
  iotacirc <- iota$invertCircle(circ)
  draw(iotacirc)
  circ <- circ0$translate(c(0,-2*i))
  iotacirc <- iota$invertCircle(circ)
  draw(iotacirc)
}
par(opar)
```

Method `transformCircle()`: An alias of `invertCircle`.

Usage:

`Inversion$transformCircle(circ)`

Arguments:

`circ` a `Circle` object

Returns: A `Circle` object or a `Line` object.

Method `invertLine()`: Inversion of a line.

Usage:

`Inversion$invertLine(line)`

Arguments:

line a Line object

Returns: A Circle object or a Line object.

Method transformLine(): An alias of invertLine.

Usage:

Inversion\$transformLine(line)

Arguments:

line a Line object

Returns: A Circle object or a Line object.

Method invertGcircle(): Inversion of a generalized circle (i.e. a circle or a line).

Usage:

Inversion\$invertGcircle(gcircle)

Arguments:

gcircle a Circle object or a Line object

Returns: A Circle object or a Line object.

Method compose(): Compose the reference inversion with another inversion. The result is a Möbius transformation.

Usage:

Inversion\$compose(iota1, left = TRUE)

Arguments:

iota1 an Inversion object

left logical, whether to compose at left or at right (i.e. returns iota1 o iota0 or iota0 o iota1)

Returns: A Mobius object.

Method clone(): The objects of this class are cloneable with this method.

Usage:

Inversion\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

See Also

[inversionSwappingTwoCircles](#), [inversionFixingTwoCircles](#), [inversionFixingThreeCircles](#) to create some inversions.

Examples

```
## -----
## Method `Inversion$print`
## -----
Inversion$new(c(0,0), 2)

## -----
## Method `Inversion$insertCircle`
## -----


# A Pappus chain
# https://www.cut-the-knot.org/Curriculum/Geometry/InversionInArbelos.shtml
opar <- par(mar = c(0,0,0,0))
plot(0, 0, type = "n", asp = 1, xlim = c(0,6), ylim = c(-4,4),
     xlab = NA, ylab = NA, axes = FALSE)
A <- c(0,0); B <- c(6,0)
ABsqr <- c(crossprod(A-B))
iota <- Inversion$new(A, ABsqr)
C <- iota$invert(c(8,0))
Sigma1 <- Circle$new((A+B)/2, sqrt(ABsqr)/2)
Sigma2 <- Circle$new((A+C)/2, sqrt(c(crossprod(A-C)))/2)
draw(Sigma1); draw(Sigma2)
circ0 <- Circle$new(c(7,0), 1)
iotacirc0 <- iota$invertCircle(circ0)
draw(iotacirc0)
for(i in 1:6){
  circ <- circ0$translate(c(0,2*i))
  iotacirc <- iota$invertCircle(circ)
  draw(iotacirc)
  circ <- circ0$translate(c(0,-2*i))
  iotacirc <- iota$invertCircle(circ)
  draw(iotacirc)
}
par(opar)
```

inversionFixingThreeCircles

Inversion fixing three circles

Description

Return the inversion which lets invariant three given circles.

Usage

```
inversionFixingThreeCircles(circ1, circ2, circ3)
```

Arguments

`circ1, circ2, circ3`
Circle objects

Value

An Inversion object, which lets each of `circ1`, `circ2` and `circ3` invariant.

inversionFixingTwoCircles

Inversion fixing two circles

Description

Return the inversion which lets invariant two given circles.

Usage

`inversionFixingTwoCircles(circ1, circ2)`

Arguments

`circ1, circ2` Circle objects

Value

An Inversion object, which maps `circ1` to `circ2` and `circ2` to `circ1`.

inversionFromCircle *Inversion on a circle*

Description

Return the inversion on a given circle.

Usage

`inversionFromCircle(circ)`

Arguments

`circ` a Circle object

Value

An Inversion object

```
inversionKeepingCircle
```

Inversion keeping a circle unchanged

Description

Return an inversion with a given pole which keeps a given circle unchanged.

Usage

```
inversionKeepingCircle(pole, circ)
```

Arguments

| | |
|------|-------------------------|
| pole | inversion pole, a point |
| circ | a Circle object |

Value

An Inversion object.

Examples

```
circ <- Circle$new(c(4,3), 2)
iota <- inversionKeepingCircle(c(1,2), circ)
iota$transformCircle(circ)
```

```
inversionSwappingTwoCircles
```

Inversion swapping two circles

Description

Return the inversion which swaps two given circles.

Usage

```
inversionSwappingTwoCircles(circ1, circ2, positive = TRUE)
```

Arguments

| | |
|--------------|---|
| circ1, circ2 | Circle objects |
| positive | logical, whether the sign of the desired inversion power must be positive or negative |

Value

An Inversion object, which maps `circ1` to `circ2` and `circ2` to `circ1`, except in the case when `circ1` and `circ2` are congruent and tangent: in this case a Reflection object is returned (a reflection is an inversion on a line).

Line

*R6 class representing a line***Description**

A line is given by two distinct points, named A and B, and two logical values `extendA` and `extendB`, indicating whether the line must be extended beyond A and B respectively. Depending on `extendA` and `extendB`, the line is an infinite line, a half-line, or a segment.

Active bindings

- A get or set the point A
- B get or set the point B
- `extendA` get or set `extendA`
- `extendB` get or set `extendB`

Methods**Public methods:**

- `Line$new()`
- `Line$print()`
- `Line$length()`
- `Line$directionAndOffset()`
- `Line$isEqual()`
- `Line$isParallel()`
- `Line$isPerpendicular()`
- `Line$includes()`
- `Line$perpendicular()`
- `Line$parallel()`
- `Line$projection()`
- `Line$distance()`
- `Line$reflection()`
- `Line$rotate()`
- `Line$translate()`
- `Line$invert()`
- `Line$clone()`

Method `new():` Create a new Line object.

Usage:

```
Line$new(A, B, extendA = TRUE, extendB = TRUE)
```

Arguments:

A, B points

extendA, extendB logical values

Returns: A new Line object.

Examples:

```
l <- Line$new(c(1,1), c(1.5,1.5), FALSE, TRUE)
l
l$A
l$A <- c(0,0)
l
```

Method print(): Show instance of a line object.

Usage:

```
Line$print(...)
```

Arguments:

... ignored

Examples:

```
Line$new(c(0,0), c(1,0), FALSE, TRUE)
```

Method length(): Segment length, returns the length of the segment joining the two points defining the line.

Usage:

```
Line$length()
```

Method directionAndOffset(): Direction (angle between 0 and 2pi) and offset (positive number) of the reference line.

Usage:

```
Line$directionAndOffset()
```

Details: The equation of the line is $\cos(\theta)x + \sin(\theta)y = d$ where θ is the direction and d is the offset.

Method isEqual(): Check whether the reference line equals a given line, without taking into account extendA and extendB.

Usage:

```
Line$isEqual(line)
```

Arguments:

line a Line object

Returns: TRUE or FALSE.

Method isParallel(): Check whether the reference line is parallel to a given line.

Usage:

`Line$isParallel(line)`

Arguments:

`line` a `Line` object

Returns: TRUE or FALSE.

Method `isPerpendicular()`: Check whether the reference line is perpendicular to a given line.

Usage:

`Line$isPerpendicular(line)`

Arguments:

`line` a `Line` object

Returns: TRUE or FALSE.

Method `includes()`: Whether a point belongs to the reference line.

Usage:

`Line$includes(M, strict = FALSE, checkCollinear = TRUE)`

Arguments:

`M` the point for which we want to test whether it belongs to the line

`strict` logical, whether to take into account `extendA` and `extendB`

`checkCollinear` logical, whether to check the collinearity of A, B, M; set to FALSE only if you are sure that M is on the line (AB) in case if you use `strict=TRUE`

Returns: TRUE or FALSE.

Examples:

```
A <- c(0,0); B <- c(1,2); M <- c(3,6)
```

```
l <- Line$new(A, B, FALSE, FALSE)
```

```
l$includes(M, strict = TRUE)
```

Method `perpendicular()`: Perpendicular line passing through a given point.

Usage:

`Line$perpendicular(M, extendH = FALSE, extendM = TRUE)`

Arguments:

`M` the point through which the perpendicular passes.

`extendH` logical, whether to extend the perpendicular line beyond the meeting point

`extendM` logical, whether to extend the perpendicular line beyond the point M

Returns: A `Line` object; its two points are the meeting point and the point M.

Method `parallel()`: Parallel to the reference line passing through a given point.

Usage:

`Line$parallel(M)`

Arguments:

`M` a point

Returns: A `Line` object.

Method `projection()`: Orthogonal projection of a point to the reference line.

Usage:

`Line$projection(M)`

Arguments:

`M` a point

Returns: A point.

Method `distance()`: Distance from a point to the reference line.

Usage:

`Line$distance(M)`

Arguments:

`M` a point

Returns: A positive number.

Method `reflection()`: Reflection of a point with respect to the reference line.

Usage:

`Line$reflection(M)`

Arguments:

`M` a point

Returns: A point.

Method `rotate()`: Rotate the reference line.

Usage:

`Line$rotate(alpha, 0, degrees = TRUE)`

Arguments:

`alpha` angle of rotation

`0` center of rotation

`degrees` logical, whether alpha is given in degrees

Returns: A Line object.

Method `translate()`: Translate the reference line.

Usage:

`Line$translate(v)`

Arguments:

`v` the vector of translation

Returns: A Line object.

Method `invert()`: Invert the reference line.

Usage:

`Line$invert(inversion)`

Arguments:

`inversion` an Inversion object

Returns: A Circle object or a Line object.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`Line$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Examples

```
## -----
## Method `Line$new`
## -----
```

```
l <- Line$new(c(1,1), c(1.5,1.5), FALSE, TRUE)
l
l$A
l$A <- c(0,0)
l

## -----
## Method `Line$print`
## -----
```

```
Line$new(c(0,0), c(1,0), FALSE, TRUE)

## -----
## Method `Line$includes`
## -----
```

```
A <- c(0,0); B <- c(1,2); M <- c(3,6)
l <- Line$new(A, B, FALSE, FALSE)
l$includes(M, strict = TRUE)
```

Description

Create a Line object representing the infinite line with given equation $ax + by + c = 0$.

Usage

`LineFromEquation(a, b, c)`

Arguments

a, b, c the parameters of the equation; a and b cannot be both zero

Value

A Line object.

LineFromInterceptAndSlope

Line from intercept and slope

Description

Create a Line object representing the infinite line with given intercept and given slope.

Usage

`LineFromInterceptAndSlope(a, b)`

Arguments

a intercept
b slope

Value

A Line object.

LownerJohnEllipse

Löwner-John ellipse (ellipse hull)

Description

Minimum area ellipse containing a set of points.

Usage

`LownerJohnEllipse(pts)`

Arguments

pts the points in a two-columns matrix (one point per row); at least three distinct points

Value

An Ellipse object.

Examples

```
pts <- cbind(rnorm(30, sd=2), rnorm(30))
ell <- LownerJohnEllipse(pts)
box <- ell$boundingbox()
plot(NULL, asp = 1, xlim = box$x, ylim = box$y, xlab = NA, ylab = NA)
draw(ell, col = "seaShell")
points(pts, pch = 19)
all(apply(pts, 1, ell$contains)) # should be TRUE
```

maxAreaInscribedCircle

Maximum area circle inscribed in a convex polygon

Description

Computes the circle inscribed in a convex polygon with maximum area. This is the so-called *Chebyshev circle*.

Usage

```
maxAreaInscribedCircle(points, verbose = FALSE)
```

Arguments

| | |
|---------|--|
| points | the vertices of the polygon in a two-columns matrix; their order has no importance, since the procedure takes the convex hull of these points (and does not check the convexity) |
| verbose | argument passed to psolve |

Value

A Circle object. The status of the optimization problem is given as an attribute of this circle. A warning is thrown if it is not optimal.

See Also

[maxAreaInscribedEllipse](#)

Examples

```
library(PlaneGeometry)
hexagon <- rbind(
  c(-1.7, -1),
  c(-1.4, 0.4),
  c(0.3, 1.3),
  c(1.7, 0.6),
  c(1.3, -0.3),
  c(-0.4, -1.8)
)
opar <- par(mar = c(2, 2, 1, 1))
plot(NULL, xlim=c(-2, 2), ylim=c(-2, 2), xlab = NA, ylab = NA, asp = 1)
points(hexagon, pch = 19)
polygon(hexagon)
circ <- maxAreaInscribedCircle(hexagon)
draw(circ, col = "yellow2", border = "blue", lwd = 2)
par(opar)
# check optimization status:
attr(circ, "status")
```

maxAreaInscribedEllipse

Maximum area ellipse inscribed in a convex polygon

Description

Computes the ellipse inscribed in a convex polygon with maximum area.

Usage

```
maxAreaInscribedEllipse(points, verbose = FALSE)
```

Arguments

| | |
|---------|--|
| points | the vertices of the polygon in a two-columns matrix; their order has no importance, since the procedure takes the convex hull of these points (and does not check the convexity) |
| verbose | argument passed to psolve |

Value

An [Ellipse](#) object. The status of the optimization problem is given as an attribute of this ellipse. A warning is thrown if it is not optimal.

See Also

[maxAreaInscribedCircle](#)

Examples

```

hexagon <- rbind(
  c(-1.7, -1),
  c(-1.4, 0.4),
  c(0.3, 1.3),
  c(1.7, 0.6),
  c(1.3, -0.3),
  c(-0.4, -1.8)
)
opar <- par(mar = c(2, 2, 1, 1))
plot(NULL, xlim=c(-2, 2), ylim=c(-2, 2), xlab = NA, ylab = NA, asp = 1)
points(hexagon, pch = 19)
polygon(hexagon)
ell <- maxAreaInscribedEllipse(hexagon)
draw(ell, col = "yellow2", border = "blue", lwd = 2)
par(opar)
# check optimization status:
attr(ell, "status")

```

midCircles

Mid-circle(s)

Description

Return the mid-circle(s) of two circles.

Usage

```
midCircles(circ1, circ2)
```

Arguments

`circ1, circ2` Circle objects

Details

A mid-circle of two circles is a generalized circle (i.e. a circle or a line) such that the inversion on this circle swaps the two circles. The case of a line appears only when the two circles have equal radii.

Value

A Circle object, or a Line object, or a list of two such objects.

See Also

[inversionSwappingTwoCircles](#)

Examples

```
circ1 <- Circle$new(c(5,4),2)
circ2 <- Circle$new(c(6,4),1)
midcircle <- midCircles(circ1, circ2)
inversionFromCircle(midcircle)
inversionSwappingTwoCircles(circ1, circ2)
```

Mobius

R6 class representing a Möbius transformation.

Description

A Möbius transformation is given by a matrix of complex numbers with non-null determinant.

Active bindings

- a get or set a
- b get or set b
- c get or set c
- d get or set d

Methods

Public methods:

- `Mobius$new()`
- `Mobius$print()`
- `Mobius$getM()`
- `Mobius$compose()`
- `Mobius$inverse()`
- `Mobius$power()`
- `Mobius$gpower()`
- `Mobius$transform()`
- `Mobius$fixedPoints()`
- `Mobius$transformCircle()`
- `Mobius$transformLine()`
- `Mobius$transformGcircle()`
- `Mobius$clone()`

Method new(): Create a new Mobius object.

Usage:

`Mobius$new(M)`

Arguments:

`M` the matrix corresponding to the Möbius transformation

Returns: A new Möbius object.

Method `print()`: Show instance of a Möbius object.

Usage:

```
Mobius$print(...)
```

Arguments:

... ignored

Examples:

```
Mobius$new(rbind(c(1+1i, 2), c(0, 3-2i)))
```

Method `getM()`: Get the matrix corresponding to the Möbius transformation.

Usage:

```
Mobius$getM()
```

Method `compose()`: Compose the reference Möbius transformation with another Möbius transformation

Usage:

```
Mobius$compose(M1, left = TRUE)
```

Arguments:

M1 a Möbius object

left logical, whether to compose at left or at right (i.e. returns $M1 \circ M0$ or $M0 \circ M1$)

Returns: A Möbius object.

Method `inverse()`: Inverse of the reference Möbius transformation.

Usage:

```
Mobius$inverse()
```

Returns: A Möbius object.

Method `power()`: Power of the reference Möbius transformation.

Usage:

```
Mobius$power(k)
```

Arguments:

k an integer, possibly negative

Returns: The Möbius transformation M^k , where M is the reference Möbius transformation.

Method `gpower()`: Generalized power of the reference Möbius transformation.

Usage:

```
Mobius$gpower(k)
```

Arguments:

k a real number, possibly negative

Returns: A Möbius object, the generalized k-th power of the reference Möbius transformation.

Examples:

```
M <- Mobius$new(rbind(c(1+1i,2),c(0,3-2i)))
Mroot <- M$gpower(1/2)
Mroot$compose(Mroot) # should be M
```

Method transform(): Transformation of a point by the reference Möbius transformation.

Usage:

```
Mobius$transform(M)
```

Arguments:

M a point or Inf

Returns: A point or Inf, the image of M.

Examples:

```
Mob <- Mobius$new(rbind(c(1+1i,2),c(0,3-2i)))
Mob$transform(c(1,1))
Mob$transform(Inf)
```

Method fixedPoints(): Returns the fixed points of the reference Möbius transformation.

Usage:

```
Mobius$fixedPoints()
```

Returns: One point, or a list of two points, or a message in the case when the transformation is the identity map.

Method transformCircle(): Transformation of a circle by the reference Möbius transformation.

Usage:

```
Mobius$transformCircle(circ)
```

Arguments:

circ a Circle object

Returns: A Circle object or a Line object.

Method transformLine(): Transformation of a line by the reference Möbius transformation.

Usage:

```
Mobius$transformLine(line)
```

Arguments:

line a Line object

Returns: A Circle object or a Line object.

Method transformGcircle(): Transformation of a generalized circle (i.e. a circle or a line) by the reference Möbius transformation.

Usage:

```
Mobius$transformGcircle(gcirc)
```

Arguments:

gcirc a Circle object or a Line object

Returns: A Circle object or a Line object.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Mobius$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

[MobiusMappingThreePoints](#) to create a Möbius transformation, and also the `compose` method of the [Inversion](#) R6 class.

Examples

```
## -----
## Method `Mobius$print`
## -----
Mobius$new(rbind(c(1+1i,2),c(0,3-2i)))

## -----
## Method `Mobius$gpower`
## -----
M <- Mobius$new(rbind(c(1+1i,2),c(0,3-2i)))
Mroot <- M$gpower(1/2)
Mroot$compose(Mroot) # should be M

## -----
## Method `Mobius$transform`
## -----
Mob <- Mobius$new(rbind(c(1+1i,2),c(0,3-2i)))
Mob$transform(c(1,1))
Mob$transform(Inf)
```

`MobiusMappingCircle` *Möbius transformation mapping a given circle to a given circle*

Description

Returns a Möbius transformation mapping a given circle to another given circle.

Usage

```
MobiusMappingCircle(circ1, circ2)
```

Arguments

`circ1, circ2` Circle objects

Value

A Möbius transformation which maps `circ1` to `circ2`.

Examples

```
library(PlaneGeometry)
C1 <- Circle$new(c(0, 0), 1)
C2 <- Circle$new(c(1, 2), 3)
M <- MobiusMappingCircle(C1, C2)
C3 <- M$transformCircle(C1)
C3$isEqual(C2)
```

MobiusMappingThreePoints

Möbius transformation mapping three given points to three given points

Description

Return a Möbius transformation which sends P1 to Q1, P2 to Q2 and P3 to Q3.

Usage

`MobiusMappingThreePoints(P1, P2, P3, Q1, Q2, Q3)`

Arguments

| | |
|-------------------------|------------------------------------|
| <code>P1, P2, P3</code> | three distinct points, Inf allowed |
| <code>Q1, Q2, Q3</code> | three distinct points, Inf allowed |

Value

A Möbius object.

MobiusSwappingTwoPoints*Möbius transformation swapping two given points***Description**

Return a Möbius transformation which sends A to B and B to A.

Usage

```
MobiusSwappingTwoPoints(A, B)
```

Arguments

| | |
|------|--------------------------------------|
| A, B | two distinct points, Inf not allowed |
|------|--------------------------------------|

Value

A Mobius object.

Projection*R6 class representing a projection***Description**

A projection on a line D parallel to another line Delta is given by the line of projection (D) and the directrix line (Delta).

Active bindings

D get or set the projection line

Delta get or set the directrix line

Methods**Public methods:**

- [Projection\\$new\(\)](#)
- [Projection\\$print\(\)](#)
- [Projection\\$project\(\)](#)
- [Projection\\$transform\(\)](#)
- [Projection\\$getMatrix\(\)](#)
- [Projection\\$asAffine\(\)](#)
- [Projection\\$clone\(\)](#)

Method new(): Create a new Projection object.

Usage:

```
Projection$new(D, Delta)
```

Arguments:

D, Delta two Line objects such that the two lines meet (not parallel); or Delta = NULL for orthogonal projection onto D

Returns: A new Projection object.

Examples:

```
D <- Line$new(c(1,1), c(5,5))
Delta <- Line$new(c(0,0), c(3,4))
Projection$new(D, Delta)
```

Method print(): Show instance of a projection object.

Usage:

```
Projection/print(...)
```

Arguments:

... ignored

Method project(): Project a point.

Usage:

```
Projection/project(M)
```

Arguments:

M a point

Examples:

```
D <- Line$new(c(1,1), c(5,5))
Delta <- Line$new(c(0,0), c(3,4))
P <- Projection$new(D, Delta)
M <- c(1,3)
Mprime <- P$project(M)
D$includes(Mprime) # should be TRUE
Delta$isParallel(Line$new(M, Mprime)) # should be TRUE
```

Method transform(): An alias of project.

Usage:

```
Projection$transform(M)
```

Arguments:

M a point

Method getMatrix(): Augmented matrix of the projection.

Usage:

```
Projection/getMatrix()
```

Returns: A 3x3 matrix.

Examples:

```
P <- Projection$new(Line$new(c(2,2), c(4,5)), Line$new(c(0,0), c(1,1)))
M <- c(1,5)
P$project(M)
P$getMatrix() %*% c(M,1)
```

Method `asAffine()`: Convert the reference projection to an Affine object.

Usage:

```
Projection$asAffine()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Projection$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

For an orthogonal projection, you can use the `projection` method of the [Line](#) R6 class.

Examples

```
## -----
## Method `Projection$new`
## -----

D <- Line$new(c(1,1), c(5,5))
Delta <- Line$new(c(0,0), c(3,4))
Projection$new(D, Delta)

## -----
## Method `Projection$project`
## -----

D <- Line$new(c(1,1), c(5,5))
Delta <- Line$new(c(0,0), c(3,4))
P <- Projection$new(D, Delta)
M <- c(1,3)
Mprime <- P$project(M)
D$includes(Mprime) # should be TRUE
Delta$isParallel(Line$new(M, Mprime)) # should be TRUE

## -----
## Method `Projection$getMatrix`
## -----

P <- Projection$new(Line$new(c(2,2), c(4,5)), Line$new(c(0,0), c(1,1)))
M <- c(1,5)
P$project(M)
P$getMatrix() %*% c(M,1)
```

```
radicalCenter
```

Radical center

Description

Returns the radical center of three circles.

Usage

```
radicalCenter(circ1, circ2, circ3)
```

Arguments

```
circ1, circ2, circ3  
Circle objects
```

Value

A point.

```
Reflection
```

R6 class representing a reflection

Description

A reflection is given by a line.

Active bindings

```
line get or set the line of the reflection
```

Methods

Public methods:

- `Reflection$new()`
- `Reflection$print()`
- `Reflection$reflect()`
- `Reflection$transform()`
- `Reflection$reflectCircle()`
- `Reflection$transformCircle()`
- `Reflection$reflectLine()`
- `Reflection$transformLine()`
- `Reflection$getMatrix()`
- `Reflection$asAffine()`

- `Reflection$clone()`

Method `new():` Create a new Reflection object.

Usage:

`Reflection$new(line)`

Arguments:

`line` a Line object

Returns: A new Reflection object.

Examples:

`l <- Line$new(c(1,1), c(1.5,1.5), FALSE, TRUE)`

`Reflection$new(l)`

Method `print():` Show instance of a reflection object.

Usage:

`Reflection/print(...)`

Arguments:

... ignored

Method `reflect():` Reflect a point.

Usage:

`Reflection$reflect(M)`

Arguments:

`M` a point, Inf allowed

Method `transform():` An alias of reflect.

Usage:

`Reflection$transform(M)`

Arguments:

`M` a point, Inf allowed

Method `reflectCircle():` Reflect a circle.

Usage:

`Reflection$reflectCircle(circ)`

Arguments:

`circ` a Circle object

Returns: A Circle object.

Method `transformCircle():` An alias of reflectCircle.

Usage:

`Reflection$transformCircle(circ)`

Arguments:

`circ` a Circle object

Returns: A Circle object.

Method reflectLine(): Reflect a line.

Usage:

```
Reflection$reflectLine(line)
```

Arguments:

line a Line object

Returns: A Line object.

Method transformLine(): An alias of reflectLine.

Usage:

```
Reflection$transformLine(line)
```

Arguments:

line a Line object

Returns: A Line object.

Method getMatrix(): Augmented matrix of the reflection.

Usage:

```
Reflection$getMatrix()
```

Returns: A 3x3 matrix.

Examples:

```
R <- Reflection$new(Line$new(c(2,2), c(4,5)))
P <- c(1,5)
R$reflect(P)
R$getMatrix() %*% c(P,1)
```

Method asAffine(): Convert the reference reflection to an Affine object.

Usage:

```
Reflection$asAffine()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
Reflection$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## -----
## Method `Reflection$new`
## -----
l <- Line$new(c(1,1), c(1.5,1.5), FALSE, TRUE)
```

```
Reflection$new(l)

## -----
## Method `Reflection$getMatrix`
## -----


R <- Reflection$new(Line$new(c(2,2), c(4,5)))
P <- c(1,5)
R$reflect(P)
R$getMatrix() %*% c(P,1)
```

Rotation*R6 class representing a rotation***Description**

A rotation is given by an angle (theta) and a center.

Active bindings

- `theta` get or set the angle of the rotation
- `center` get or set the center
- `degrees` get or set the degrees field

Methods**Public methods:**

- [Rotation\\$new\(\)](#)
- [Rotation\\$print\(\)](#)
- [Rotation\\$rotate\(\)](#)
- [Rotation\\$transform\(\)](#)
- [Rotation\\$rotateCircle\(\)](#)
- [Rotation\\$transformCircle\(\)](#)
- [Rotation\\$rotateEllipse\(\)](#)
- [Rotation\\$transformEllipse\(\)](#)
- [Rotation\\$rotateLine\(\)](#)
- [Rotation\\$transformLine\(\)](#)
- [Rotation\\$getMatrix\(\)](#)
- [Rotation\\$asAffine\(\)](#)
- [Rotation\\$clone\(\)](#)

Method new(): Create a new Rotation object.

Usage:

```
Rotation$new(theta, center, degrees = TRUE)
```

Arguments:

theta a number, the angle of the rotation
center a point, the center of the rotation
degrees logical, whether theta is given in degrees

Returns: A new Rotation object.

Examples:

```
Rotation$new(60, c(1,1))
```

Method print(): Show instance of a Rotation object.

Usage:

```
Rotation$print(...)
```

Arguments:

... ignored

Method rotate(): Rotate a point or several points.

Usage:

```
Rotation$rotate(M)
```

Arguments:

M a point or a two-column matrix of points, one point per row

Method transform(): An alias of rotate.

Usage:

```
Rotation$transform(M)
```

Arguments:

M a point or a two-column matrix of points, one point per row

Method rotateCircle(): Rotate a circle.

Usage:

```
Rotation$rotateCircle(circ)
```

Arguments:

circ a Circle object

Returns: A Circle object.

Method transformCircle(): An alias of rotateCircle.

Usage:

```
Rotation$transformCircle(circ)
```

Arguments:

circ a Circle object

Returns: A Circle object.

Method rotateEllipse(): Rotate an ellipse.

Usage:

`Rotation$rotateEllipse(ell)`

Arguments:

`ell` an Ellipse object

Returns: An Ellipse object.

Method `transformEllipse()`: An alias of `rotateEllipse`.

Usage:

`Rotation$transformEllipse(ell)`

Arguments:

`ell` an Ellipse object

Returns: An Ellipse object.

Method `rotateLine()`: Rotate a line.

Usage:

`Rotation$rotateLine(line)`

Arguments:

`line` a Line object

Returns: A Line object.

Method `transformLine()`: An alias of `rotateLine`.

Usage:

`Rotation$transformLine(line)`

Arguments:

`line` a Line object

Returns: A Line object.

Method `getMatrix()`: Augmented matrix of the rotation.

Usage:

`Rotation$getMatrix()`

Returns: A 3x3 matrix.

Examples:

`R <- Rotation$new(60, c(1,1))`

`P <- c(1,5)`

`R$rotate(P)`

`R$getMatrix() %*% c(P,1)`

Method `asAffine()`: Convert the reference rotation to an Affine object.

Usage:

`Rotation$asAffine()`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`Rotation$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Examples

```
## -----
## Method `Rotation$new`
## -----
Rotation$new(60, c(1,1))

## -----
## Method `Rotation$getMatrix`
## -----
R <- Rotation$new(60, c(1,1))
P <- c(1,5)
R$rotate(P)
R$getMatrix() %*% c(P,1)
```

Scaling

R6 class representing a (non-uniform) scaling

Description

A (non-uniform) scaling is given by a center, a direction vector, and a scale factor.

Active bindings

- `center` get or set the center
- `direction` get or set the direction
- `scale` get or set the scale factor

Methods

Public methods:

- `Scaling$new()`
- `Scaling$print()`
- `Scaling$transform()`
- `Scaling$getMatrix()`
- `Scaling$asAffine()`
- `Scaling$scaleCircle()`
- `Scaling$clone()`

Method new(): Create a new Scaling object.

Usage:

`Scaling$new(center, direction, scale)`

Arguments:

`center` a point, the center of the scaling
`direction` a vector, the direction of the scaling
`scale` a number, the scale factor

Returns: A new Scaling object.

Examples:

```
Scaling$new(c(1,1), c(1,3), 2)
```

Method `print()`: Show instance of a Scaling object.

Usage:

```
Scaling$print(...)
```

Arguments:

... ignored

Method `transform()`: Transform a point or several points by the reference scaling.

Usage:

```
Scaling$transform(M)
```

Arguments:

`M` a point or a two-column matrix of points, one point per row

Method `getMatrix()`: Augmented matrix of the scaling.

Usage:

```
Scaling$getMatrix()
```

Returns: A 3x3 matrix.

Examples:

```
S <- Scaling$new(c(1,1), c(2,3), 2)
```

```
P <- c(1,5)
```

```
S$transform(P)
```

```
S$getMatrix() %*% c(P,1)
```

Method `asAffine()`: Convert the reference scaling to an Affine object.

Usage:

```
Scaling$asAffine()
```

Method `scaleCircle()`: Scale a circle. The result is an ellipse.

Usage:

```
Scaling$scaleCircle(circ)
```

Arguments:

`circ` a Circle object

Returns: An Ellipse object.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Scaling$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

R. Goldman, *An Integrated Introduction to Computer Graphics and Geometric Modeling*. CRC Press, 2009.

Examples

```

Q <- c(1,1); w <- c(1,3); s <- 2
S <- Scaling$new(Q, w, s)
# the center is mapped to itself:
S$transform(Q)
# any vector \code{u} parallel to the direction vector is mapped to \code{s*u}:
u <- 3*w
all.equal(s*u, S$transform(u) - S$transform(c(0,0)))
# any vector perpendicular to the direction vector is mapped to itself
wt <- 3*c(-w[2], w[1])
all.equal(wt, S$transform(wt) - S$transform(c(0,0)))

## -----
## Method `Scaling$new`
## -----
Scaling$new(c(1,1), c(1,3), 2)

## -----
## Method `Scaling$getMatrix'
## -----
S <- Scaling$new(c(1,1), c(2,3), 2)
P <- c(1,5)
S$transform(P)
S$getMatrix() %*% c(P,1)

```

Description

An axis-scaling is given by a center, and two scale factors `sx` and `sy`, one for the x-axis and one for the y-axis.

Active bindings

- `center` get or set the center
- `sx` get or set the scale factor of the x-axis
- `sy` get or set the scale factor of the y-axis

Methods

Public methods:

- `ScalingXY$new()`
- `ScalingXY$print()`
- `ScalingXY$transform()`
- `ScalingXY$getMatrix()`
- `ScalingXY$asAffine()`
- `ScalingXY$clone()`

Method new(): Create a new `ScalingXY` object.

Usage:

```
ScalingXY$new(center, sx, sy)
```

Arguments:

`center` a point, the center of the scaling
`sx` a number, the scale factor of the x-axis
`sy` a number, the scale factor of the y-axis

Returns: A new `ScalingXY` object.

Examples:

```
ScalingXY$new(c(1,1), 4, 2)
```

Method print(): Show instance of a `ScalingXY` object.

Usage:

```
ScalingXY$print(...)
```

Arguments:

`...` ignored

Method transform(): Transform a point or several points by the reference axis-scaling.

Usage:

```
ScalingXY$transform(M)
```

Arguments:

`M` a point or a two-column matrix of points, one point per row

Returns: A point or a two-column matrix of points.

Method getMatrix(): Augmented matrix of the axis-scaling.

Usage:

```
ScalingXY$getMatrix()
```

Returns: A 3x3 matrix.

Examples:

```
S <- ScalingXY$new(c(1,1), 4, 2)
P <- c(1,5)
S$transform(P)
S$getMatrix() %*% c(P,1)
```

Method asAffine(): Convert the reference axis-scaling to an Affine object.

Usage:

`ScalingXY$asAffine()`

Method clone(): The objects of this class are cloneable with this method.

Usage:

`ScalingXY$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Examples

```
## -----
## Method `ScalingXY$new`
## -----
ScalingXY$new(c(1,1), 4, 2)

## -----
## Method `ScalingXY$getMatrix`
## -----
S <- ScalingXY$new(c(1,1), 4, 2)
P <- c(1,5)
S$transform(P)
S$getMatrix() %*% c(P,1)
```

Description

A shear is given by a vertex, two perpendicular vectors, and an angle.

Active bindings

`vertex` get or set the vertex

`vector` get or set the first vector

`ratio` get or set the ratio between the length of `vector` and the length of the second vector, perpendicular to the first one

`angle` get or set the angle

`degrees` get or set the degrees field

Methods

Public methods:

- `Shear$new()`
- `Shear$print()`
- `Shear$transform()`
- `Shear$getMatrix()`
- `Shear$asAffine()`
- `Shear$clone()`

Method `new():` Create a new Shear object.

Usage:

```
Shear$new(vertex, vector, ratio, angle, degrees = TRUE)
```

Arguments:

`vertex` a point

`vector` a vector

`ratio` a positive number, the ratio between the length of `vector` and the length of the second vector, perpendicular to the first one

`angle` an angle strictly between -90 degrees and 90 degrees

`degrees` logical, whether angle is given in degrees

Returns: A new Shear object.

Examples:

```
Shear$new(c(1,1), c(1,3), 0.5, 30)
```

Method `print():` Show instance of a Shear object.

Usage:

```
Shear$print(...)
```

Arguments:

... ignored

Method `transform():` Transform a point or several points by the reference shear.

Usage:

```
Shear$transform(M)
```

Arguments:

`M` a point or a two-column matrix of points, one point per row

Method `getMatrix():` Augmented matrix of the shear.

Usage:

```
Shear$getMatrix()
```

Returns: A 3x3 matrix.

Examples:

```
S <- Shear$new(c(1,1), c(1,3), 0.5, 30)
S$getMatrix()
```

Method asAffine(): Convert the reference shear to an Affine object.

Usage:

```
Shear$asAffine()
```

Examples:

```
Shear$new(c(0,0), c(1,0), 1, atan(30), FALSE)$asAffine()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
Shear$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

References

R. Goldman, *An Integrated Introduction to Computer Graphics and Geometric Modeling*. CRC Press, 2009.

Examples

```
P <- c(0,0); w <- c(1,0); ratio <- 1; angle <- 45
shear <- Shear$new(P, w, ratio, angle)
wt <- ratio * c(-w[2], w[1])
Q <- P + w; R <- Q + wt; S <- P + wt
A <- shear$transform(P)
B <- shear$transform(Q)
C <- shear$transform(R)
D <- shear$transform(S)
plot(0, 0, type = "n", asp = 1, xlim = c(0,1), ylim = c(0,2))
lines(rbind(P,Q,R,S,P), lwd = 2) # unit square
lines(rbind(A,B,C,D,A), lwd = 2, col = "blue") # image by the shear

## -----
## Method `Shear$new`
## -----
```



```
Shear$new(c(1,1), c(1,3), 0.5, 30)

## -----
## Method `Shear$getMatrix`
## -----
```



```
S <- Shear$new(c(1,1), c(1,3), 0.5, 30)
S$getMatrix()

## -----
## Method `Shear$asAffine`
## -----
```



```
Shear$new(c(0,0), c(1,0), 1, atan(30), FALSE)$asAffine()
```

soddyCircle*Inner Soddy circle***Description**

Inner Soddy circles associated to three circles.

Usage

```
soddyCircle(circ1, circ2, circ3)
```

Arguments

| | |
|----------------------------------|------------------|
| <code>circ1, circ2, circ3</code> | |
| | distinct circles |

Value

A Circle object.

SteinerChain*Steiner chain***Description**

Return a Steiner chain of circles.

Usage

```
SteinerChain(c0, n, phi, shift, ellipse = FALSE)
```

Arguments

| | |
|----------------------|---|
| <code>c0</code> | exterior circle, a Circle object |
| <code>n</code> | number of circles, not including the inner circle; at least 3 |
| <code>phi</code> | $-1 < \text{phi} < 1$ controls the radii of the circles |
| <code>shift</code> | any number; it produces a kind of rotation around the inner circle; values between 0 and n cover all possibilities |
| <code>ellipse</code> | logical; the centers of the circles of the Steiner chain lie on an ellipse, and this ellipse is returned as an attribute if you set this argument to TRUE |

Value

A list of $n+1$ Circle objects. The inner circle is stored at the last position.

Examples

```
c0 <- Circle$new(c(1,1), 3)
chain <- SteinerChain(c0, 5, 0.3, 0.5, ellipse = TRUE)
plot(0, 0, type = "n", asp = 1, xlim = c(-4,4), ylim = c(-4,4))
invisible(lapply(chain, draw, lwd = 2, border = "blue"))
draw(c0, lwd = 2)
draw(attr(chain, "ellipse"), lwd = 2, border = "red")
```

Translation

R6 class representing a translation

Description

A translation is given by a vector v .

Active bindings

- ✓ get or set the vector of translation

Methods

Public methods:

- `Translation$new()`
- `Translation$print()`
- `Translation$project()`
- `Translation$transform()`
- `Translation$translateLine()`
- `Translation$transformLine()`
- `Translation$translateEllipse()`
- `Translation$transformEllipse()`
- `Translation$getMatrix()`
- `Translation$asAffine()`
- `Translation$clone()`

Method `new()`: Create a new Translation object.

Usage:

`Translation$new(v)`

Arguments:

✓ v a numeric vector of length two, the vector of translation

Returns: A new Translation object.

Method `print()`: Show instance of a translation object.

Usage:

`Translation$print(...)`

Arguments:

... ignored

Method project(): Transform a point or several points by the reference translation.

Usage:

Translation\$project(M)

Arguments:

M a point or a two-column matrix of points, one point per row

Method transform(): An alias of translate.

Usage:

Translation\$transform(M)

Arguments:

M a point or a two-column matrix of points, one point per row

Method translateLine(): Translate a line.

Usage:

Translation\$translateLine(line)

Arguments:

line a Line object

Returns: A Line object.

Method transformLine(): An alias of translateLine.

Usage:

Translation\$transformLine(line)

Arguments:

line a Line object

Returns: A Line object.

Method translateEllipse(): Translate a circle or an ellipse.

Usage:

Translation\$translateEllipse(ell)

Arguments:

ell an Ellipse object or a Circle object

Returns: An Ellipse object or a Circle object.

Method transformEllipse(): An alias of translateEllipse.

Usage:

Translation\$transformEllipse(ell)

Arguments:

ell an Ellipse object or a Circle object

Returns: An Ellipse object or a Circle object.

Method `getMatrix()`: Augmented matrix of the translation.

Usage:

`Translation$getMatrix()`

Returns: A 3x3 matrix.

Method `asAffine()`: Convert the reference translation to an Affine object.

Usage:

`Translation$asAffine()`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`Translation$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Triangle

R6 class representing a triangle

Description

A triangle has three vertices. They are named A, B, C.

Active bindings

- A get or set the vertex A
- B get or set the vertex B
- C get or set the vertex C

Methods

Public methods:

- `Triangle$new()`
- `Triangle$print()`
- `Triangle$flatness()`
- `Triangle$a()`
- `Triangle$b()`
- `Triangle$c()`
- `Triangle$edges()`
- `Triangle$perimeter()`
- `Triangle$orientation()`
- `Triangle$contains()`
- `Triangle$isAcute()`
- `Triangle$angleA()`

- `Triangle$angleB()`
- `Triangle$angleC()`
- `Triangle$angles()`
- `Triangle$X175()`
- `Triangle$VeldkampIsoperimetricPoint()`
- `Triangle$centroid()`
- `Triangle$orthocenter()`
- `Triangle$area()`
- `Triangle$incircle()`
- `Triangle$inradius()`
- `Triangle$incenter()`
- `Triangle$excircles()`
- `Triangle$excentralTriangle()`
- `Triangle$BevanPoint()`
- `Triangle$medialTriangle()`
- `Triangle$orthicTriangle()`
- `Triangle$incentralTriangle()`
- `Triangle$NagelTriangle()`
- `Triangle$NagelPoint()`
- `Triangle$GergonneTriangle()`
- `Triangle$GergonnePoint()`
- `Triangle$tangentialTriangle()`
- `Triangle$symmedianTriangle()`
- `Triangle$symmedianPoint()`
- `Triangle$circumcircle()`
- `Triangle$circumcenter()`
- `Triangle$circumradius()`
- `Triangle$BrocardCircle()`
- `Triangle$BrocardPoints()`
- `Triangle$LemoineCircleI()`
- `Triangle$LemoineCircleII()`
- `Triangle$LemoineTriangle()`
- `Triangle$LemoineCircleIII()`
- `Triangle$ParryCircle()`
- `Triangle$outerSoddyCircle()`
- `Triangle$pedalTriangle()`
- `Triangle$CevianTriangle()`
- `Triangle$MalfattiCircles()`
- `Triangle$AjimaMalfatti1()`
- `Triangle$AjimaMalfatti2()`
- `Triangle$equalDetourPoint()`
- `Triangle$trilinearToPoint()`

- `Triangle$pointToTrilinear()`
- `Triangle$isogonalConjugate()`
- `Triangle$rotate()`
- `Triangle$translate()`
- `Triangle$SteinerEllipse()`
- `Triangle$SteinerInellipse()`
- `Triangle$MandartInellipse()`
- `Triangle$randomPoints()`
- `Triangle$hexylTriangle()`
- `Triangle$plot()`
- `Triangle$clone()`

Method `new()`: Create a new Triangle object.

Usage:

`Triangle$new(A, B, C)`

Arguments:

`A, B, C` vertices

Returns: A new Triangle object.

Examples:

```
t <- Triangle$new(c(0,0), c(1,0), c(1,1))
t
t$C
t$C <- c(2,2)
t
```

Method `print()`: Show instance of a triangle object

Usage:

`Triangle/print(...)`

Arguments:

... ignored

Examples:

```
Triangle$new(c(0,0), c(1,0), c(1,1))
```

Method `flatness()`: Flatness of the triangle.

Usage:

`Triangle$flatness()`

Returns: A number between 0 and 1. A triangle is flat when its flatness is 1.

Method `a()`: Length of the side BC.

Usage:

`Triangle$a()`

Method `b()`: Length of the side AC.

Usage:

`Triangle$b()`

Method `c()`: Length of the side AB.

Usage:

`Triangle$c()`

Method `edges()`: The lengths of the sides of the triangle.

Usage:

`Triangle$edges()`

Returns: A named numeric vector.

Method `perimeter()`: Perimeter of the triangle.

Usage:

`Triangle$perimeter()`

Returns: The perimeter of the triangle.

Method `orientation()`: Determine the orientation of the triangle.

Usage:

`Triangle$orientation()`

Returns: An integer: 1 for counterclockwise, -1 for clockwise, 0 for collinear.

Method `contains()`: Determine whether a point lies inside the reference triangle.

Usage:

`Triangle$contains(M)`

Arguments:

`M` a point

Method `isAcute()`: Determines whether the reference triangle is acute.

Usage:

`Triangle$isAcute()`

Returns: ‘TRUE’ if the triangle is acute (or right), ‘FALSE’ otherwise.

Method `angleA()`: Angle at the vertex A.

Usage:

`Triangle$angleA()`

Returns: The angle at the vertex A in radians.

Method `angleB()`: Angle at the vertex B.

Usage:

`Triangle$angleB()`

Returns: The angle at the vertex B in radians.

Method `angleC()`: Angle at the vertex C.

Usage:

`Triangle$angleC()`

Returns: The angle at the vertex C in radians.

Method `angles()`: The three angles of the triangle.

Usage:

`Triangle$angles()`

Returns: A named vector containing the values of the angles in radians.

Method `X175()`: Isoperimetric point, also known as the X(175) triangle center; this is the center of the outer Soddy circle.

Usage:

`Triangle$X175()`

Method `VeldkampIsoperimetricPoint()`: Isoperimetric point in the sense of Veldkamp.

Usage:

`Triangle$VeldkampIsoperimetricPoint()`

Returns: The isoperimetric point in the sense of Veldkamp, if it exists. Otherwise, returns ‘NULL’.

Method `centroid()`: Centroid.

Usage:

`Triangle$centroid()`

Method `orthocenter()`: Orthocenter.

Usage:

`Triangle$orthocenter()`

Method `area()`: Area of the triangle.

Usage:

`Triangle$area()`

Method `incircle()`: Incircle of the triangle.

Usage:

`Triangle$incircle()`

Returns: A Circle object.

Method `inradius()`: Inradius of the reference triangle.

Usage:

`Triangle$inradius()`

Method `incenter()`: Incenter of the reference triangle.

Usage:

`Triangle$incenter()`

Method excircles(): Excircles of the triangle.

Usage:

```
Triangle$excircles()
```

Returns: A list with the three excircles, Circle objects.

Method excentralTriangle(): Excentral triangle of the reference triangle.

Usage:

```
Triangle$excentralTriangle()
```

Returns: A Triangle object.

Method BevanPoint(): Bevan point. This is the circumcenter of the excentral triangle.

Usage:

```
Triangle$BevanPoint()
```

Method medialTriangle(): Medial triangle. Its vertices are the mid-points of the sides of the reference triangle.

Usage:

```
Triangle$medialTriangle()
```

Method orthicTriangle(): Orthic triangle. Its vertices are the feet of the altitudes of the reference triangle.

Usage:

```
Triangle$orthicTriangle()
```

Method incentralTriangle(): Incentral triangle.

Usage:

```
Triangle$incentralTriangle()
```

Details: It is the triangle whose vertices are the intersections of the reference triangle's angle bisectors with the respective opposite sides.

Returns: A Triangle object.

Method NagelTriangle(): Nagel triangle (or extouch triangle) of the reference triangle.

Usage:

```
Triangle$NagelTriangle(NagelPoint = FALSE)
```

Arguments:

NagelPoint logical, whether to return the Nagel point as attribute

Returns: A Triangle object.

Examples:

```
t <- Triangle$new(c(0,-2), c(0.5,1), c(3,0.6))
lineAB <- Line$new(t$A, t$B)
lineAC <- Line$new(t$A, t$C)
lineBC <- Line$new(t$B, t$C)
NagelTriangle <- t$NagelTriangle(NagelPoint = TRUE)
```

```

NagelPoint <- attr(NagelTriangle, "Nagel point")
excircles <- t$excircles()
opar <- par(mar = c(0,0,0,0))
plot(0, 0, type="n", asp = 1, xlim = c(-1,5), ylim = c(-3,3),
     xlab = NA, ylab = NA, axes = FALSE)
draw(t, lwd = 2)
draw(lineAB); draw(lineAC); draw(lineBC)
draw(excircles$A, border = "orange")
draw(excircles$B, border = "orange")
draw(excircles$C, border = "orange")
draw(NagelTriangle, lwd = 2, col = "red")
draw(Line$new(t$A, NagelTriangle$A, FALSE, FALSE), col = "blue")
draw(Line$new(t$B, NagelTriangle$B, FALSE, FALSE), col = "blue")
draw(Line$new(t$C, NagelTriangle$C, FALSE, FALSE), col = "blue")
points(rbind(NagelPoint), pch = 19)
par(opar)

```

Method `NagelPoint()`: Nagel point of the triangle.

Usage:

```
Triangle$NagelPoint()
```

Method `GergonneTriangle()`: Gergonne triangle of the reference triangle.

Usage:

```
Triangle$GergonneTriangle(GergonnePoint = FALSE)
```

Arguments:

`GergonnePoint` logical, whether to return the Gergonne point as an attribute

Details: The Gergonne triangle is also known as the *intouch triangle* or the *contact triangle*. This is the triangle made of the three tangency points of the incircle.

Returns: A `Triangle` object.

Method `GergonnePoint()`: Gergonne point of the reference triangle.

Usage:

```
Triangle$GergonnePoint()
```

Method `tangentialTriangle()`: Tangential triangle of the reference triangle. This is the triangle formed by the lines tangent to the circumcircle of the reference triangle at its vertices. It does not exist for a right triangle.

Usage:

```
Triangle$tangentialTriangle()
```

Returns: A `Triangle` object.

Method `symmedialTriangle()`: Symmedial triangle of the reference triangle.

Usage:

```
Triangle$symmedialTriangle()
```

Returns: A `Triangle` object.

Examples:

```
t <- Triangle$new(c(0,-2), c(0.5,1), c(3,0.6))
symt <- t$symmedianTriangle()
symmedianA <- Line$new(t$A, symt$A, FALSE, FALSE)
symmedianB <- Line$new(t$B, symt$B, FALSE, FALSE)
symmedianC <- Line$new(t$C, symt$C, FALSE, FALSE)
K <- t$symmedianPoint()
opar <- par(mar = c(0,0,0,0))
plot(NULL, asp = 1, xlim = c(-1,5), ylim = c(-3,3),
      xlab = NA, ylab = NA, axes = FALSE)
draw(t, lwd = 2)
draw(symmedianA, lwd = 2, col = "blue")
draw(symmedianB, lwd = 2, col = "blue")
draw(symmedianC, lwd = 2, col = "blue")
points(rbind(K), pch = 19, col = "red")
par(opar)
```

Method `symmedianPoint()`: Symmedian point of the reference triangle.

Usage:

```
Triangle$symmedianPoint()
```

Returns: A point.

Method `circumcircle()`: Circumcircle of the reference triangle.

Usage:

```
Triangle$circumcircle()
```

Returns: A `Circle` object.

Method `circumcenter()`: Circumcenter of the reference triangle.

Usage:

```
Triangle$circumcenter()
```

Method `circumradius()`: Circumradius of the reference triangle.

Usage:

```
Triangle$circumradius()
```

Method `BrocardCircle()`: The Brocard circle of the reference triangle (also known as the seven-point circle).

Usage:

```
Triangle$BrocardCircle()
```

Returns: A `Circle` object.

Method `BrocardPoints()`: Brocard points of the reference triangle.

Usage:

```
Triangle$BrocardPoints()
```

Returns: A list of two points, the first Brocard point and the second Brocard point.

Method LemoineCircleI(): The first Lemoine circle of the reference triangle.

Usage:

Triangle\$LemoineCircleI()

Returns: A Circle object.

Method LemoineCircleII(): The second Lemoine circle of the reference triangle (also known as the cosine circle)

Usage:

Triangle\$LemoineCircleII()

Returns: A Circle object.

Method LemoineTriangle(): The Lemoine triangle of the reference triangle.

Usage:

Triangle\$LemoineTriangle()

Returns: A Triangle object.

Method LemoineCircleIII(): The third Lemoine circle of the reference triangle.

Usage:

Triangle\$LemoineCircleIII()

Returns: A Circle object.

Method ParryCircle(): Parry circle of the reference triangle.

Usage:

Triangle\$ParryCircle()

Returns: A Circle object.

Method outerSoddyCircle(): Soddy outer circle of the reference triangle.

Usage:

Triangle\$outerSoddyCircle()

Returns: A Circle object.

Method pedalTriangle(): Pedal triangle of a point with respect to the reference triangle. The pedal triangle of a point P is the triangle whose vertices are the feet of the perpendiculars from P to the sides of the reference triangle.

Usage:

Triangle\$pedalTriangle(P)

Arguments:

P a point

Returns: A Triangle object.

Method CevianTriangle(): Cevian triangle of a point with respect to the reference triangle.

Usage:

Triangle\$CevianTriangle(P)

Arguments:

P a point

Returns: A Triangle object.

Method MalfattiCircles(): Malfatti circles of the triangle.

Usage:

```
Triangle$MalfattiCircles(tangencyPoints = FALSE)
```

Arguments:

tangencyPoints logical, whether to return the tangency points of the Malfatti circles as an attribute.

Returns: A list with the three Malfatti circles, Circle objects.

Examples:

```
t <- Triangle$new(c(0,0), c(2,0.5), c(1.5,2))
Mcircles <- t$MalfattiCircles(TRUE)
plot(NULL, asp = 1, xlim = c(0,2.5), ylim = c(0,2.5),
      xlab = NA, ylab = NA)
grid()
draw(t, col = "blue", lwd = 2)
invisible(lapply(Mcircles, draw, col = "green", border = "red"))
invisible(lapply(attr(Mcircles, "tangencyPoints"), function(P){
  points(P[1], P[2], pch = 19)
}))
```

Method AjimaMalfatti1(): First Ajima-Malfatti point of the triangle.

Usage:

```
Triangle$AjimaMalfatti1()
```

Method AjimaMalfatti2(): Second Ajima-Malfatti point of the triangle.

Usage:

```
Triangle$AjimaMalfatti2()
```

Method equalDetourPoint(): Equal detour point of the triangle.

Usage:

```
Triangle$equalDetourPoint(detour = FALSE)
```

Arguments:

detour logical, whether to return the detour as an attribute

Details: Also known as the X(176) triangle center.

Method trilinearToPoint(): Point given by trilinear coordinates.

Usage:

```
Triangle$trilinearToPoint(x, y, z)
```

Arguments:

x, y, z trilinear coordinates

Returns: The point with trilinear coordinates $x:y:z$ with respect to the reference triangle.

Examples:

```
t <- Triangle$new(c(0,0), c(2,1), c(5,7))
incircle <- t$incircle()
t$trilinearToPoint(1, 1, 1)
incircle$center
```

Method `pointToTrilinear()`: Give the trilinear coordinates of a point with respect to the reference triangle.

Usage:

```
Triangle$pointToTrilinear(P)
```

Arguments:

P a point

Returns: The trilinear coordinates, a numeric vector of length 3.

Method `isogonalConjugate()`: Isogonal conjugate of a point with respect to the reference triangle.

Usage:

```
Triangle$isogonalConjugate(P)
```

Arguments:

P a point

Returns: A point, the isogonal conjugate of P.

Method `rotate()`: Rotate the triangle.

Usage:

```
Triangle$rotate(alpha, 0, degrees = TRUE)
```

Arguments:

alpha angle of rotation

0 center of rotation

degrees logical, whether alpha is given in degrees

Returns: A Triangle object.

Method `translate()`: Translate the triangle.

Usage:

```
Triangle$translate(v)
```

Arguments:

v the vector of translation

Returns: A Triangle object.

Method `SteinerEllipse()`: The Steiner ellipse (or circumellipse) of the reference triangle. This is the ellipse passing through the three vertices of the triangle and centered at the centroid of the triangle.

Usage:

```
Triangle$SteinerEllipse()
```

Returns: An Ellipse object.

Examples:

```
t <- Triangle$new(c(0,0), c(2,0.5), c(1.5,2))
ell <- t$SteinerEllipse()
plot(NULL, asp = 1, xlim = c(0,2.5), ylim = c(-0.7,2.4),
      xlab = NA, ylab = NA)
draw(t, col = "blue", lwd = 2)
draw(ell, border = "red", lwd =2)
```

Method `SteinerInellipse()`: The Steiner inellipse (or midpoint ellipse) of the reference triangle. This is the ellipse tangent to the sides of the triangle at their midpoints, and centered at the centroid of the triangle.

Usage:

```
Triangle$SteinerInellipse()
```

Returns: An Ellipse object.

Examples:

```
t <- Triangle$new(c(0,0), c(2,0.5), c(1.5,2))
ell <- t$SteinerInellipse()
plot(NULL, asp = 1, xlim = c(0,2.5), ylim = c(-0.1,2.4),
      xlab = NA, ylab = NA)
draw(t, col = "blue", lwd = 2)
draw(ell, border = "red", lwd =2)
```

Method `MandartInellipse()`: The Mandart inellipse of the reference triangle. This is the unique ellipse tangent to the triangle's sides at the contact points of its excircles

Usage:

```
Triangle$MandartInellipse()
```

Returns: An Ellipse object.

Method `randomPoints()`: Random points on or in the reference triangle.

Usage:

```
Triangle$randomPoints(n, where = "in")
```

Arguments:

`n` an integer, the desired number of points

`where` "in" to generate inside the triangle, "on" to generate on the sides of the triangle

Returns: The generated points in a two columns matrix with `n` rows.

Method `hexylTriangle()`: Hexyl triangle.

Usage:

```
Triangle$hexylTriangle()
```

Method `plot()`: Plot a Triangle object.

Usage:

```
Triangle$plot(add = FALSE, ...)
```

Arguments:

add Boolean, whether to add the plot to the current plot

... named arguments passed to `polygon`

Returns: Nothing, called for plotting only.

Examples:

```
trgl <- Triangle$new(c(0, 0), c(1, 0), c(0.5, sqrt(3)/2))
trgl$plot(col = "yellow", border = "red")
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
Triangle$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

The Steiner ellipse is also the smallest area ellipse which passes through the vertices of the triangle, and thus can be obtained with the function `EllipseFromThreeBoundaryPoints`. We can also note that the major axis of the Steiner ellipse is the Deming least squares line of the three triangle vertices.

See Also

`TriangleThreeLines` to define a triangle by three lines.

Examples

```
# incircle and excircles
A <- c(0,0); B <- c(1,2); C <- c(3.5,1)
t <- Triangle$new(A, B, C)
incircle <- t$incircle()
excircles <- t$excircles()
JA <- excircles$A$center
JB <- excircles$B$center
JC <- excircles$C$center
JA_JB_JC <- Triangle$new(JA, JB, JC)
A_JA <- Line$new(A, JA, FALSE, FALSE)
B_JB <- Line$new(B, JB, FALSE, FALSE)
C_JC <- Line$new(C, JC, FALSE, FALSE)
opar <- par(mar = c(0,0,0,0))
plot(NULL, asp = 1, xlim = c(0,6), ylim = c(-4,4),
      xlab = NA, ylab = NA, axes = FALSE)
draw(t, lwd = 2)
draw(incircle, border = "orange")
draw(excircles$A); draw(excircles$B); draw(excircles$C)
draw(JA_JB_JC, col = "blue")
draw(A_JA, col = "green")
```

```

draw(B_JB, col = "green")
draw(C_JC, col = "green")
par(opar)

## -----
## Method `Triangle$new`
## -----


t <- Triangle$new(c(0,0), c(1,0), c(1,1))
t
t$c
t$c <- c(2,2)
t

## -----
## Method `Triangle$print`
## -----


Triangle$new(c(0,0), c(1,0), c(1,1))

## -----
## Method `Triangle$NagelTriangle`
## -----


t <- Triangle$new(c(0,-2), c(0.5,1), c(3,0.6))
lineAB <- Line$new(t$a, t$b)
lineAC <- Line$new(t$a, t$c)
lineBC <- Line$new(t$b, t$c)
NagelTriangle <- t$NagelTriangle(NagelPoint = TRUE)
NagelPoint <- attr(NagelTriangle, "Nagel point")
excircles <- t$excircles()
opar <- par(mar = c(0,0,0,0))
plot(0, 0, type="n", asp = 1, xlim = c(-1,5), ylim = c(-3,3),
     xlab = NA, ylab = NA, axes = FALSE)
draw(t, lwd = 2)
draw(lineAB); draw(lineAC); draw(lineBC)
draw(excircles$a, border = "orange")
draw(excircles$b, border = "orange")
draw(excircles$c, border = "orange")
draw(NagelTriangle, lwd = 2, col = "red")
draw(Line$new(t$a, NagelTriangle$a, FALSE, FALSE), col = "blue")
draw(Line$new(t$b, NagelTriangle$b, FALSE, FALSE), col = "blue")
draw(Line$new(t$c, NagelTriangle$c, FALSE, FALSE), col = "blue")
points(rbind(NagelPoint), pch = 19)
par(opar)

## -----
## Method `Triangle$symmedianTriangle`
## -----


t <- Triangle$new(c(0,-2), c(0.5,1), c(3,0.6))
symt <- t$symmedianTriangle()

```

```

symmedianA <- Line$new(t$A, symt$A, FALSE, FALSE)
symmedianB <- Line$new(t$B, symt$B, FALSE, FALSE)
symmedianC <- Line$new(t$C, symt$C, FALSE, FALSE)
K <- t$symmedianPoint()
opar <- par(mar = c(0,0,0,0))
plot(NULL, asp = 1, xlim = c(-1,5), ylim = c(-3,3),
      xlab = NA, ylab = NA, axes = FALSE)
draw(t, lwd = 2)
draw(symmedianA, lwd = 2, col = "blue")
draw(symmedianB, lwd = 2, col = "blue")
draw(symmedianC, lwd = 2, col = "blue")
points(rbind(K), pch = 19, col = "red")
par(opar)

## -----
## Method `Triangle$MalfattiCircles`
## -----


t <- Triangle$new(c(0,0), c(2,0.5), c(1.5,2))
Mcircles <- t$MalfattiCircles(TRUE)
plot(NULL, asp = 1, xlim = c(0,2.5), ylim = c(0,2.5),
      xlab = NA, ylab = NA)
grid()
draw(t, col = "blue", lwd = 2)
invisible(lapply(Mcircles, draw, col = "green", border = "red"))
invisible(lapply(attr(Mcircles, "tangencyPoints"), function(P){
  points(P[1], P[2], pch = 19)
}))

## -----
## Method `Triangle$trilinearToPoint`
## -----


t <- Triangle$new(c(0,0), c(2,1), c(5,7))
incircle <- t$incircle()
t$trilinearToPoint(1, 1, 1)
incircle$center

## -----
## Method `Triangle$SteinerEllipse`
## -----


t <- Triangle$new(c(0,0), c(2,0.5), c(1.5,2))
ell <- t$SteinerEllipse()
plot(NULL, asp = 1, xlim = c(0,2.5), ylim = c(-0.7,2.4),
      xlab = NA, ylab = NA)
draw(t, col = "blue", lwd = 2)
draw(ell, border = "red", lwd = 2)

## -----
## Method `Triangle$SteinerInellipse`
## -----
```

```
t <- Triangle$new(c(0,0), c(2,0.5), c(1.5,2))
ell <- t$SteinerInellipse()
plot(NULL, asp = 1, xlim = c(0,2.5), ylim = c(-0.1,2.4),
      xlab = NA, ylab = NA)
draw(t, col = "blue", lwd = 2)
draw(ell, border = "red", lwd =2)

## -----
## Method `Triangle$plot'
## -----


trgl <- Triangle$new(c(0, 0), c(1, 0), c(0.5, sqrt(3)/2))
trgl$plot(col = "yellow", border = "red")
```

TriangleThreeLines *Triangle defined by three lines*

Description

Return the triangle formed by three lines.

Usage

```
TriangleThreeLines(line1, line2, line3)
```

Arguments

| | |
|---------------------|--------------|
| line1, line2, line3 | Line objects |
|---------------------|--------------|

Value

A `Triangle` object.

unitCircle *Unit circle*

Description

Circle centered at the origin with radius 1.

Usage

```
unitCircle
```

Format

An object of class `Circle` (inherits from `R6`) of length 25.

Index

* datasets
 unitCircle, 98

abline, 18
Affine, 3
AffineMappingEllipse2Ellipse, 5
AffineMappingThreePoints, 5
Arc, 6
 Circle, 8
 CircleAB, 15
 CircleOA, 16
 crossRatio, 16
 curve, 18
draw, 17
 Ellipse, 18
 EllipseEquationFromFivePoints, 27
 EllipseFromCenterAndMatrix, 28
 EllipseFromEquation, 28
 EllipseFromFivePoints, 29
 EllipseFromFociAndOnePoint, 30
 EllipseFromThreeBoundaryPoints, 30, 95
 EllipticalArc, 31
fitEllipse, 33
GaussianEllipse, 34
Homothety, 34
Hyperbola, 36
HyperbolaFromEquation, 40
intersectionCircleCircle, 41
intersectionCircleLine, 41
intersectionEllipseLine, 42
intersectionLineLine, 43
Inversion, 43, 62
inversionFixingThreeCircles, 46, 47
inversionFixingTwoCircles, 46, 48
 inversionFromCircle, 48
 inversionKeepingCircle, 49
 inversionSwappingTwoCircles, 46, 49, 58
Line, 50, 66
LineFromEquation, 54
LineFromInterceptAndSlope, 55
lines, 18, 38
LownerJohnEllipse, 55
maxAreaInscribedCircle, 56, 57
maxAreaInscribedEllipse, 56, 57
midCircles, 58
Möbius, 59
MöbiusMappingCircle, 62
MöbiusMappingThreePoints, 62, 63
MöbiusSwappingTwoPoints, 64
polygon, 21, 95
polypath, 18
Projection, 64
psolve, 56, 57
radicalCenter, 14, 67
Reflection, 67
Rotation, 70
Scaling, 73
ScalingXY, 75
Shear, 77
soddyCircle, 80
SteinerChain, 80
Translation, 81
Triangle, 83
TriangleThreeLines, 95, 98
unitCircle, 98