

Package ‘statpsych’

December 20, 2023

Type Package

Title Statistical Methods for Psychologists

Version 1.5.0

Description Implements confidence interval and sample size methods that are especially useful in psychological research. The methods can be applied in 1-group, 2-group, paired-samples, and multiple-group designs and to a variety of parameters including means, medians, proportions, slopes, standardized mean differences, standardized linear contrasts of means, plus several measures of correlation and association. The confidence intervals and sample size functions are applicable to single parameters as well as differences, ratios, and linear contrasts of parameters. The sample size functions can be used to approximate the sample size needed to estimate a parameter or function of parameters with desired confidence interval precision or to perform a variety of hypothesis tests (directional two-sided, equivalence, superiority, noninferiority) with desired power. For details see: Statistical Methods for Psychologists, Volumes 1 – 4, <<https://dgbonett.sites.ucsc.edu/>>.

BugReports <https://github.com/dgbonett/statpsych/issues>

License GPL-3

Encoding UTF-8

Imports utils, stats, mnonr, Rdpack, mathjaxr

RoxygenNote 7.2.3

RdMacros Rdpack, mathjaxr

Suggests MASS, testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation no

Author Douglas G. Bonett [aut, cre],
Robert J. Calin-Jageman [ctb]

Maintainer Douglas G. Bonett <dgbonett@ucsc.edu>

Repository CRAN

Date/Publication 2023-12-20 22:20:02 UTC

R topics documented:

ci.2x2.mean.bs	6
ci.2x2.mean.mixed	7
ci.2x2.mean.ws	8
ci.2x2.median.bs	10
ci.2x2.median.mixed	11
ci.2x2.median.ws	12
ci.2x2.prop.bs	13
ci.2x2.prop.mixed	14
ci.2x2.stdmean.bs	15
ci.2x2.stdmean.mixed	17
ci.2x2.stdmean.ws	18
ci.agree	19
ci.agree.3rater	20
ci.agree2	21
ci.bayes.normal	23
ci.bayes.prop1	24
ci.biphi	25
ci.cod1	26
ci.cod2	27
ci.condslope	28
ci.condslope.log	29
ci.cor	30
ci.cor.dep	31
ci.cor2	32
ci.cor2.gen	33
ci.cqv1	34
ci.cramer	35
ci.cronbach	36
ci.cronbach2	37
ci.cv1	38
ci.etasqr	39
ci.fisher	40
ci.indirect	41
ci.kappa	42
ci.lc.gen.bs	43
ci.lc.glm	44
ci.lc.mean.bs	45
ci.lc.median.bs	46
ci.lc.prop.bs	47
ci.lc.reg	48
ci.lc.stdmean.bs	49
ci.lc.stdmean.ws	51
ci.mad1	52
ci.mann	53
ci.mape1	54
ci.mape2	55

ci.mean.ps	56
ci.mean1	57
ci.mean2	58
ci.median.ps	59
ci.median1	60
ci.median2	61
ci.oddsratio	62
ci.pairs.prop.bs	63
ci.pairs.prop1	64
ci.pbcor	65
ci.phi	66
ci.popsiz	67
ci.prop.ps	68
ci.prop1	69
ci.prop1.inv	70
ci.prop2	71
ci.prop2.inv	72
ci.pv	73
ci.random.anova1	74
ci.ratio.cv2	75
ci.ratio.mad.ps	76
ci.ratio.mad2	77
ci.ratio.mean.ps	78
ci.ratio.mean2	79
ci.ratio.median.ps	80
ci.ratio.median2	81
ci.ratio.prop.ps	82
ci.ratio.prop2	83
ci.ratio.sd2	84
ci.rel2	85
ci.reliability	86
ci.rsqr	87
ci.sign1	88
ci.slope.mean.bs	89
ci.slope.prop.bs	90
ci.spcor	91
ci.spear	92
ci.spear2	93
ci.stdmean.ps	94
ci.stdmean.strat	95
ci.stdmean1	96
ci.stdmean2	97
ci.tetra	98
ci.theil	99
ci.tukey	100
ci.var.upper	102
ci.yule	102
etasqr.adj	104

etasqr.gen.2way	104
iqv	105
pi.score.ps	106
pi.score1	107
pi.score2	108
pi.var.upper	109
power.cor1	110
power.cor2	110
power.lc.mean.bs	111
power.mean.ps	112
power.mean1	113
power.mean2	114
power.prop.ps	115
power.prop1	116
power.prop2	116
random.sample	117
random.y	118
random.yx	119
randomize	120
sim.ci.cor	120
sim.ci.mean.ps	121
sim.ci.mean1	123
sim.ci.mean2	124
sim.ci.median.ps	125
sim.ci.median1	126
sim.ci.median2	127
sim.ci.spear	128
sim.ci.stdmean.ps	129
sim.ci.stdmean2	130
size.ci.agree	131
size.ci.condmean	132
size.ci.cor	133
size.ci.cronbach	134
size.ci.cronbach2	135
size.ci.etasqr	136
size.ci.indirect	136
size.ci.lc.ancova	137
size.ci.lc.mean.bs	138
size.ci.lc.mean.ws	139
size.ci.lc.prop.bs	140
size.ci.lc.stdmean.bs	140
size.ci.lc.stdmean.ws	141
size.ci.mape1	142
size.ci.mean.ps	143
size.ci.mean1	144
size.ci.mean2	144
size.ci.pbcor	145
size.ci.prop.ps	146

size.ci.prop1	147
size.ci.prop2	148
size.ci.ratio.mean.ps	148
size.ci.ratio.mean2	149
size.ci.ratio.prop.ps	150
size.ci.ratio.prop2	151
size.ci.rsqr	152
size.ci.second	152
size.ci.slope	153
size.ci.spear	154
size.ci.stdmean.ps	155
size.ci.stdmean2	156
size.equiv.mean.ps	157
size.equiv.mean2	158
size.equiv.prop.ps	159
size.equiv.prop2	160
size.interval.cor	161
size.supinf.mean.ps	161
size.supinf.mean2	162
size.supinf.prop.ps	163
size.supinf.prop2	164
size.test.cor	165
size.test.cor2	166
size.test.cronbach	166
size.test.cronbach2	167
size.test.lc.ancova	168
size.test.lc.mean.bs	169
size.test.lc.mean.ws	170
size.test.lc.prop.bs	171
size.test.mann	172
size.test.mean.ps	173
size.test.mean1	173
size.test.mean2	174
size.test.prop.ps	175
size.test.prop1	176
size.test.prop2	177
size.test.sign.ps	178
size.test.sign1	178
size.test.slope	179
slope.contrast	180
spearmanbrown	181
test.anova1.bs	181
test.kurtosis	182
test.mono.mean.bs	183
test.mono.prop.bs	184
test.prop.bs	185
test.prop.ps	186
test.prop1	187

test.prop2	188
test.skew	189

Index	190
--------------	------------

ci.2x2.mean.bs	<i>Computes tests and confidence intervals of effects in a 2x2 between-subjects design for means</i>
----------------	--

Description

Computes confidence intervals and tests for the AB interaction effect, main effect of A, main effect of B, simple main effects of A, and simple main effects of B in a 2x2 between-subjects design with a quantitative response variable. A Satterthwaite adjustment to the degrees of freedom is used and equality of population variances is not assumed.

Usage

```
ci.2x2.mean.bs(alpha, y11, y12, y21, y22)
```

Arguments

alpha	alpha level for 1-alpha confidence
y11	vector of scores at level 1 of A and level 1 of B
y12	vector of scores at level 1 of A and level 2 of B
y21	vector of scores at level 2 of A and level 1 of B
y22	vector of scores at level 2 of A and level 2 of B

Value

Returns a 7-row matrix (one row per effect). The columns are:

- Estimate - estimate of effect
- SE - standard error
- t - t test statistic
- df - degrees of freedom
- p - p-value
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```

y11 <- c(14, 15, 11, 7, 16, 12, 15, 16, 10, 9)
y12 <- c(18, 24, 14, 18, 22, 21, 16, 17, 14, 13)
y21 <- c(16, 11, 10, 17, 13, 18, 12, 16, 6, 15)
y22 <- c(18, 17, 11, 9, 9, 13, 18, 15, 14, 11)
ci.2x2.mean.bs(.05, y11, y12, y21, y22)

# Should return:
#      Estimate      SE      t      df      p      LL      UL
# AB:      -5.10 2.224860 -2.29227953 35.47894 0.027931810 -9.6145264 -0.5854736
# A:         1.65 1.112430  1.48323970 35.47894 0.146840430 -0.6072632  3.9072632
# B:        -2.65 1.112430 -2.38217285 35.47894 0.022698654 -4.9072632 -0.3927368
# A at b1:   -0.90 1.545244 -0.58243244 17.56296 0.567678242 -4.1522367  2.3522367
# A at b2:    4.20 1.600694  2.62386142 17.93761 0.017246053  0.8362274  7.5637726
# B at a1:   -5.20 1.536952 -3.38331916 17.61093 0.003393857 -8.4341379 -1.9658621
# B at a2:   -0.10 1.608657 -0.06216365 17.91650 0.951120753 -3.4807927  3.2807927

```

ci.2x2.mean.mixed	<i>Computes tests and confidence intervals of effects in a 2x2 mixed design for means</i>
-------------------	---

Description

Computes confidence intervals and tests for the AB interaction effect, main effect of A, main effect of B, simple main effects of A, and simple main effects of B in a 2x2 mixed factorial design with a quantitative response variable where Factor A is a within-subjects factor, and Factor B is a between-subjects factor. A Satterthwaite adjustment to the degrees of freedom is used and equality of population variances is not assumed.

Usage

```
ci.2x2.mean.mixed(alpha, y11, y12, y21, y22)
```

Arguments

alpha	alpha level for 1-alpha confidence
y11	vector of scores at level 1 of A and level 1 of B
y12	vector of scores at level 1 of A and level 2 of B
y21	vector of scores at level 2 of A and level 1 of B
y22	vector of scores at level 2 of A and level 2 of B

Value

Returns a 7-row matrix (one row per effect). The columns are:

- Estimate - estimate of effect
- SE - standard error
- t - t test statistic
- df - degrees of freedom
- p - p-value
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```

y11 <- c(18, 19, 20, 17, 20, 16)
y12 <- c(19, 18, 19, 20, 17, 16)
y21 <- c(19, 16, 16, 14, 16, 18)
y22 <- c(16, 10, 12, 9, 13, 15)
ci.2x2.mean.mixed(.05, y11, y12, y21, y22)

# Should return:
#      Estimate      SE      t      df      p      LL      UL
# AB:    -3.8333333  0.9803627 -3.910117  8.346534  0.0041247610 -6.0778198 -1.588847
# A:      2.0833333  0.4901814  4.250128  8.346534  0.0025414549  0.9610901  3.205577
# B:      3.7500000  1.0226599  3.666908  7.601289  0.0069250119  1.3700362  6.129964
# A at b1: 0.1666667  0.8333333  0.200000  5.000000  0.8493605140 -1.9754849  2.308818
# A at b2: 4.0000000  0.5163978  7.745967  5.000000  0.0005732451  2.6725572  5.327443
# B at a1: 1.8333333  0.9803627  1.870056  9.943850  0.0911668588 -0.3527241  4.019391
# B at a2: 5.6666667  1.2692955  4.464419  7.666363  0.0023323966  2.7173445  8.615989

```

ci.2x2.mean.ws

Computes tests and confidence intervals of effects in a 2x2 within-subjects design for means

Description

Computes confidence intervals and tests for the AB interaction effect, main effect of A, main effect of B, simple main effects of A, and simple main effects of B in a 2x2 within-subjects design with a quantitative response variable.

Usage

```
ci.2x2.mean.ws(alpha, y11, y12, y21, y22)
```

Arguments

alpha	alpha level for 1-alpha confidence
y11	vector of scores at level 1 of A and level 1 of B
y12	vector of scores at level 1 of A and level 2 of B
y21	vector of scores at level 2 of A and level 1 of B
y22	vector of scores at level 2 of A and level 2 of B

Value

Returns a 7-row matrix (one row per effect). The columns are:

- Estimate - estimate of effect
- SE - standard error
- t - t test statistic
- df - degrees of freedom
- p - p-value
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
y11 <- c(1,2,3,4,5,7,7)
y12 <- c(1,0,2,4,3,8,7)
y21 <- c(4,5,6,7,8,9,8)
y22 <- c(5,6,8,7,8,9,9)
ci.2x2.mean.ws(.05, y11, y12, y21, y22)
```

```
# Should return:
#           Estimate      SE      t df      p      LL      UL
# AB:      1.28571429  0.5654449  2.2738102  6 0.0633355395 -0.09787945  2.66930802
# A:      -3.21428571  0.4862042 -6.6109784  6 0.0005765210 -4.40398462 -2.02458681
# B:      -0.07142857  0.2296107 -0.3110855  6 0.7662600658 -0.63326579  0.49040865
# A at b1: -2.57142857  0.2973809 -8.6469203  6 0.0001318413 -3.29909331 -1.84376383
# A at b2: -3.85714286  0.7377111 -5.2285275  6 0.0019599725 -5.66225692 -2.05202879
# B at a1:  0.57142857  0.4285714  1.3333333  6 0.2308094088 -0.47724794  1.62010508
# B at a2: -0.71428571  0.2857143 -2.5000000  6 0.0465282323 -1.41340339 -0.01516804
```

ci.2x2.median.bs *Computes tests and confidence intervals of effects in a 2x2 between-subjects design for medians*

Description

Computes confidence intervals for the AB interaction effect, main effect of A, main effect of B, simple main effects of A, and simple main effects of B in a 2x2 between-subjects design with a quantitative response variable. The effects are defined in terms of medians rather than means.

Usage

```
ci.2x2.median.bs(alpha, y11, y12, y21, y22)
```

Arguments

alpha	alpha level for 1-alpha confidence
y11	vector of scores at level 1 of A and level 1 of B
y12	vector of scores at level 1 of A and level 2 of B
y21	vector of scores at level 2 of A and level 1 of B
y22	vector of scores at level 2 of A and level 2 of B

Value

Returns a 7-row matrix (one row per effect). The columns are:

- Estimate - estimate of effect
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
y11 <- c(14, 15, 11, 7, 16, 12, 15, 16, 10, 9)
y12 <- c(18, 24, 14, 18, 22, 21, 16, 17, 14, 13)
y21 <- c(16, 11, 10, 17, 13, 18, 12, 16, 6, 15)
y22 <- c(18, 17, 11, 9, 9, 13, 18, 15, 14, 11)
ci.2x2.median.bs(.05, y11, y12, y21, y22)

# Should return:
#      Estimate      SE      LL      UL
# AB:      -5.0 3.389735 -11.643758 1.64375833
# A:         1.5 1.694867  -1.821879 4.82187916
# B:        -2.0 1.694867  -5.321879 1.32187916
# A at b1:  -1.0 2.152661  -5.219138 3.21913797
# A at b2:   4.0 2.618464  -1.132095 9.13209504
# B at a1:  -4.5 2.311542  -9.030539 0.03053939
```

```
# B at a2:      0.5 2.479330 -4.359397 5.35939682
```

ci.2x2.median.mixed *Computes confidence intervals in a 2x2 mixed design for medians*

Description

Computes distribution-free confidence intervals based on medians for the AB interaction effect, main effect of A, main effect of B, simple main effects of A, and simple main effects of B in a 2x2 mixed design where Factor A is the within-subjects factor and Factor B is the between subjects factor. Tied scores are assumed to be rare.

Usage

```
ci.2x2.median.mixed(alpha, y11, y12, y21, y22)
```

Arguments

alpha	alpha level for 1-alpha confidence
y11	vector of scores at level 1 of A in group 1
y12	vector of scores at level 2 of A in group 1
y21	vector of scores at level 1 of A in group 2
y22	vector of scores at level 2 of A in group 2

Value

Returns a 7-row matrix (one row per effect). The columns are:

- Estimate - estimate of effect
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Price RM (2020). "Interval estimation for linear functions of medians in within-subjects and mixed designs." *British Journal of Mathematical and Statistical Psychology*, **73**(2), 333–346. ISSN 0007-1102, doi:10.1111/bmsp.12171.

Examples

```

y11 <- c(18, 19, 20, 17, 20, 16)
y12 <- c(19, 18, 19, 20, 17, 16)
y21 <- c(19, 16, 16, 14, 16, 18)
y22 <- c(16, 10, 12, 9, 13, 15)
ci.2x2.median.mixed(.05, y11, y12, y21, y22)

# Should return:
#      Estimate      SE      LL      UL
# AB:      -3.50 2.698647 -8.7892514 1.789251
# A:         1.75 1.349324 -0.8946257 4.394626
# B:         4.25 1.017564  2.2556114 6.244389
# A at b1:   0.00 1.489007 -2.9184005 2.918400
# A at b2:   3.50 2.250679 -0.9112492 7.911249
# B at a1:   2.50 1.486420 -0.4133294 5.413329
# B at a2:   6.00 1.871571  2.3317887 9.668211

```

ci.2x2.median.ws

Computes confidence intervals in a 2x2 within-subjects design for medians

Description

Computes distribution-free confidence intervals based on medians for the AB interaction effect, main effect of A, main effect of B, simple main effects of A, and simple main effects of B in a 2x2 within-subjects design. Tied scores are assumed to be rare.

Usage

```
ci.2x2.median.ws(alpha, y11, y12, y21, y22)
```

Arguments

alpha	alpha level for 1-alpha confidence
y11	vector of scores at level 1 of A and level 1 of B
y12	vector of scores at level 1 of A and level 2 of B
y21	vector of scores at level 2 of A and level 1 of B
y22	vector of scores at level 2 of A and level 2 of B

Value

Returns a 7-row matrix (one row per effect). The columns are:

- Estimate - estimate of effect
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Price RM (2020). “Interval estimation for linear functions of medians in within-subjects and mixed designs.” *British Journal of Mathematical and Statistical Psychology*, **73**(2), 333–346. ISSN 0007-1102, doi:10.1111/bmsp.12171.

Examples

```
y11 <- c(221, 402, 333, 301, 284, 182, 281, 230, 290, 182, 133, 278)
y12 <- c(221, 371, 340, 288, 293, 150, 317, 211, 286, 161, 126, 234)
y21 <- c(219, 371, 314, 279, 284, 155, 278, 185, 296, 169, 118, 229)
y22 <- c(170, 332, 280, 273, 272, 160, 260, 204, 252, 153, 137, 221)
ci.2x2.median.ws(.05, y11, y12, y21, y22)

# Should return:
#           Estimate      SE      LL      UL
# AB:           2.50 21.050122 -38.757482 43.75748
# A:           24.75  9.603490  5.927505 43.57250
# B:           18.25  9.101881  0.410641 36.08936
# A at b1:     26.00 11.813742  2.845491 49.15451
# A at b2:     23.50 16.323093 -8.492675 55.49267
# B at a1:     19.50 15.710347 -11.291715 50.29171
# B at a2:     17.00 11.850202 -6.225970 40.22597
```

ci.2x2.prop.bs

Computes tests and confidence intervals of effects in a 2x2 between-subjects design for proportions

Description

Computes adjusted Wald confidence intervals and tests for the AB interaction effect, main effect of A, main effect of B, simple main effects of A, and simple main effects of B in a 2x2 between-subjects factorial design with a dichotomous response variable. The input vector of frequency counts is $f = [f_{11}, f_{12}, f_{21}, f_{22}]$, and the input vector of sample sizes is $n = [n_{11}, n_{12}, n_{21}, n_{22}]$ where the first subscript represents the levels of Factor A and the second subscript represents the levels of Factor B.

Usage

```
ci.2x2.prop.bs(alpha, f, n)
```

Arguments

alpha	alpha level for 1-alpha confidence
f	vector of frequency counts of participants who have the attribute
n	vector of sample sizes

Value

Returns a 7-row matrix (one row per effect). The columns are:

- Estimate - adjusted estimate of effect
- SE - standard error
- z - z test statistic for test of null hypothesis
- p - p-value
- LL - lower limit of the adjusted Wald confidence interval
- UL - upper limit of the adjusted Wald confidence interval

References

Price RM, Bonett DG (2004). “An improved confidence interval for a linear function of binomial proportions.” *Computational Statistics & Data Analysis*, **45**(3), 449–456. ISSN 01679473, doi:10.1016/S01679473(03)000070.

Examples

```
f <- c(15, 24, 28, 23)
n <- c(50, 50, 50, 50)
ci.2x2.prop.bs(.05, f, n)
```

```
# Should return:
#           Estimate      SE      z      p      LL      UL
# AB:      -0.27450980  0.13692496 -2.0048193  0.044982370 -0.54287780 -0.00614181
# A:       -0.11764706  0.06846248 -1.7184165  0.085720668 -0.25183106  0.01653694
# B:       -0.03921569  0.06846248 -0.5728055  0.566776388 -0.17339968  0.09496831
# A at b1: -0.25000000  0.09402223 -2.6589456  0.007838561 -0.43428019 -0.06571981
# A at b2:  0.01923077  0.09787658  0.1964798  0.844234654 -0.17260380  0.21106534
# B at a1: -0.17307692  0.09432431 -1.8349132  0.066518551 -0.35794917  0.01179533
# B at a2:  0.09615385  0.09758550  0.9853293  0.324462356 -0.09511021  0.28741790
```

ci.2x2.prop.mixed

Computes tests and confidence intervals of effects in a 2x2 mixed factorial design for proportions

Description

Computes adjusted Wald confidence intervals and tests for the AB interaction effect, main effect of A, main effect of B, simple main effects of A, and simple main effects of B in a 2x2 mixed factorial design with a dichotomous response variable where Factor A is a within-subjects factor and Factor B is a between-subjects factor. The 4x1 vector of frequency counts for Factor A within each group is f00, f01, f10, f11 where f_{ij} is the number of participants with a response of i = 0 or 1 at level 1 of Factor A and a response of j = 0 or 1 at level 2 of Factor A.

Usage

```
ci.2x2.prop.mixed(alpha, group1, group2)
```

Arguments

alpha	alpha level for 1-alpha confidence
group1	vector of frequency counts from 2x2 contingency table for Factor A in group 1
group2	vector of frequency counts from 2x2 contingency table for Factor A in group 2

Value

Returns a 7-row matrix (one row per effect). The columns are:

- Estimate - adjusted estimate of effect
- SE - standard error of estimate
- z - z test statistic
- p - p-value
- LL - lower limit of the adjusted Wald confidence interval
- UL - upper limit of the adjusted Wald confidence interval

Examples

```
group1 <- c(125, 14, 10, 254)
group2 <- c(100, 16, 9, 275)
ci.2x2.prop.mixed (.05, group1, group2)
```

Should return:

#	Estimate	SE	z	p	LL	UL
# AB:	0.007555369	0.017716073	0.4264697	0.66976559	-0.02716750	0.042278234
# A:	-0.013678675	0.008858036	-1.5442107	0.12253730	-0.03104011	0.003682758
# B:	-0.058393219	0.023032656	-2.5352360	0.01123716	-0.10353640	-0.013250043
# A at b1:	-0.009876543	0.012580603	-0.7850612	0.43241768	-0.03453407	0.014780985
# A at b2:	-0.017412935	0.012896543	-1.3502018	0.17695126	-0.04268969	0.007863824
# B at a1:	-0.054634236	0.032737738	-1.6688458	0.09514794	-0.11879902	0.009530550
# B at a2:	-0.062170628	0.032328556	-1.9230871	0.05446912	-0.12553343	0.001192177

Description

Computes confidence intervals for standardized linear contrasts of means (AB interaction, main effect of A, main effect of B, simple main effects of A, and simple main effects of B) in a 2x2 between-subjects design with a quantitative response variable. Equality of population variances is not assumed. An unweighed variance standardizer is used, which is the recommended standardizer when both factors are treatment factors.

Usage

```
ci.2x2.stdmean.bs(alpha, y11, y12, y21, y22)
```

Arguments

alpha	alpha level for 1-alpha confidence
y11	vector of scores at level 1 of A and level 1 of B
y12	vector of scores at level 1 of A and level 2 of B
y21	vector of scores at level 2 of A and level 1 of B
y22	vector of scores at level 2 of A and level 2 of B

Value

Returns a 7-row matrix (one row per effect). The columns are:

- Estimate - estimate of standardized effect
- adj Estimate - bias adjusted estimate of standardized effect
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
y11 <- c(14, 15, 11, 7, 16, 12, 15, 16, 10, 9)
y12 <- c(18, 24, 14, 18, 22, 21, 16, 17, 14, 13)
y21 <- c(16, 11, 10, 17, 13, 18, 12, 16, 6, 15)
y22 <- c(18, 17, 11, 9, 9, 13, 18, 15, 14, 11)
ci.2x2.stdmean.bs(.05, y11, y12, y21, y22)

# Should return:
#           Estimate  adj Estimate      SE      LL      UL
# AB:      -1.44976487 -1.4193502 0.6885238 -2.7992468 -0.1002829
# A:         0.46904158  0.4592015 0.3379520 -0.1933321  1.1314153
# B:        -0.75330920 -0.7375055 0.3451209 -1.4297338 -0.0768846
# A at b1: -0.25584086 -0.2504736 0.4640186 -1.1653006  0.6536189
# A at b2:  1.19392401  1.1688767 0.5001423  0.2136630  2.1741850
# B at a1: -1.47819163 -1.4471806 0.4928386 -2.4441376 -0.5122457
# B at a2: -0.02842676 -0.0278304 0.4820369 -0.9732017  0.9163482
```

ci.2x2.stdmean.mixed *Computes confidence intervals of standardized effects in a 2x2 mixed design*

Description

Computes confidence intervals for the standardized AB interaction effect, main effect of A, main effect of B, simple main effects of A, and simple main effects of B in a 2x2 mixed factorial design where Factor A is a within-subjects factor, and Factor B is a between-subjects factor. Equality of population variances is not assumed.

Usage

```
ci.2x2.stdmean.mixed(alpha, y11, y12, y21, y22)
```

Arguments

alpha	alpha level for 1-alpha confidence
y11	vector of scores at level 1 of A in group 1
y12	vector of scores at level 2 of A in group 1
y21	vector of scores at level 1 of A in group 2
y22	vector of scores at level 2 of A in group 2

Value

Returns a 7-row matrix (one row per effect). The columns are:

- Estimate - estimated standardized effect
- adj Estimate - bias adjusted standardized effect estimate
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
y11 <- c(18, 19, 20, 17, 20, 16)
y12 <- c(19, 18, 19, 20, 17, 16)
y21 <- c(19, 16, 16, 14, 16, 18)
y22 <- c(16, 10, 12, 9, 13, 15)
ci.2x2.stdmean.mixed(.05, y11, y12, y21, y22)

# Should return:
#           Estimate adj Estimate      SE      LL      UL
# AB:      -1.95153666  -1.80141845 0.5424100 -3.0146407 -0.8884326
# A:         1.06061775   1.01125934 0.2780119  0.5157244  1.6055111
# B:         1.90911195   1.76225718 0.5743510  0.7834047  3.0348192
```

```
# A at b1:  0.08484942    0.07589163  0.4649598 -0.8264549  0.9961538
# A at b2:  2.03638608    1.82139908  0.2964013  1.4554502  2.6173219
# B at a1:  0.93334362    0.86154796  0.5487927 -0.1422703  2.0089575
# B at a2:  2.88488027    2.66296641  0.7127726  1.4878717  4.2818889
```

ci.2x2.stdmean.ws *Computes confidence intervals of standardized effects in a 2x2 within-subjects design*

Description

Computes confidence intervals for standardized linear contrasts of means (AB interaction, main effect of A, main effect of B, simple main effects of A, and simple main effects of B) in a 2x2 within-subjects design. Equality of population variances is not assumed. An unweighted variance standardizer is used.

Usage

```
ci.2x2.stdmean.ws(alpha, y11, y12, y21, y22)
```

Arguments

alpha	alpha level for 1-alpha confidence
y11	vector of scores at level 1 of A and level 1 of B
y12	vector of scores at level 1 of A and level 2 of B
y21	vector of scores at level 2 of A and level 1 of B
y22	vector of scores at level 2 of A and level 2 of B

Value

Returns a 7-row matrix (one row per effect). The columns are:

- Estimate - estimated standardized effect
- adj Estimate - bias adjusted standardized effect estimate
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```

y11 <- c(21, 39, 32, 29, 27, 17, 27, 21, 28, 17, 12, 27)
y12 <- c(20, 36, 33, 27, 28, 14, 30, 20, 27, 15, 11, 22)
y21 <- c(21, 36, 30, 27, 28, 15, 27, 18, 29, 16, 11, 22)
y22 <- c(18, 34, 29, 28, 28, 17, 27, 21, 26, 16, 14, 23)
ci.2x2.stdmean.ws(.05, y11, y12, y21, y22)

# Should return:
#           Estimate adj Estimate      SE      LL      UL
# AB:      0.17248839  0.16446123 0.13654635 -0.095137544 0.4401143
# A:       0.10924265  0.10415878 0.05752822 -0.003510596 0.2219959
# B:       0.07474497  0.07126653 0.05920554 -0.041295751 0.1907857
# A at b1: 0.19548684  0.18638939 0.08460680  0.029660560 0.3613131
# A at b2: 0.02299845  0.02192816 0.09371838 -0.160686202 0.2066831
# B at a1: 0.16098916  0.15349715 0.09457347 -0.024371434 0.3463498
# B at a2: -0.01149923 -0.01096408 0.08595873 -0.179975237 0.1569768

```

ci.agree

Confidence interval for a G-index of agreement

Description

Computes a confidence interval for a G-index of agreement between two polychotomous ratings. This function requires the number of objects that were given the same rating by both raters.

Usage

```
ci.agree(alpha, n, f, k)
```

Arguments

alpha	alpha level for 1-alpha confidence
n	sample size
f	number of objects rated in agreement
k	number of rating categories

Value

Returns a 1-row matrix. The columns are:

- Estimate - maximum likelihood estimate of G-index
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG (2022). “Statistical inference for G-indices of agreement.” *Journal of Educational and Behavioral Statistics*, **47**(4), 438–458. ISSN 1076-9986, doi:10.3102/10769986221088561.

Examples

```
ci.agree(.05, 100, 80, 4)

# Should return:
# Estimate      SE      LL      UL
# 0.7333333 0.05333333 0.6132949 0.8226025
```

ci.agree.3rater	<i>Computes confidence intervals for a 3-rater design with dichotomous ratings</i>
-----------------	--

Description

Computes adjusted Wald confidence intervals for a G-index of agreement for all pairs of raters in a 3-rater design with a dichotomous rating, and computes adjusted Wald confidence intervals for differences of all pairs of G agreement. An adjusted Wald confidence interval for unanimous G agreement among the three raters is also computed. In the three-rater design, unanimous G agreement is equal to the average of all pairs of G agreement.

Usage

```
ci.agree.3rater(alpha, f)
```

Arguments

alpha	alpha level for 1-alpha confidence
f	vector of frequency counts from 2x2x2 table where f = [f111, f112, f121, f122, f211, f212, f221, f222], first subscript represents rating of rater 1, second subscript represents rating of rater 2, and third subscript represents rating of rater 3

Value

Returns a 3-row matrix. The rows are:

- G(1,2): G-index for raters 1 and 2
- G(1,3): G-index for raters 1 and 3
- G(2,3): G-index for raters 2 and 3
- G(1,2)-G(1,3): difference in G(1,2) and G(1,3)

- $G(1,2)$ - $G(2,3)$: difference in $G(1,2)$ and $G(2,3)$
- $G(2,3)$ - $G(1,3)$: difference in $G(2,3)$ and $G(1,3)$
- $G(3)$: G-index of unanimous agreement for all three raters

The columns are:

- Estimate - estimate of G-index (two-rater, difference, or unanimous)
- LL - lower limit of confidence interval
- UL - upper limit of confidence interval

References

Bonett DG (2022). “Statistical inference for G-indices of agreement.” *Journal of Educational and Behavioral Statistics*, **47**(4), 438–458. ISSN 1076-9986, [doi:10.3102/10769986221088561](https://doi.org/10.3102/10769986221088561).

Examples

```
f <- c(100, 6, 4, 40, 20, 1, 9, 120)
ci.agree.3rater(.05, f)

# Should return:
#           Estimate      LL      UL
# G(1,2)      0.5666667  0.46601839  0.6524027
# G(1,3)      0.50000000  0.39564646  0.5911956
# G(2,3)      0.8666667  0.79701213  0.9135142
# G(1,2)-G(1,3) 0.0666667  0.00580397  0.1266464
# G(1,2)-G(2,3) -0.30000000 -0.40683919 -0.1891873
# G(2,3)-G(1,3) -0.3666667  -0.46222023 -0.2662566
# G(3)        0.64444444  0.57382971  0.7068720
```

ci.agree2

Confidence interval for G-index difference in a 2-group design

Description

Computes adjusted Wald confidence intervals for the G-index of agreement within each group and the difference of G-indices.

Usage

```
ci.agree2(alpha, n1, f1, n2, f2, r)
```

Arguments

alpha	alpha level for simultaneous 1-alpha confidence
n1	sample size (objects) in group 1
f1	number of objects rated in agreement in group 1
n2	sample size (objects) in group 2
f2	number of objects rated in agreement in group 2
r	number of rating categories

Value

Returns a 3-row matrix. The rows are:

- Row 1: G-index for group 1
- Row 2: G-index for group 2
- Row 3: G-index difference

The columns are:

- Estimate - maximum likelihood estimate of G-index and difference
- SE - standard error
- LL - lower limit of confidence interval
- UL - upper limit of confidence interval

References

Bonett DG (2022). “Statistical inference for G-indices of agreement.” *Journal of Educational and Behavioral Statistics*, **47**(4), 438–458. ISSN 1076-9986, [doi:10.3102/10769986221088561](https://doi.org/10.3102/10769986221088561).

Examples

```
ci.agree2(.05, 75, 70, 60, 45, 2)

# Should return:
#      Estimate      SE      LL      UL
# G1      0.8666667 0.02880329 0.6974555 0.9481141
# G2      0.5000000 0.05590170 0.2523379 0.6851621
# G1 - G2 0.3666667 0.06288585 0.1117076 0.6088621
```

ci.bayes.normal	<i>Bayesian credible interval for a normal prior distribution</i>
-----------------	---

Description

Computes an approximate Bayesian credible interval for a normal prior distribution. This function can be used with any parameter estimator (e.g., mean, mean difference, linear contrast of means, slope coefficient standardized mean difference, standardized linear contrast of means, median, median difference, linear contrast of medians, etc.) that has an approximate normal sampling distribution. The mean and standard deviation of the posterior normal distribution are also reported.

Usage

```
ci.bayes.normal(alpha, prior.mean, prior.sd, est, se)
```

Arguments

alpha	alpha level for 1-alpha credibility interval
prior.mean	mean of prior Normal distribution
prior.sd	standard deviation of prior Normal distribution
est	sample estimate
se	standard error of sample estimate

Value

Returns a 1-row matrix. The columns are:

- Posterior mean - posterior mean of Normal distributoin
- Posterior SD - posterior standard deviation of Normal distributoin
- LL - lower limit of the credible interval
- UL - upper limit of the credible interval

References

Gelman A, B. CJ, Stern HS, Rubin DB (2004). *Bayesian Data Analysis*, 2nd edition. Chapman & Hall.

Examples

```
ci.bayes.normal(.05, 30, 2, 24.5, 0.577)

# Should return:
# Posterior mean Posterior SD      LL      UL
#      24.9226      0.5543895 23.83602 26.00919
```

ci.bayes.prop1 *Bayesian credible interval for a single proportion*

Description

Computes a Bayesian credible interval for a single proportion using the mean and standard deviation of a prior Beta distribution along with sample information. The mean and standard deviation of the posterior Beta distribution are also reported. For a noninformative prior, set the prior mean to .5 and the prior standard deviation to 1/sqrt(12) (which corresponds to a Beta(1,1) distribution). The prior variance must be less than $m(1 - m)$ where m is the prior mean.

Usage

```
ci.bayes.prop1(alpha, prior.mean, prior.sd, f, n)
```

Arguments

alpha	alpha level for 1-alpha credibility interval
prior.mean	mean of prior Beta distribution
prior.sd	standard deviation of prior Beta distribution
f	number of participants who have the attribute
n	sample size

Value

Returns a 1-row matrix. The columns are:

- Posterior mean - posterior mean of Beta distributoin
- Posterior SD - posterior standard deviation of Beta distributoin
- LL - lower limit of the credible interval
- UL - upper limit of the credible interval

References

Gelman A, B. CJ, Stern HS, Rubin DB (2004). *Bayesian Data Analysis*, 2nd edition. Chapman & Hall.

Examples

```
ci.bayes.prop1(.05, .4, .1, 12, 100)

# Should return:
# Posterior mean Posterior SD      LL      UL
#           0.15    0.03273268  0.09218 0.2188484
```

`ci.biphi`*Confidence interval for a biserial-phi correlation*

Description

Computes a confidence interval for a biserial-phi correlation using a transformation of a confidence interval for an odds ratio with .5 added to each cell frequency. This measure of association assumes the group variable is naturally dichotomous and the response variable is artificially dichotomous.

Usage

```
ci.biphi(alpha, f1, f2, n1, n2)
```

Arguments

alpha	alpha level for 1-alpha confidence
f1	number of participants in group 1 who have the attribute
f2	number of participants in group 2 who have the attribute
n1	sample size for group 1
n2	sample size for group 2

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimate of biserial-phi correlation
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Ulrich R, Wirtz M (2004). "On the correlation of a naturally and an artificially dichotomized variable." *British Journal of Mathematical and Statistical Psychology*, **57**(2), 235–251. ISSN 00071102, doi:[10.1348/0007110042307203](https://doi.org/10.1348/0007110042307203).

Examples

```
ci.biphi(.05, 46, 15, 100, 100)

# Should return:
# Estimate      SE      LL      UL
# 0.4145733 0.07551281 0.2508866 0.546141
```

`ci.cod1`*Confidence interval for a single coefficient of dispersion*

Description

Computes a confidence interval for a population coefficient of dispersion which is defined as a mean absolute deviation from the median divided by a median. The coefficient of dispersion assumes ratio-scale scores and is a robust alternative to the coefficient of variation. An approximate standard error is recovered from the confidence interval.

Usage

```
ci.cod1(alpha, y)
```

Arguments

<code>alpha</code>	alpha level for 1-alpha confidence
<code>y</code>	vector of scores

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated coefficient of dispersion
- SE - recovered standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Seier E (2006). "Confidence interval for a coefficient of dispersion in nonnormal distributions." *Biometrical Journal*, **48**(1), 144–148. ISSN 0323-3847, [doi:10.1002/bimj.200410148](https://doi.org/10.1002/bimj.200410148).

Examples

```
y <- c(30, 20, 15, 10, 10, 60, 20, 25, 20, 30, 10, 5, 50, 40,
      20, 10, 0, 20, 50)
ci.cod1(.05, y)

# Should return:
# Estimate      SE      LL      UL
# 0.5921053 0.1814708 0.3813259 1.092679
```

ci.cod2	<i>Confidence interval for a ratio of dispersion coefficients in a 2-group design</i>
---------	---

Description

Computes a confidence interval for a ratio of population dispersion coefficients (mean absolute deviation from median divided by median) in a 2-group design. Ratio-scale scores are assumed.

Usage

```
ci.cod2(alpha, y1, y2)
```

Arguments

alpha	alpha level for 1-alpha confidence
y1	vector of scores in group 1
y2	vector of scores in group 2

Value

Returns a 1-row matrix. The columns are:

- COD1 - estimated coefficient of dispersion in group 1
- COD2 - estimated coefficient of dispersion in group 2
- COD1/COD2 - estimated ratio of dispersion coefficients
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
y1 <- c(32, 39, 26, 35, 43, 27, 40, 37, 34, 29)
y2 <- c(36, 44, 47, 42, 49, 39, 46, 31, 33, 48)
ci.cod2(.05, y1, y2)

# Should return:
#   COD1      COD2 COD1/COD2      LL      UL
# 0.1333333 0.1232558  1.081761 0.494964 2.282254
```

 ci.condslope

Confidence interval for conditional (simple) slopes in a linear model

Description

Computes confidence intervals and test statistics for population conditional slopes (simple slopes) in a general linear model that includes a predictor variable (x1), a moderator variable (x2), and a product predictor variable (x1*x2). Conditional slopes are computed at specified low and high values of the moderator variable.

Usage

```
ci.condslope(alpha, b1, b2, se1, se2, cov, lo, hi, dfe)
```

Arguments

alpha	alpha level for 1-alpha confidence
b1	estimated slope coefficient for predictor variable
b2	estimated slope coefficient for product variable
se1	standard error for predictor coefficient
se2	standard error for product coefficient
cov	estimated covariance between predictor and product coefficients
lo	low value of moderator variable
hi	high value of moderator variable
dfe	error degrees of freedom

Value

Returns a 2-row matrix. The columns are:

- Estimate - estimated conditional slope
- t - t test statistic
- p - p-value
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
ci.condslope(.05, .132, .154, .031, .021, .015, 5.2, 10.6, 122)

# Should return:
#           Estimate      SE      t  df      p
# At low moderator    0.9328 0.4109570 2.269824 122 0.024973618
# At high moderator   1.7644 0.6070517 2.906507 122 0.004342076
#           LL      UL
```

```
# At low moderator    0.1192696 1.746330
# At high moderator   0.5626805 2.966119
```

ci.condslope.log *Confidence interval for conditional (simple) slopes in a logistic model*

Description

Computes confidence intervals and test statistics for population conditional slopes (simple slopes) in a logistic model that includes a predictor variable (x1), a moderator variable (x2), and a product predictor variable (x1*x2). Conditional slopes are computed at low and high values of the moderator variable.

Usage

```
ci.condslope.log(alpha, b1, b2, se1, se2, cov, lo, hi)
```

Arguments

alpha	alpha level for 1-alpha confidence
b1	estimated slope coefficient for predictor variable
b2	estimated slope coefficient for product variable
se1	standard error for predictor coefficient
se2	standard error for product coefficient
cov	estimated covariance between predictor and product coefficients
lo	low value of moderator variable
hi	high value of moderator variable

Value

Returns a 2-row matrix. The columns are:

- Estimate - estimated conditional slope
- exp(Estimate) - estimated exponentiated conditional slope
- z - z test statistic
- p - p-value
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```

ci.condslope.log(.05, .132, .154, .031, .021, .015, 5.2, 10.6)

# Should return:
#           Estimate exp(Estimate)      z      p
# At low moderator  0.9328      2.541616 2.269824 0.023218266
# At high moderator 1.7644      5.838068 2.906507 0.003654887
#           LL      UL
# At low moderator  1.135802  5.687444
# At high moderator 1.776421 19.186357

```

ci.cor

Confidence interval for a Pearson or partial correlation

Description

Computes a Fisher confidence interval for a population Pearson correlation or partial correlation with s control variables. Set $s = 0$ for a Pearson correlation. A bias adjustment is used to reduce the bias of the Fisher transformed correlation. This function uses an estimated correlation as input. Use the `cor.test` function for raw data input.

Usage

```
ci.cor(alpha, cor, s, n)
```

Arguments

alpha	alpha level for 1-alpha confidence
cor	estimated Pearson or partial correlation
s	number of control variables
n	sample size

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated correlation
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Snedecor GW, Cochran WG (1989). *Statistical Methods*, 8th edition. ISU University Pres, Ames, Iowa.

Examples

```
ci.cor(.05, .536, 0, 50)

# Should return:
# Estimate      SE      LL      UL
# 0.536 0.1018149 0.2978573 0.7058914
```

ci.cor.dep

Confidence interval for a difference in dependent Pearson correlations

Description

Computes a confidence interval for a difference in population Pearson correlations that are estimated from the same sample and have one variable in common. A bias adjustment is used to reduce the bias of each Fisher transformed correlation. An approximate standard error is recovered from the confidence interval.

Usage

```
ci.cor.dep(alpha, cor1, cor2, cor12, n)
```

Arguments

alpha	alpha level for 1-alpha confidence
cor1	estimated Pearson correlation between y and x1
cor2	estimated Pearson correlation between y and x2
cor12	estimated Pearson correlation between x1 and x2
n	sample size

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated correlation difference
- SE - recovered standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Zou GY (2007). "Toward using confidence intervals to compare correlations." *Psychological Methods*, 12(4), 399–413. ISSN 1939-1463, doi:[10.1037/1082989X.12.4.399](https://doi.org/10.1037/1082989X.12.4.399).

Examples

```
ci.cor.dep(.05, .396, .179, .088, 166)

# Should return:
# Estimate      SE      LL      UL
# 0.217 0.1026986 0.01323072 0.415802
```

ci.cor2

Confidence interval for a 2-group Pearson correlation difference

Description

Computes a confidence interval for a difference in population Pearson correlations in a 2-group design. A bias adjustment is used to reduce the bias of each Fisher transformed correlation.

Usage

```
ci.cor2(alpha, cor1, cor2, n1, n2)
```

Arguments

alpha	alpha level for 1-alpha confidence
cor1	estimated Pearson correlation in group 1
cor2	estimated Pearson correlation in group 2
n1	sample size for group 1
n2	sample size for group 2

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated correlation difference
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Zou GY (2007). "Toward using confidence intervals to compare correlations." *Psychological Methods*, 12(4), 399–413. ISSN 1939-1463, doi:[10.1037/1082989X.12.4.399](https://doi.org/10.1037/1082989X.12.4.399).

Examples

```
ci.cor2(.05, .886, .802, 200, 200)

# Should return:
# Estimate      SE      LL      UL
# 0.084 0.02967934 0.02803246 0.1463609
```

ci.cor2.gen

Confidence interval for a 2-group correlation difference

Description

Computes a 100(1 - alpha)% confidence interval for a difference in population correlations in a 2-group design. The correlations can be Pearson, Spearman, partial, semipartial, or point-biserial correlations. The function requires a point estimate and a 100(1 - alpha)% confidence interval for each correlation as input.

Usage

```
ci.cor2.gen(cor1, ll1, ul1, cor2, ll2, ul2)
```

Arguments

cor1	estimated correlation for group 1
ll1	lower limit for group 1 correlation
ul1	upper limit for group 1 correlation
cor2	estimated correlation for group 2
ll2	lower limit for group 2 correlation
ul2	upper limit for group 2 correlation

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated correlation difference
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Zou GY (2007). "Toward using confidence intervals to compare correlations." *Psychological Methods*, 12(4), 399–413. ISSN 1939-1463, doi:[10.1037/1082989X.12.4.399](https://doi.org/10.1037/1082989X.12.4.399).

Examples

```
ci.cor2.gen(.4, .35, .47, .2, .1, .32)

# Should return:
# Estimate  LL      UL
#      0.2 0.07 0.3220656
```

ci.cqv1

Confidence interval for a single coefficient of quartile variation

Description

Computes a distribution-free confidence interval for a population coefficient of quartile variation which is defined as $(Q3 - Q1)/(Q3 + Q1)$ where $Q1$ is the 25th percentile and $Q3$ is the 75th percentile. The coefficient of quartile variation assumes ratio-scale scores and is a robust alternative to the coefficient of variation. The 25th and 75th percentiles are computed using the type = 2 method (SAS default).

Usage

```
ci.cqv1(alpha, y)
```

Arguments

alpha	alpha level for 1-alpha confidence
y	vector of scores

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated coefficient of quartile variation
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG (2006). "Confidence interval for a coefficient of quartile variation." *Computational Statistics and Data Analysis*, **50**(11), 2953–2957. doi:10.1016/j.csda.2005.05.007.

Examples

```

y <- c(30, 20, 15, 10, 10, 60, 20, 25, 20, 30, 10, 5, 50, 40,
      20, 10, 0, 20, 50)
ci.cqv1(.05, y)

# Should return:
# Estimate      SE      LL      UL
#      0.5 0.1552485 0.2617885 0.8841821

```

ci.cramer

Confidence interval for Cramer's V

Description

Computes a confidence interval for a population Cramer's V coefficient of nominal association for an $r \times s$ contingency table and its approximate standard error. The confidence interval is based on a noncentral chi-square distribution, and an approximate standard error is recovered from the confidence interval.

Usage

```
ci.cramer(alpha, chisqr, r, c, n)
```

Arguments

alpha	alpha value for 1-alpha confidence
chisqr	Pearson chi-square test statistic of independence
r	number of rows in contingency table
c	number of columns in contingency table
n	sample size

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimate of Cramer's V
- SE - recovered standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Smithson M (2003). *Confidence Intervals*. Sage.

Examples

```
ci.cramer(.05, 19.21, 2, 3, 200)

# Should return:
# Estimate    SE    LL    UL
# 0.3099 0.0718 0.1601 0.4417
```

ci.cronbach	<i>Confidence interval for a Cronbach reliability</i>
-------------	---

Description

Computes a confidence interval for a population Cronbach reliability. The point estimate of Cronbach's reliability assumes essentially tau-equivalent measurements and this confidence interval assumes parallel measurements.

Usage

```
ci.cronbach(alpha, rel, r, n)
```

Arguments

alpha	alpha level for 1-alpha confidence
rel	estimated Cronbach's reliability
r	number of measurements (items, raters, etc.)
n	sample size

Value

Returns a 1-row matrix. The columns are:

- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Feldt LS (1965). "The approximate sampling distribution of Kuder-Richardson reliability coefficient twenty." *Psychometrika*, **30**(3), 357–370. ISSN 0033-3123, doi:[10.1007/BF02289499](https://doi.org/10.1007/BF02289499).

Examples

```
ci.cronbach(.05, .85, 7, 89)

# Should return:
# Estimate      SE      LL      UL
#      0.85  0.02456518 0.7971254 0.8931436
```

ci.cronbach2	<i>Confidence interval for a difference in Cronbach reliabilities in a 2-group design</i>
--------------	---

Description

Computes a confidence interval for a difference in population Cronbach reliability coefficients in a 2-group design. The number of measurements (e.g., items or raters) used in each group need not be equal.

Usage

```
ci.cronbach2(alpha, rel1, rel2, r1, r2, n1, n2)
```

Arguments

alpha	alpha level for 1-alpha confidence
rel1	estimated Cronbach reliability for group 1
rel2	estimated Cronbach reliability for group 2
r1	number of measurements used in group 1
r2	number of measurements used in group 2
n1	sample size for group 1
n2	sample size for group 2

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated reliability difference
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Wright TA (2015). "Cronbach's alpha reliability: Interval estimation, hypothesis testing, and sample size planning." *Journal of Organizational Behavior*, **36**(1), 3–15. ISSN 08943796, [doi:10.1002/job.1960](https://doi.org/10.1002/job.1960).

Examples

```
ci.cronbach2(.05, .88, .76, 8, 8, 200, 250)

# Should return:
# Estimate      LL      UL
#    0.12 0.06973411 0.173236
```

ci.cv1

Confidence interval for a single coefficient of variation

Description

Computes a confidence interval for a population coefficient of variation (standard deviation divided by mean). This confidence interval is the reciprocal of a confidence interval for a standardized mean (see description of ci.stdmean1 function). An approximate standard error is recovered from the confidence interval. The coefficient of variation assumes ratio-scale scores.

Usage

```
ci.cv1(alpha, m, sd, n)
```

Arguments

alpha	alpha level for 1-alpha confidence
m	estimated mean
sd	estimated standard deviation
n	sample size

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated coefficient of variation
- SE - recovered standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
ci.cv1(.05, 24.5, 3.65, 40)

# Should return:
# Estimate      SE      LL      UL
# 0.1489796 0.01817373 0.1214381 0.1926778
```

 ci.etasqr

Confidence interval for eta-squared

Description

Computes a confidence interval for a population eta-squared, partial eta-squared, or generalized eta-squared in a fixed-factor between-subjects design. An approximate bias adjusted estimate is computed, and an approximate standard error is recovered from the confidence interval.

Usage

```
ci.etasqr(alpha, etasqr, df1, df2)
```

Arguments

alpha	alpha value for 1-alpha confidence
etasqr	estimated eta-squared
df1	degrees of freedom for effect
df2	error degrees of freedom

Value

Returns a 1-row matrix. The columns are:

- Eta-squared - eta-squared (from input)
- adj Eta-squared - bias adjusted eta-squared estimate
- SE - recovered standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
ci.etasqr(.05, .241, 3, 116)

# Should return:
# Eta-squared  adj Eta-squared      SE      LL      UL
#      0.241      0.2213707 0.06258283 0.1040229 0.3493431
```

`ci.fisher`*Fisher confidence interval*

Description

Computes a Fisher confidence interval for any type of correlation (e.g., Pearson, Spearman, Kendall-tau, tetrachoric, phi, partial, semipartial, etc.) or ordinal association such as gamma, Somers' d, or tau-b. The correlation could also be between two latent factors obtained from a SEM analysis (the Fisher CI will be more accurate than the large-sample CI from a SEM analysis). The standard error can be a traditional standard error, a bootstrap standard error, or a robust standard error from a SEM analysis.

Usage

```
ci.fisher(alpha, cor, se)
```

Arguments

<code>alpha</code>	alpha value for 1-alpha confidence
<code>cor</code>	estimated correlation or association coefficient
<code>se</code>	standard error of correlation or association coefficient

Value

Returns a 1-row matrix. The columns are:

- Estimate - correlation (from input)
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
ci.fisher(.05, .641, .052)

# Should return:
# Estimate      LL      UL
# 0.641 0.5276396 0.7319293
```

`ci.indirect`*Confidence interval for an indirect effect*

Description

Computes a Monte Carlo confidence interval (500,000 trials) for a population unstandardized indirect effect in a path model and a Sobel standard error. This function is not recommended for a standardized indirect effect. The Monte Carlo method is general in that the slope estimates and standard errors do not need to be OLS estimates with homoscedastic standard errors. For example, LAD slope estimates and their standard errors, OLS slope estimates and heteroscedastic-consistent standard errors, and (in models with no direct effects) distribution-free Theil-Sen slope estimates with recovered standard errors also could be used.

Usage

```
ci.indirect(alpha, b1, b2, se1, se2)
```

Arguments

<code>alpha</code>	alpha level for 1-alpha confidence
<code>b1</code>	unstandardized slope estimate for first path
<code>b2</code>	unstandardized slope estimate for second path
<code>se1</code>	standard error for b1
<code>se2</code>	standard error for b2

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated indirect effect
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
ci.indirect (.05, 2.48, 1.92, .586, .379)

# Should return (within sampling error):
# Estimate      SE      LL      UL
# 4.7616 1.625282 2.178812 7.972262
```

 ci.kappa

Confidence interval for a kappa reliability

Description

Computes a confidence interval for the intraclass kappa coefficient and Cohen's kappa coefficient for two dichotomous ratings. Both measures are intraclass reliability coefficients.

Usage

```
ci.kappa(alpha, f00, f01, f10, f11)
```

Arguments

alpha	alpha level for 1-alpha confidence
f00	number of objects rated y = 0 and x = 0
f01	number of objects rated y = 0 and x = 1
f10	number of objects rated y = 1 and x = 0
f11	number of objects rated y = 1 and x = 1

Value

Returns a 2-row matrix. The results in row 1 are for the intraclass kappa. The results in row 2 are for Cohen's kappa. The columns are:

- Estimate - estimate of interrater reliability
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Fleiss JL, Paik MC (2003). *Statistical Methods for Rates and Proportions*, 3rd edition. Wiley.

Examples

```
ci.kappa(.05, 31, 12, 4, 58)

# Should return:
#           Estimate      SE      LL      UL
# IC kappa:  0.6736597 0.07479965 0.5270551 0.8202643
# Cohen kappa: 0.6756757 0.07344761 0.5317210 0.8196303
```

ci.lc.gen.bs	<i>Confidence interval for a linear contrast of parameters in a between-subjects design</i>
--------------	---

Description

Computes the estimate, standard error, and approximate confidence interval for a linear contrast of any type of parameter (e.g., quartile, ordinal regression slope, path coefficient, G-index) where each parameter value has been estimated from a different sample. The parameter values are assumed to be of the same type (e.g., all unstandardized path coefficients) and their sampling distributions are assumed to be approximately normal.

Usage

```
ci.lc.gen.bs(alpha, est, se, v)
```

Arguments

alpha	alpha level for simultaneous 1-alpha confidence
est	vector of parameter estimates
se	vector of standard errors
v	vector of contrast coefficients

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimate of linear contrast
- SE - standard error of linear contrast
- LL - lower limit of confidence interval
- UL - upper limit of confidence interval

Examples

```
est <- c(3.86, 4.57, 2.29, 2.88)
se <- c(0.185, 0.365, 0.275, 0.148)
v <- c(.5, .5, -.5, -.5)
ci.lc.gen.bs(.05, est, se, v)

# Should return:
# Estimate      SE      LL      UL
#      1.63 0.2573806 1.125543 2.134457
```

ci.lc.glm	<i>Confidence interval for a linear contrast of general linear model parameters</i>
-----------	---

Description

Computes the estimate, standard error, and confidence interval for a linear contrast of parameters in a general linear model using `coef(object)` and `vcov(object)` where "object" is a fitted model object from the `lm` function.

Usage

```
ci.lc.glm(alpha, n, b, V, q)
```

Arguments

alpha	alpha for 1 - alpha confidence
n	sample size
b	vector of parameter estimates from <code>coef(object)</code>
V	covariance matrix of parameter estimates from <code>vcov(object)</code>
q	vector of coefficients

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimate of linear function
- SE - standard error
- t - t test statistic
- df - degrees of freedom
- p - p-value
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
y <- c(43, 62, 49, 60, 36, 79, 55, 42, 67, 50)
x1 <- c(3, 6, 4, 6, 2, 7, 4, 2, 7, 5)
x2 <- c(4, 6, 3, 7, 1, 9, 3, 3, 8, 4)
out <- lm(y ~ x1 + x2)
b <- coef(out)
V <- vcov(out)
n <- length(y)
q <- c(0, .5, .5)
b
ci.lc.glm(.05, n, b, V, q)
```

```

# Should return:
# (Intercept)      x1      x2
# 26.891111  3.648889  2.213333
# > ci.lc.glm(.05, n, b, V, q)
# Estimate      SE      t df      p      LL      UL
# 2.931111 0.4462518 6.56829 7 0.000313428 1.875893 3.986329

```

ci.lc.mean.bs	<i>Confidence interval for a linear contrast of means in a between-subjects design</i>
---------------	--

Description

Computes a test statistic and confidence interval for a linear contrast of means. This function computes both unequal variance and equal variance confidence intervals and test statistics. A Satterthwaite adjustment to the degrees of freedom is used with the unequal variance method.

Usage

```
ci.lc.mean.bs(alpha, m, sd, n, v)
```

Arguments

alpha	alpha level for 1-alpha confidence
m	vector of estimated group means
sd	vector of estimated group standard deviations
n	vector of sample sizes
v	vector of between-subjects contrast coefficients

Value

Returns a 2-row matrix. The columns are:

- Estimate - estimated linear contrast
- SE - standard error
- t - t test statistic
- df - degrees of freedom
- p - p-value
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Snedecor GW, Cochran WG (1989). *Statistical Methods*, 8th edition. ISU University Pres, Ames, Iowa.

Examples

```
m <- c(33.5, 37.9, 38.0, 44.1)
sd <- c(3.84, 3.84, 3.65, 4.98)
n <- c(10,10,10,10)
v <- c(.5, .5, -.5, -.5)
ci.lc.mean.bs(.05, m, sd, n, v)

# Should return:
#
#           Estimate      SE      t      df
# Equal Variances Assumed:    -5.35  1.300136  -4.114955  36.00000
# Equal Variances Not Assumed:  -5.35  1.300136  -4.114955  33.52169
#
#           p           LL           UL
# Equal Variances Assumed:    0.0002152581  -7.986797  -2.713203
# Equal Variances Not Assumed: 0.0002372436  -7.993583  -2.706417
```

ci.lc.median.bs	<i>Confidence interval for a linear contrast of medians in a between-subjects design</i>
-----------------	--

Description

Computes a confidence interval for a linear contrast of medians in a between-subjects design using estimated medians and their standard errors. The sample median and standard error for each group can be computed using the ci.median1 function.

Usage

```
ci.lc.median.bs(alpha, m, se, v)
```

Arguments

alpha	alpha level for 1-alpha confidence
m	vector of estimated group medians
se	vector of group standard errors
v	vector of between-subjects contrast coefficients

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated linear contrast of medians
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Price RM (2002). “Statistical inference for a linear function of medians: Confidence intervals, hypothesis testing, and sample size requirements.” *Psychological Methods*, 7(3), 370–383. ISSN 1939-1463, doi:10.1037/1082989X.7.3.370.

Examples

```
m <- c(46.13, 29.19, 30.32, 49.15)
se <- c(6.361, 5.892, 4.887, 6.103)
v <- c(1, -1, -1, 1)
ci.lc.median.bs(.05, m, se, v)

# Should return:
# Estimate      SE      LL      UL
# 35.77 11.67507 12.88727 58.65273
```

ci.lc.prop.bs

Confidence interval for a linear contrast of proportions in a between-subjects design

Description

Computes an adjusted Wald confidence interval for a linear contrast of proportions in a between-subjects design.

Usage

```
ci.lc.prop.bs(alpha, f, n, v)
```

Arguments

alpha	alpha level for 1-alpha confidence
f	vector of frequency counts of participants who have the attribute
n	vector of sample sizes
v	vector of between-subjects contrast coefficients

Value

Returns a 1-row matrix. The columns are:

- Estimate - adjusted estimate of proportion linear contrast
- SE - adjusted standard error
- z - z test statistic
- p - p-value
- LL - lower limit of the adjusted Wald confidence interval
- UL - upper limit of the adjusted Wald confidence interval

References

Price RM, Bonett DG (2004). “An improved confidence interval for a linear function of binomial proportions.” *Computational Statistics & Data Analysis*, **45**(3), 449–456. ISSN 01679473, doi:[10.1016/S01679473\(03\)000070](https://doi.org/10.1016/S01679473(03)000070).

Examples

```
f <- c(26, 24, 38)
n <- c(60, 60, 60)
v <- c(-.5, -.5, 1)
ci.lc.prop.bs(.05, f, n, v)

# Should return:
# Estimate      SE      z      p      LL      UL
# 0.2119565 0.07602892 2.787841 0.005306059 0.06294259 0.3609705
```

ci.lc.reg

Confidence interval for a linear contrast of regression coefficients in multiple group regression model

Description

Compute a confidence interval and test statistic for a linear contrast of a population regression coefficients (y-intercept or slope) across groups in a multiple group regression model. Equality of error variances across groups is not assumed. A Satterthwaite adjustment to the degrees of freedom is used to improve the accuracy of the confidence interval.

Usage

```
ci.lc.reg(alpha, est, se, n, s, v)
```

Arguments

alpha	alpha level for 1-alpha confidence
est	vector of parameter estimates
se	vector of standard errors
n	vector of group sample sizes
s	number of predictor variables for each within-group model
v	vector of contrast coefficients

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated linear contrast
- SE - standard error
- t - t test statistic
- df - degrees of freedom
- p - p-value
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
est <- c(1.74, 1.83, 0.482)
se <- c(.483, .421, .395)
n <- c(40, 40, 40)
v <- c(.5, .5, -1)
ci.lc.reg(.05, est, se, n, 4, v)

# Should return:
# Estimate      SE          t      df          p          LL          UL
# 1.303 0.5085838 2.562016 78.8197 0.01231256 0.2906532 2.315347
```

ci.lc.stdmean.bs	<i>Confidence interval for a standardized linear contrast of means in a between-subjects design</i>
------------------	---

Description

Computes confidence intervals for a population standardized linear contrast of means in a between-subjects design. The unweighted standardizer is recommended in experimental designs. The weighted standardizer is recommended in nonexperimental designs with simple random sampling. The group 1 standardizer is useful in both experimental and nonexperimental designs. Equality of variances is not assumed.

Usage

```
ci.lc.stdmean.bs(alpha, m, sd, n, v)
```

Arguments

alpha	alpha level for 1-alpha confidence
m	vector of estimated group means
sd	vector of estimated group standard deviation
n	vector of sample sizes
v	vector of between-subjects contrast coefficients

Value

Returns a 3-row matrix. The columns are:

- Estimate - estimated standardized linear contrast
- adj Estimate - bias adjusted standardized linear contrast estimate
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG (2008). "Confidence intervals for standardized linear contrasts of means." *Psychological Methods*, **13**(2), 99–109. ISSN 1939-1463, doi:[10.1037/1082989X.13.2.99](https://doi.org/10.1037/1082989X.13.2.99).

Examples

```
m <- c(33.5, 37.9, 38.0, 44.1)
sd <- c(3.84, 3.84, 3.65, 4.98)
n <- c(10,10,10,10)
v <- c(.5, .5, -.5, -.5)
ci.lc.stdmean.bs(.05, m, sd, n, v)

# Should return:
#           Estimate  adj Estimate      SE      LL      UL
# Unweighted standardizer: -1.301263   -1.273964  0.3692800 -2.025039 -0.5774878
# Weighted standardizer:   -1.301263   -1.273964  0.3514511 -1.990095 -0.6124317
# Group 1 standardizer:    -1.393229   -1.273810  0.4849842 -2.343781 -0.4426775
```

ci.lc.stdmean.ws	<i>Confidence interval for a standardized linear contrast of means in a within-subjects design</i>
------------------	--

Description

Computes confidence intervals for two types of population standardized linear contrast of means (unweighted standardizer and level 1 standardizer) in a within-subjects design. Equality of variances is not assumed, but the correlations among the repeated measures are assumed to be approximately equal.

Usage

```
ci.lc.stdmean.ws(alpha, m, sd, cor, n, q)
```

Arguments

alpha	alpha level for 1-alpha confidence
m	vector of within-subjects estimated means
sd	vector of within-subjects estimated standard deviations
cor	average estimated correlation of all measurement pairs
n	sample size
q	vector of within-subjects contrast coefficients

Value

Returns a 2-row matrix. The columns are:

- Estimate - estimated standardized linear contrast
- adj Estimate - bias adjusted standardized linear contrast estimate
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG (2008). "Confidence intervals for standardized linear contrasts of means." *Psychological Methods*, **13**(2), 99–109. ISSN 1939-1463, [doi:10.1037/1082989X.13.2.99](https://doi.org/10.1037/1082989X.13.2.99).

Examples

```

m <- c(33.5, 37.9, 38.0, 44.1)
sd <- c(3.84, 3.84, 3.65, 4.98)
q <- c(.5, .5, -.5, -.5)
ci.lc.stdmean.ws(.05, m, sd, .672, 20, q)

# Should return:
#           Estimate adj Estimate      SE      LL      UL
# Unweighted standardizer: -1.301263   -1.266557  0.3147937 -1.918248 -0.6842788
# Level 1 standardizer:   -1.393229   -1.337500  0.3661824 -2.110934 -0.6755248

```

ci.mad1

Confidence interval for a single mean absolute deviation

Description

Computes a confidence interval for a population mean absolute deviation from the median (MAD). The MAD is a robust alternative to the standard deviation.

Usage

```
ci.mad1(alpha, y)
```

Arguments

alpha	alpha level for 1-alpha confidence
y	vector of scores

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated mean absolute deviation
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Seier E (2003). "Confidence intervals for mean absolute deviations." *The American Statistician*, **57**(4), 233–236. ISSN 0003-1305, doi:[10.1198/0003130032323](https://doi.org/10.1198/0003130032323).

Examples

```

y <- c(30, 20, 15, 10, 10, 60, 20, 25, 20, 30, 10, 5, 50, 40,
      20, 10, 0, 20, 50)
ci.mad1(.05, y)

# Should return:
# Estimate      SE      LL      UL
#      12.5 2.876103 7.962667 19.62282

```

ci.mann

Confidence interval for a Mann-Whitney parameter

Description

Computes a distribution-free confidence interval for the Mann-Whitney parameter (a "common language effect size"). In a 2-group experiment, this parameter is the proportion of members in the population with scores that would be higher under treatment 1 than treatment 2. In a 2-group nonexperiment where participants are sampled from two subpopulations of sizes N_1 and N_2 , the parameter is the proportion of all $N_1 \times N_2$ pairs in which a member from subpopulation 1 has a larger score than a member from subpopulation 2.

Usage

```
ci.mann(alpha, y1, y2)
```

Arguments

alpha	alpha level for 1-alpha confidence
y1	vector of scores for group 1
y2	vector of scores for group 2

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated proportion
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Sen PK (1967). "A note on asymptotically distribution-free confidence bounds for $P(X < Y)$, based on two independent samples." *The Indian Journal of Statistics, Series A*, **29**(1), 95–102.

Examples

```
y2 <- c(36, 44, 47, 42, 49, 39, 46, 31, 33, 48)
y1 <- c(32, 39, 26, 35, 43, 27, 40, 37, 34, 29)
ci.mann(.05, y1, y2)

# Should return:
# Estimate      SE      LL UL
# 0.795 0.1401834 0.5202456 1
```

`ci.mape1`*Confidence interval for a mean absolute prediction error*

Description

Computes a confidence interval for a population mean absolute prediction error (MAPE) in a general linear model. The MAPE is a more robust alternative to the residual standard deviation. This function requires a vector of estimated residuals from a general linear model. This confidence interval does not assume zero excess kurtosis but does assume symmetry of the population prediction errors.

Usage

```
ci.mape1(alpha, res, s)
```

Arguments

<code>alpha</code>	alpha level for 1-alpha confidence
<code>res</code>	vector of residuals
<code>s</code>	number of predictor variables in model

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated mean absolute prediction error
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
res <- c(-2.70, -2.69, -1.32, 1.02, 1.23, -1.46, 2.21, -2.10, 2.56,
        -3.02, -1.55, 1.46, 4.02, 2.34)
ci.mape1(.05, res, 1)

# Should return:
# Estimate      SE      LL      UL
# 2.3744 0.3314752 1.751678 3.218499
```

ci.mape2	<i>Confidence interval for a ratio of mean absolute prediction errors in a 2-group design</i>
----------	---

Description

Computes a confidence interval for a ratio of population mean absolute prediction errors (MAPEs) from a general linear model in two independent groups. The number of predictor variables can differ across groups and the two models can be non-nested. This function requires a vector of estimated residuals from each group. This function does not assume zero excess kurtosis but does assume symmetry in the population prediction errors for the two models.

Usage

```
ci.mape2(alpha, res1, res2, s1, s2)
```

Arguments

alpha	alpha level for 1-alpha confidence
res1	vector of residuals from group 1
res2	vector of residuals from group 2
s1	number of predictor variables used in group 1
s2	number of predictor variables used in group 2

Value

Returns a 1-row matrix. The columns are:

- MAPE1 - bias adjusted mean absolute prediction error for group 1
- MAPE2 - bias adjusted mean absolute prediction error for group 2
- MAPE1/MAPE2 - ratio of bias adjusted mean absolute prediction errors
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
res1 <- c(-2.70, -2.69, -1.32, 1.02, 1.23, -1.46, 2.21, -2.10, 2.56, -3.02
         -1.55, 1.46, 4.02, 2.34)
res2 <- c(-0.71, -0.89, 0.72, -0.35, 0.33 -0.92, 2.37, 0.51, 0.68, -0.85,
         -0.15, 0.77, -1.52, 0.89, -0.29, -0.23, -0.94, 0.93, -0.31 -0.04)
ci.mape2(.05, res1, res2, 1, 1)

# Should return:
#   MAPE1      MAPE2 MAPE1/MAPE2      LL      UL
# 2.58087 0.8327273   3.099298 1.917003 5.010761
```

ci.mean.ps

Confidence interval for a paired-samples mean difference

Description

Computes a confidence interval for a population paired-samples mean difference using the estimated means, estimated standard deviations, estimated correlation, and sample size. Use the `t.test` function for raw data input.

Usage

```
ci.mean.ps(alpha, m1, m2, sd1, sd2, cor, n)
```

Arguments

alpha	alpha level for 1-alpha confidence
m1	estimated mean for measurement 1
m2	estimated mean for measurement 2
sd1	estimated standard deviation for measurement 1
sd2	estimated standard deviation for measurement 2
cor	estimated correlation between measurements
n	sample size

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated mean difference
- SE - standard error
- t - t test statistic
- df - degrees of freedom
- p - p-value
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
ci.mean.ps(.05, 58.2, 51.4, 7.43, 8.92, .537, 30)

# Should return:
# Estimate      SE      t df      p      LL      UL
#      6.8 1.455922 4.670578 29 6.33208e-05 3.822304 9.777696
```

ci.mean1	<i>Confidence interval for a single mean</i>
----------	--

Description

Computes a confidence interval for a population mean using the estimated mean, estimated standard deviation, and sample size. Use the t.test function for raw data input.

Usage

```
ci.mean1(alpha, m, sd, n)
```

Arguments

alpha	alpha level for 1-alpha confidence
m	estimated mean
sd	estimated standard deviation
n	sample size

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated mean
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Snedecor GW, Cochran WG (1989). *Statistical Methods*, 8th edition. ISU University Pres, Ames, Iowa.

Examples

```
ci.mean1(.05, 24.5, 3.65, 40)

# Should return:
# Estimate      SE      LL      UL
#      24.5 0.5771157 23.33267 25.66733
```

ci.mean2

Confidence interval for a 2-group mean difference

Description

Computes equal variance and unequal variance confidence intervals for a population 2-group mean difference using the estimated means, estimated standard deviations, and sample sizes. Use the `t.test` function for raw data input.

Usage

```
ci.mean2(alpha, m1, m2, sd1, sd2, n1, n2)
```

Arguments

alpha	alpha level for 1-alpha confidence
m1	estimated mean for group 1
m2	estimated mean for group 2
sd1	estimated standard deviation for group 1
sd2	estimated standard deviation for group 2
n1	sample size for group 1
n2	sample size for group 2

Value

Returns a 2-row matrix. The columns are:

- Estimate - estimated mean difference
- SE - standard error
- t - t test statistic
- df - degrees of freedom
- p - p-value
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Snedecor GW, Cochran WG (1989). *Statistical Methods*, 8th edition. ISU University Pres, Ames, Iowa.

Examples

```
ci.mean2(.05, 15.4, 10.3, 2.67, 2.15, 30, 20)

# Should return:
#
#           Estimate      SE      t      df
# Equal Variances Assumed:      5.1 1.602248 3.183029 48.0000
# Equal Variances Not Assumed:  5.1 1.406801 3.625247 44.1137
#
#           p      LL      UL
# Equal Variances Assumed:  0.0025578586 1.878465 8.321535
# Equal Variances Not Assumed: 0.0007438065 2.264986 7.935014
```

ci.median.ps

Confidence interval for a paired-samples median difference

Description

Computes a confidence interval for a difference of population medians in a paired-samples design. This function also computes the standard errors for each median and the covariance between the two estimated medians.

Usage

```
ci.median.ps(alpha, y1, y2)
```

Arguments

alpha	alpha level for 1-alpha confidence
y1	vector of scores for measurement 1
y2	vector of scores for measurement 2 (paired with y1)

Value

Returns a 1-row matrix. The columns are:

- Median1 - estimated median for measurement 1
- Median2 - estimated median for measurement 2
- Median1-Median2 - estimated difference of medians
- SE1 - standard error of median 1
- SE2 - standard error of median 2

- COV - covariance of the two estimated medians
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Price RM (2020). "Interval estimation for linear functions of medians in within-subjects and mixed designs." *British Journal of Mathematical and Statistical Psychology*, **73**(2), 333–346. ISSN 0007-1102, doi:10.1111/bmsp.12171.

Examples

```
y1 <- c(21, 4, 9, 12, 35, 18, 10, 22, 24, 1, 6, 8, 13, 16, 19)
y2 <- c(67, 28, 30, 28, 52, 40, 25, 37, 44, 10, 14, 20, 28, 40, 51)
ci.median.ps(.05, y1, y2)

# Should return:
# Median1 Median2 Median1-Median2      SE      LL      UL
#      13      30          -17 3.362289 -23.58996 -10.41004
#      SE1      SE2      COV
# 3.085608 4.509735 9.276849
```

ci.median1

Confidence interval for a single median

Description

Computes a confidence interval for a single population median.

Usage

```
ci.median1(alpha, y)
```

Arguments

alpha	alpha level for 1-alpha confidence
y	vector of scores

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated median
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Snedecor GW, Cochran WG (1989). *Statistical Methods*, 8th edition. ISU University Pres, Ames, Iowa.

Examples

```
y <- c(30, 20, 15, 10, 10, 60, 20, 25, 20, 30, 10, 5, 50, 40,
      20, 10, 0, 20, 50)
ci.median1(.05, y)

# Should return:
# Estimate      SE LL UL
#      20 4.270922 10 30
```

ci.median2

Confidence interval for a 2-group median difference

Description

Computes a confidence interval for a difference of population medians in a 2-group design.

Usage

```
ci.median2(alpha, y1, y2)
```

Arguments

alpha	alpha level for 1-alpha confidence
y1	vector of scores for group 1
y2	vector of scores for group 2

Value

Returns a 1-row matrix. The columns are:

- Median1 - estimated median from group 1
- Median2 - estimated median from group 2
- Median1-Median2 - estimated difference in medians
- SE - standard error of the difference
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Price RM (2002). "Statistical inference for a linear function of medians: Confidence intervals, hypothesis testing, and sample size requirements." *Psychological Methods*, 7(3), 370–383. ISSN 1939-1463, doi:10.1037/1082989X.7.3.370.

Examples

```
y1 <- c(32, 39, 26, 35, 43, 27, 40, 37, 34, 29)
y2 <- c(36, 44, 47, 42, 49, 39, 46, 31, 33, 48)
ci.median2(.05, y1, y2)

# Should return:
# Median1 Median2 Median1-Median2      SE      LL      UL
#   34.5      43      -8.5 4.316291 -16.95977 -0.04022524
```

<code>ci.oddsratio</code>	<i>Confidence interval for an odds ratio</i>
---------------------------	--

Description

Computes a confidence interval for an odds ratio with .5 added to each cell frequency. This function requires the frequency counts from a 2 x 2 contingency table for two dichotomous variables.

Usage

```
ci.oddsratio(alpha, f00, f01, f10, f11)
```

Arguments

<code>alpha</code>	alpha level for 1-alpha confidence
<code>f00</code>	number of participants with y = 0 and x = 0
<code>f01</code>	number of participants with y = 0 and x = 1
<code>f10</code>	number of participants with y = 1 and x = 0
<code>f11</code>	number of participants with y = 1 and x = 1

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimate of odds ratio
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Fleiss JL, Paik MC (2003). *Statistical Methods for Rates and Proportions*, 3rd edition. Wiley.

Examples

```
ci.oddsratio(.05, 229, 28, 96, 24)

# Should return:
#   Estimate      SE      LL      UL
# [1,] 2.044451 0.6154578 1.133267 3.688254
```

ci.pairs.prop.bs	<i>Bonferroni confidence intervals for all pairwise proportion differences in a between-subjects design</i>
------------------	---

Description

Computes adjusted Wald confidence intervals for all pairwise differences of proportions in a between-subjects design with a Bonferroni adjusted alpha level.

Usage

```
ci.pairs.prop.bs(alpha, f, n)
```

Arguments

alpha	alpha level for simultaneous 1-alpha confidence
f	vector of frequency counts of participants who have the attribute
n	vector of sample sizes

Value

Returns a matrix with the number of rows equal to the number of pairwise comparisons. The columns are:

- Estimate - adjusted estimate of proportion difference
- SE - adjusted standard error
- z - z test statistic
- p - p-value
- LL - lower limit of the adjusted Wald confidence interval
- UL - upper limit of the adjusted Wald confidence interval

References

Agresti A, Caffo B (2000). "Simple and effective confidence intervals for proportions and differences of proportions result from adding two successes and two failures." *The American Statistician*, 54(4), 280. ISSN 00031305, doi:10.2307/2685779.

Examples

```
f <- c(111, 161, 132)
n <- c(200, 200, 200)
ci.pairs.prop.bs(.05, f, n)

# Should return:
#      Estimate      SE      z      p      LL      UL
# 1 2 -0.2475248 0.04482323 -5.522243 3.346989e-08 -0.35483065 -0.14021885
# 1 3 -0.1039604 0.04833562 -2.150803 3.149174e-02 -0.21967489 0.011175409
# 2 3 0.1435644 0.04358401 3.293968 9.878366e-04 0.03922511 0.24790360
```

<code>ci.pairs.prop1</code>	<i>Confidence intervals for pairwise proportion differences of a polychotomous variable</i>
-----------------------------	---

Description

Computes adjusted Wald confidence intervals for pairwise proportion differences of a polychotomous variable. These adjusted Wald confidence intervals use the same method that is used to compare the two proportions in a paired-samples design.

Usage

```
ci.pairs.prop1(alpha, f)
```

Arguments

<code>alpha</code>	alpha level for 1-alpha confidence
<code>f</code>	vector of multinomial frequency counts

Value

Returns a matrix with the number of rows equal to the number of pairwise comparisons. The columns are:

- Estimate - adjusted estimate of proportion difference
- SE - adjusted standard error
- LL - lower limit of the adjusted Wald confidence interval
- UL - upper limit of the adjusted Wald confidence interval

References

Bonett DG, Price RM (2012). “Adjusted wald confidence interval for a difference of binomial proportions based on paired data.” *Journal of Educational and Behavioral Statistics*, **37**(4), 479–488. ISSN 1076-9986, doi:10.3102/1076998611411915.

Examples

```
f <- c(125, 82, 92)
ci.pairs.prop1(.05, f)

# Should return:
#      Estimate      SE      LL      UL
# 1 2  0.14285714  0.04731825  0.05011508  0.23559920
# 1 3  0.10963455  0.04875715  0.01407230  0.20519680
# 2 3 -0.03322259  0.04403313 -0.11952594  0.05308076
```

ci.pbcor

Confidence interval for a point-biserial correlation

Description

Computes confidence intervals for two types of population point-biserial correlations. One type uses a weighted average of the group variances and is appropriate for nonexperimental designs with simple random sampling (but not stratified random sampling). The other type uses an unweighted average of the group variances and is appropriate for experimental designs. Equality of variances is not assumed for either type.

Usage

```
ci.pbcor(alpha, m1, m2, sd1, sd2, n1, n2)
```

Arguments

alpha	alpha level for 1-alpha confidence
m1	estimated mean for group 1
m2	estimated mean for group 2
sd1	estimated standard deviation for group 1
sd2	estimated standard deviation for group 2
n1	sample size for group 1
n2	sample size for group 2

Value

Returns a 2-row matrix. The columns are:

- Estimate - estimated point-biserial correlation
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG (2020). "Point-biserial correlation: Interval estimation, hypothesis testing, meta-analysis, and sample size determination." *British Journal of Mathematical and Statistical Psychology*, **73**(S1), 113–144. ISSN 0007-1102, doi:10.1111/bmsp.12189.

Examples

```
ci.pbcor(.05, 28.32, 21.48, 3.81, 3.09, 40, 40)

# Should return:
#           Estimate      SE      LL      UL
# Weighted:  0.7065799 0.04890959 0.5885458 0.7854471
# Unweighted: 0.7020871 0.05018596 0.5808366 0.7828948
```

ci.phi

Confidence interval for a phi correlation

Description

Computes a confidence interval for a phi correlation. This function requires the frequency counts from a 2 x 2 contingency table for two dichotomous variables. This measure of association is usually most appropriate when both dichotomous variables are naturally dichotomous.

Usage

```
ci.phi(alpha, f00, f01, f10, f11)
```

Arguments

alpha	alpha level for 1-alpha confidence
f00	number of participants with y = 0 and x = 0
f01	number of participants with y = 0 and x = 1
f10	number of participants with y = 1 and x = 0
f11	number of participants with y = 1 and x = 1

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimate of phi correlation
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bishop YMM, Fienberg SE, Holland PW (1975). *Discrete Multivariate Analysis*. MIT Press.

Examples

```
ci.phi(.05, 229, 28, 96, 24)

# Should return:
# Estimate      SE      LL      UL
# 0.1229976 0.05746271 0.01037273 0.2356224
```

 ci.popsiz

Confidence interval for an unknown population size

Description

Computes a Wald confidence interval for an unknown population size using mark-recapture sampling. This method assumes independence of the two samples. This function requires the frequency counts from an incomplete 2 x 2 contingency table for the two samples (f11 is the unknown number of people who were not observed in either sample). This method sets the estimated odds ratio (with .5 added to each cell) to 1 and solves for unobserved cell frequency. An approximate standard error is recovered from the confidence interval.

Usage

```
ci.popsiz(alpha, f00, f01, f10)
```

Arguments

alpha	alpha level for 1-alpha confidence
f00	number of people observed in both samples
f01	number of people observed in first sample but not second sample
f10	number of people observed in second sample but not first sample

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimate of the unknown population size
- SE - recovered standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
ci.popsiize(.05, 794, 710, 741)

# Should return:
# Estimate      SE    LL    UL
#      2908 49.49071 2818 3012
```

ci.prop.ps

Confidence interval for a paired-samples proportion difference

Description

Computes an adjusted Wald confidence interval for a difference of proportions in a paired-samples design. This function requires the frequency counts from a 2 x 2 contingency table for two repeated dichotomous measurements.

Usage

```
ci.prop.ps(alpha, f00, f01, f10, f11)
```

Arguments

alpha	alpha level for 1-alpha confidence
f00	number of participants with y = 0 and x = 0
f01	number of participants with y = 0 and x = 1
f10	number of participants with y = 1 and x = 0
f11	number of participants with y = 1 and x = 1

Value

Returns a 1-row matrix. The columns are:

- Estimate - adjusted estimate of proportion difference
- SE - adjusted standard error
- LL - lower limit of the adjusted Wald confidence interval
- UL - upper limit of the adjusted Wald confidence interval

References

Bonett DG, Price RM (2012). “Adjusted wald confidence interval for a difference of binomial proportions based on paired data.” *Journal of Educational and Behavioral Statistics*, **37**(4), 479–488. ISSN 1076-9986, doi:10.3102/1076998611411915.

Examples

```
ci.prop.ps(.05, 12, 4, 26, 6)

# Should return:
# Estimate      SE      LL      UL
#    0.44 0.09448809 0.2548067 0.6251933
```

```
ci.prop1          Confidence interval for a single proportion
```

Description

Computes adjusted Wald and Wilson confidence intervals for a single population proportion. The Wilson confidence interval uses a continuity correction.

Usage

```
ci.prop1(alpha, f, n)
```

Arguments

alpha	alpha level for 1-alpha confidence
f	number of participants who have the attribute
n	sample size

Value

Returns a 2-row matrix. The columns of row 1 are:

- Estimate - adjusted estimate of proportion
- SE - adjusted standard error
- LL - lower limit of the adjusted Wald confidence interval
- UL - upper limit of the adjusted Wald confidence interval

The columns of row 2 are:

- Estimate - ML estimate of proportion
- SE - standard error
- LL - lower limit of the Wilson confidence interval
- UL - upper limit of the Wilson confidence interval

References

Agresti A, Coull BA (1998). “Approximate is better than ‘exact’ for interval estimation of binomial proportions.” *The American Statistician*, **52**(2), 119–126. ISSN 0003-1305, doi:10.1080/00031305.1998.10480550.

Examples

```
ci.prop1(.05, 12, 100)

# Should return:
#           Estimate      SE      LL      UL
# Adjusted Wald 0.1346154 0.03346842 0.06901848 0.2002123
# Wilson with cc 0.1200000 0.03249615 0.06625153 0.2039772
```

ci.prop1.inv

Confidence interval for a single proportion using inverse sampling

Description

Computes an exact confidence interval for a single population proportion when inverse sampling has been used. An approximate standard error is recovered from the confidence interval. With inverse sampling, the number of participants who have the attribute (f) is predetermined and sampling continues until f attains its prespecified value. With inverse sampling, the sample size (n) will not be known in advance.

Usage

```
ci.prop1.inv(alpha, f, n)
```

Arguments

alpha	alpha level for 1-alpha confidence
f	number of participants who have the attribute
n	sample size

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimate of proportion
- SE - recovered standard error
- LL - lower limit of confidence interval
- UL - upper limit of confidence interval

References

Zou GY (2010). "Confidence interval estimation under inverse sampling." *Computational Statistics and Data Analysis*, **54**(1), 55–64. ISSN 0167-9473, doi:10.1016/j.csda.2005.05.007.

Examples

```
ci.prop1.inv(.05, 5, 67)

# Should return:
# Estimate      SE      LL      UL
# 0.07462687 0.03145284 0.02467471 0.1479676
```

ci.prop2

Confidence interval for a 2-group proportion difference

Description

Computes an adjusted Wald confidence interval for a proportion difference in a 2-group design.

Usage

```
ci.prop2(alpha, f1, f2, n1, n2)
```

Arguments

alpha	alpha level for 1-alpha confidence
f1	number of participants in group 1 who have the attribute
f2	number of participants in group 2 who have the attribute
n1	sample size for group 1
n2	sample size for group 2

Value

Returns a 1-row matrix. The columns are:

- Estimate - adjusted estimate of proportion difference
- SE - adjusted standard error
- LL - lower limit of the adjusted Wald confidence interval
- UL - upper limit of the adjusted Wald confidence interval

References

Agresti A, Caffo B (2000). "Simple and effective confidence intervals for proportions and differences of proportions result from adding two successes and two failures." *The American Statistician*, **54**(4), 280. ISSN 00031305, doi:10.2307/2685779.

Examples

```
ci.prop2(.05, 35, 21, 150, 150)

# Should return:
# Estimate      SE      LL      UL
# 0.09210526 0.04476077 0.004375769 0.1798348
```

ci.prop2.inv	<i>Confidence interval for a 2-group proportion difference using inverse sampling</i>
--------------	---

Description

Computes an approximate confidence interval for a population proportion difference when inverse sampling has been used. An approximate standard error is recovered from the confidence interval. With inverse sampling, the number of participants who have the attribute within group 1 (f1) and group 2 (f2) are predetermined, and sampling continues within each group until f1 and f2 attain their prespecified values. With inverse sampling, the sample sizes (n1 and n2) will not be known in advance.

Usage

```
ci.prop2.inv(alpha, f1, f2, n1, n2)
```

Arguments

alpha	alpha level for 1-alpha confidence
f1	number of participants in group 1 who have the attribute
f2	number of participants in group 2 who have the attribute
n1	sample size for group 1
n2	sample size for group 2

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimate of proportion difference
- SE - recovered standard error
- LL - lower limit of confidence interval
- UL - upper limit of confidence interval

References

Zou GY (2010). "Confidence interval estimation under inverse sampling." *Computational Statistics and Data Analysis*, **54**(1), 55–64. ISSN 0167-9473, doi:10.1016/j.csda.2005.05.007.

Examples

```
ci.prop2.inv(.05, 10, 10, 48, 213)

# Should return:
# Estimate      SE      LL      UL
# 0.161385 0.05997618 0.05288277 0.2879851
```

ci.pv	<i>Confidence intervals for positive and negative predictive values with retrospective sampling</i>
-------	---

Description

Computes adjusted Wald confidence intervals for positive and negative predictive values (PPV and NPV) of a diagnostic test with retrospective sampling where the population prevalence rate is assumed to be known. With retrospective sampling, one random sample is obtained from a sub-population that is known to have a "positive" outcome, a second random sample is obtained from a subpopulation that is known to have a "negative" outcome, and then the diagnostic test (scored "pass" or "fail") is given in each sample. PPV and NPV can be expressed as a function of proportion ratios and the known population prevalence rate (the population proportion who would "pass"). The confidence intervals for PPV and NPV are based on the Price-Bonett adjusted Wald confidence interval for a proportion ratio.

Usage

```
ci.pv(alpha, f1, f2, n1, n2, prev)
```

Arguments

alpha	alpha level for 1-alpha confidence
f1	number of participants with a positive outcome who pass the test
f2	number of participants with a negative outcome who fail the test
n1	sample size for the positive outcome group
n2	sample size for the negative outcome group
prev	known population proportion with a positive outcome

Value

Returns a 2-row matrix. The columns are:

- Estimate - adjusted estimate of the predictive value
- LL - lower limit of the adjusted Wald confidence interval
- UL - upper limit of the adjusted Wald confidence interval

References

Price RM, Bonett DG (2008). “Confidence intervals for a ratio of two independent binomial proportions.” *Statistics in Medicine*, **27**(26), 5497–5508. ISSN 02776715, doi:10.1002/sim.3376.

Examples

```
ci.pv(.05, 89, 5, 100, 100, .16)

# Should return:
#      Estimate      LL      UL
# PPV: 0.7640449 0.5838940 0.8819671
# NPV: 0.9779978 0.9623406 0.9872318
```

ci.random.anova1	<i>Confidence intervals for parameters of one-way random effects ANOVA</i>
------------------	--

Description

Computes estimates and confidence intervals for four parameters of the one-way random effects ANOVA: 1) the superpopulation grand mean, 2) the square-root within-group variance component, 3) the square-root between-group variance component, and 4) the omega-squared coefficient. This function assumes equal sample sizes.

Usage

```
ci.random.anova1(alpha, m, sd, n)
```

Arguments

alpha	1 - alpha confidence
m	vector of estimated group means
sd	vector of estimated group standard deviations
n	sample size per group

Value

Returns a 4-row matrix. The rows are:

- Grand mean - the mean of the superpopulation of means
- Within SD - the square-root within-group variance component
- Between SD - the square-root between-group variance component
- Omega-squared - the omega-squared coefficient

The columns are:

- Estimate - estimate of parameter
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
m <- c(56.1, 51.2, 60.3, 68.2, 48.9, 70.5)
sd <- c(9.45, 8.79, 9.71, 8.90, 8.31, 9.75)
ci.random.anova1(.05, m, sd, 20)

# Should return:
#           Estimate      LL      UL
# Grand mean 59.200000 49.9363896 68.4636104
# Within SD:  9.166782  8.0509046 10.4373219
# Between SD:  8.585948  8.3239359  8.8562078
# Omega-squared: 0.467317 0.2284142 0.8480383
```

ci.ratio.cv2	<i>Confidence interval for a ratio of coefficients of variation in a 2-group design</i>
--------------	---

Description

Computes a confidence interval for a ratio of population coefficients of variation (CV) in a 2-group design. This confidence interval uses the confidence interval for each CV and then uses the MOVER-DL method (see Newcombe, page 138) to obtain a confidence interval for CV1/CV2. The CV assumes ratio-scale scores.

Usage

```
ci.ratio.cv2(alpha, m1, m2, sd1, sd2, n1, n2)
```

Arguments

alpha	alpha level for 1-alpha confidence
m1	estimated mean for group 1
m2	estimated mean for group 2
sd1	estimated standard deviation for group 1
sd2	estimated standard deviation for group 2
n1	sample size for group 1
n2	sample size for group 2

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated ratio of coefficients of variation
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Newcombe RG (2013). *Confidence Interval for Proportions and Related Measures of Effect Size*. CRC Press.

Examples

```
ci.ratio.cv2(.05, 34.5, 26.1, 4.15, 2.26, 50, 50)

# Should return:
# Estimate      LL      UL
# 1.389188 1.041478 1.854101
```

ci.ratio.mad.ps *Confidence interval for a paired-sample MAD ratio*

Description

Computes a confidence interval for a ratio of population MADs (mean absolute deviation from median) in a paired-samples design.

Usage

```
ci.ratio.mad.ps(alpha, y1, y2)
```

Arguments

alpha	alpha level for 1-alpha confidence
y1	vector of measurement 1 scores
y2	vector of measurement 2 scores (paired with y1)

Value

Returns a 1-row matrix. The columns are:

- MAD1 - estimated MAD for measurement 1
- MAD2 - estimated MAD for measurement 2
- MAD1/MAD2 - estimate of MAD ratio
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Seier E (2003). "Statistical inference for a ratio of dispersions using paired samples." *Journal of Educational and Behavioral Statistics*, **28**(1), 21–30. ISSN 1076-9986, doi:[10.3102/10769986028001021](https://doi.org/10.3102/10769986028001021).

Examples

```
y2 <- c(21, 4, 9, 12, 35, 18, 10, 22, 24, 1, 6, 8, 13, 16, 19)
y1 <- c(67, 28, 30, 28, 52, 40, 25, 37, 44, 10, 14, 20, 28, 40, 51)
ci.ratio.mad.ps(.05, y1, y2)

# Should return:
#   MAD1 MAD2 MAD1/MAD2      LL      UL
# 12.71429  7.5  1.695238 1.109176 2.590961
```

ci.ratio.mad2

Confidence interval for a 2-group ratio of mean absolute deviations

Description

Computes a confidence interval for a ratio of population MADs (mean absolute deviation from median) in a 2-group design.

Usage

```
ci.ratio.mad2(alpha, y1, y2)
```

Arguments

alpha	alpha level for 1-alpha confidence
y1	vector of scores for group 1
y2	vector of scores for group 2

Value

Returns a 1-row matrix. The columns are:

- MAD1 - estimated MAD from group 1
- MAD2 - estimated MAD from group 2
- MAD1/MAD2 - estimate of MAD ratio
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Seier E (2003). “Confidence intervals for mean absolute deviations.” *The American Statistician*, **57**(4), 233–236. ISSN 0003-1305, doi:10.1198/0003130032323.

Examples

```
y1 <- c(32, 39, 26, 35, 43, 27, 40, 37, 34, 29)
y2 <- c(36, 44, 47, 42, 49, 39, 46, 31, 33, 48)
ci.ratio.mad2(.05, y1, y2)

# Should return:
#   MAD1     MAD2  MAD1/MAD2      LL      UL
# 5.111111 5.888889 0.8679245 0.4520879 1.666253
```

ci.ratio.mean.ps

Confidence interval for a paired-samples mean ratio

Description

Compute a confidence interval for a ratio of population means of ratio-scale measurements in a paired-samples design. Equality of variances is not assumed.

Usage

```
ci.ratio.mean.ps(alpha, y1, y2)
```

Arguments

alpha	alpha level for 1-alpha confidence
y1	vector of measurement 1 scores
y2	vector of measurement 2 scores (paired with y1)

Value

Returns a 1-row matrix. The columns are:

- Mean1 - estimated measurement 1 mean
- Mean2 - estimated measurement 2 mean
- Mean1/Mean2 - estimate of mean ratio
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Price RM (2020). “Confidence intervals for ratios of means and medians.” *Journal of Educational and Behavioral Statistics*, **45**(6), 750–770. ISSN 1076-9986, doi:[10.3102/1076998620934125](https://doi.org/10.3102/1076998620934125).

Examples

```
y1 <- c(3.3, 3.6, 3.0, 3.1, 3.9, 4.2, 3.5, 3.3)
y2 <- c(3.0, 3.1, 2.7, 2.6, 3.2, 3.8, 3.2, 3.0)
ci.ratio.mean.ps(.05, y1, y2)

# Should return:
# Mean1 Mean2 Mean1/Mean2      LL      UL
# 3.4875 3.075   1.134146 1.09417 1.175583
```

<code>ci.ratio.mean2</code>	<i>Confidence interval for a 2-group mean ratio</i>
-----------------------------	---

Description

Computes a confidence interval for a ratio of population means of ratio-scale measurements in a 2-group design. Equality of variances is not assumed.

Usage

```
ci.ratio.mean2(alpha, y1, y2)
```

Arguments

<code>alpha</code>	alpha level for 1-alpha confidence
<code>y1</code>	vector of scores for group 1
<code>y2</code>	vector of scores for group 2

Value

Returns a 1-row matrix. The columns are:

- Mean1 - estimated mean from group 1
- Mean2 - estimated mean from group 2
- Mean1/Mean2- estimated mean ratio
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Price RM (2020). “Confidence intervals for ratios of means and medians.” *Journal of Educational and Behavioral Statistics*, **45**(6), 750–770. ISSN 1076-9986, doi:10.3102/1076998620934125.

Examples

```
y2 <- c(32, 39, 26, 35, 43, 27, 40, 37, 34, 29, 49, 42, 40)
y1 <- c(36, 44, 47, 42, 49, 39, 46, 31, 33, 48)
ci.ratio.mean2(.05, y1, y2)

# Should return:
#
# Mean1    Mean2 Mean1/Mean2      LL      UL
# 41.5 36.38462  1.140592 0.9897482 1.314425
```

ci.ratio.median.ps *Confidence interval for a paired-samples median ratio*

Description

Computes a confidence interval for a ratio of population medians in a paired-samples design.

Usage

```
ci.ratio.median.ps(alpha, y1, y2)
```

Arguments

alpha	alpha level for 1-alpha confidence
y1	vector of scores for measurement 1
y2	vector of scores for measurement 2 (paired with y1)

Value

Returns a 1-row matrix. The columns are:

- Median1 - estimated median from measurement 1
- Median2 - estimated median from measurement 2
- Median1/Median2 - estimated ratio of medians
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Price RM (2020). “Confidence intervals for ratios of means and medians.” *Journal of Educational and Behavioral Statistics*, **45**(6), 750–770. ISSN 1076-9986, doi:[10.3102/1076998620934125](https://doi.org/10.3102/1076998620934125).

Examples

```
y1 <- c(21, 4, 9, 12, 35, 18, 10, 22, 24, 1, 6, 8, 13, 16, 19)
y2 <- c(67, 28, 30, 28, 52, 40, 25, 37, 44, 10, 14, 20, 28, 40, 51)
ci.ratio.median.ps(.05, y1, y2)

# Should return:
# Median1 Median2 Median1/Median2 LL UL
# 13 30 0.4333333 0.3094838 0.6067451
```

ci.ratio.median2 *Confidence interval for a 2-group median ratio*

Description

Computes a confidence interval for a ratio of population medians of ratio-scale measurements in a 2-group design.

Usage

```
ci.ratio.median2(alpha, y1, y2)
```

Arguments

alpha	alpha level for 1-alpha confidence
y1	vector of scores for group 1
y2	vector of scores for group 2

Value

Returns a 1-row matrix. The columns are:

- Median1 - estimated median from group 1
- Median2 - estimated median from group 2
- Median1/Median2 - estimated ratio of medians
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Price RM (2020). “Confidence intervals for ratios of means and medians.” *Journal of Educational and Behavioral Statistics*, **45**(6), 750–770. ISSN 1076-9986, doi:10.3102/1076998620934125.

Examples

```
y2 <- c(32, 39, 26, 35, 43, 27, 40, 37, 34, 29, 49, 42, 40)
y1 <- c(36, 44, 47, 42, 49, 39, 46, 31, 33, 48)
ci.ratio.median2(.05, y1, y2)

# Should return:
# Median1 Median2 Median1/Median2      LL      UL
#      43      37      1.162162 0.927667 1.455933
```

ci.ratio.prop.ps *Confidence interval for a paired-samples proportion ratio*

Description

Computes a confidence interval for a ratio of proportions in a paired-samples design. This function requires the frequency counts from a 2 x 2 contingency table for two repeated dichotomous measurements.

Usage

```
ci.ratio.prop.ps(alpha, f00, f01, f10, f11)
```

Arguments

alpha	alpha level for 1-alpha confidence
f00	number of participants with y = 0 and x = 0
f01	number of participants with y = 0 and x = 1
f10	number of participants with y = 1 and x = 0
f11	number of participants with y = 1 and x = 1

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimate of proportion ratio
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Price RM (2006). “Confidence intervals for a ratio of binomial proportions based on paired data.” *Statistics in Medicine*, **25**(17), 3039–3047. ISSN 0277-6715, doi:10.1002/sim.2440.

Examples

```
ci.ratio.prop.ps(.05, 12, 4, 26, 6)

# Should return:
# Estimate      LL      UL
#      3.2 1.766544 5.796628
```

<code>ci.ratio.prop2</code>	<i>Confidence interval for a 2-group proportion ratio</i>
-----------------------------	---

Description

Computes an adjusted Wald confidence interval for a proportion ratio in a 2-group design.

Usage

```
ci.ratio.prop2(alpha, f1, f2, n1, n2)
```

Arguments

alpha	alpha level for 1-alpha confidence
f1	number of participants in group 1 who have the attribute
f2	number of participants in group 2 who have the attribute
n1	sample size for group 1
n2	sample size for group 2

Value

Returns a 1-row matrix. The columns are:

- Estimate - adjusted estimate of proportion ratio
- LL - lower limit of the adjusted Wald confidence interval
- UL - upper limit of the adjusted Wald confidence interval

References

Price RM, Bonett DG (2008). “Confidence intervals for a ratio of two independent binomial proportions.” *Statistics in Medicine*, **27**(26), 5497–5508. ISSN 02776715, doi:10.1002/sim.3376.

Examples

```
ci.ratio.prop2(.05, 35, 21, 150, 150)

# Should return:
# Estimate      LL      UL
# 1.666667 1.017253 2.705025
```

ci.ratio.sd2

Confidence interval for a 2-group ratio of standard deviations

Description

Computes a robust confidence interval for a ratio of population standard deviations in a 2-group design. This function is a modification of the confidence interval proposed by Bonett (2006). The original Bonett method used a pooled kurtosis estimate in the standard error that assumed equal variances, which limited the confidence interval's use to tests of equal population variances and equivalence tests. This function uses a pooled kurtosis estimate that does not assume equal variances and provides a useful confidence interval for a ratio of standard deviations under general conditions. This function requires of minimum sample size of four per group but sample sizes of at least 10 per group are recommended.

Usage

```
ci.ratio.sd2(alpha, y1, y2)
```

Arguments

alpha	alpha level for 1-alpha confidence
y1	vector of scores for group 1
y2	vector of scores for group 2

Value

Returns a 1-row matrix. The columns are:

- SD1 - estimated SD from group 1
- SD2 - estimated SD from group 2
- SD1/SD2 - estimate of SD ratio
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG (2006). "Robust confidence interval for a ratio of standard deviations." *Applied Psychological Measurement*, **30**(5), 432–439. ISSN 0146-6216, doi:10.1177/0146621605279551.

Examples

```

y1 <- c(32, 39, 26, 35, 43, 27, 40, 37, 34, 29)
y2 <- c(36, 44, 47, 42, 49, 39, 46, 31, 33, 48)
ci.ratio.sd2(.05, y1, y2)

# Should return:
#   SD1   SD2  SD1/SD2   LL   UL
# 5.711587 6.450667 0.8854257 0.486279 1.728396

```

ci.rel2

Confidence interval for a 2-group reliability difference

Description

Computes a 100(1 - alpha)% confidence interval for a difference in population reliabilities in a 2-group design. This function can be used with any type of reliability coefficient (e.g., Cronbach alpha, McDonald omega, intraclass reliabilities). The function requires point estimates and 100(1 - alpha)% confidence intervals for each reliability as input.

Usage

```
ci.rel2(rel1, ll1, ul1, rel2, ll2, ul2)
```

Arguments

rel1	estimated reliability for group 1
ll1	lower limit for group 1 reliability
ul1	upper limit for group 1 reliability
rel2	estimated reliability for group 2
ll2	lower limit for group 2 reliability
ul2	upper limit for group 2 reliability

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated reliability difference
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Wright TA (2015). "Cronbach's alpha reliability: Interval estimation, hypothesis testing, and sample size planning." *Journal of Organizational Behavior*, **36**(1), 3–15. ISSN 08943796, [doi:10.1002/job.1960](https://doi.org/10.1002/job.1960).

Examples

```
ci.rel2(.4, .35, .47, .2, .1, .32)

# Should return:
# Estimate  LL      UL
#      0.2 0.07 0.3220656
```

ci.reliability

Confidence interval for a reliability coefficient

Description

Computes a confidence interval for a population reliability coefficient such as Cronbach's alpha or McDonald's omega using an estimate of the reliability and its standard error. The standard error can be a robust standard error or bootstrap standard error obtained from an SEM program.

Usage

```
ci.reliability(alpha, rel, se, n)
```

Arguments

alpha	alpha level for 1-alpha confidence
rel	estimated reliability
se	standard error of reliability
n	sample size

Value

Returns a 1-row matrix. The columns are:

- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
ci.reliability(.05, .88, .0147, 100)

# Should return:
# Estimate      LL      UL
#      0.88 0.8489612 0.9065575
```

ci.rsqr	<i>Confidence interval for squared multiple correlation</i>
---------	---

Description

Computes an approximate confidence interval for a population squared multiple correlation in a linear model with random predictor variables. This function uses the scaled central F approximation method. An approximate standard error is recovered from the confidence interval.

Usage

```
ci.rsqr(alpha, r2, s, n)
```

Arguments

alpha	alpha value for 1-alpha confidence
r2	estimated unadjusted squared multiple correlation
s	number of predictor variables
n	sample size

Value

Returns a 1-row matrix. The columns are:

- R-squared - estimate of unadjusted R-squared
- adj R-squared - bias adjusted R-squared estimate
- SE - recovered standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Helland IS (1987). "On the interpretation and use of R2 in regression analysis." *Biometrics*, **43**(1), 61-69. doi:10.2307/2531949.

Examples

```
ci.rsqr(.05, .241, 3, 116)

# Should return:
# R-squared adj R-squared      SE      LL      UL
#    0.241    0.2206696 0.06752263 0.09819599 0.3628798
```

 ci.sign1

Confidence interval for the parameter of the one-sample sign test

Description

Computes adjusted Wald interval for the population proportion of quantitative scores that are greater than the null hypothesis value of the population median in a one-sample sign test.

Usage

```
ci.sign1(alpha, y, h)
```

Arguments

alpha	alpha level for 1-alpha confidence
y	vector of y scores
h	null hypothesis value for population median

Value

Returns a 1-row matrix. The columns are:

- Estimate - adjusted estimate of proportion
- SE - adjusted standard error
- LL - lower limit of adjusted Wald confidence interval
- UL - upper limit of adjusted Wald confidence interval

References

Agresti, A, & Coull, BA (1998) Approximate is better than “exact” for interval estimation of binomial proportions. *American Statistician*, 52, 119–126. doi: 10.1080/00031305.1998.10480550

Examples

```
y <- c(30, 20, 15, 10, 10, 60, 20, 25, 20, 30, 10, 5, 50, 40, 20, 10,
      0, 20, 50)
ci.sign1(.05, y, 9)

# Should return:
# Estimate      SE      LL      UL
# 0.826087 0.0790342 0.6711828 0.9809911
```

ci.slope.mean.bs	<i>Confidence interval for the slope of means in a single-factor design with a quantitative between-subjects factor</i>
------------------	---

Description

Computes a test statistic and confidence interval for the slope of means in a single-factor design with a quantitative between-subjects factor. This function computes both the unequal variance and equal variance confidence intervals and test statistics. A Satterthwaite adjustment to the degrees of freedom is used with the unequal variance method.

Usage

```
ci.slope.mean.bs(alpha, m, sd, n, x)
```

Arguments

alpha	alpha level for 1-alpha confidence
m	vector of sample means
sd	vector of sample standard deviations
n	vector of sample sizes
x	vector of numeric predictor variable values

Value

Returns a 2-row matrix. The columns are:

- Estimate - estimated slope
- SE - standard error
- t - t test statistic
- df - degrees of freedom
- p - p-value
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

Examples

```
m <- c(33.5, 37.9, 38.0, 44.1)
sd <- c(3.84, 3.84, 3.65, 4.98)
n <- c(10,10,10,10)
x <- c(5, 10, 20, 30)
ci.slope.mean.bs(.05, m, sd, n, x)
```

```
# Should return:
```

```
#           Estimate      SE      t      df
```

```
# Equal Variances Assumed:    0.3664407 0.06770529 5.412290 36.00000
# Equal Variances Not Assumed: 0.3664407 0.07336289 4.994905 18.65826
#                               p          LL          UL
# Equal Variances Assumed:    4.242080e-06 0.2291280 0.5037534
# Equal Variances Not Assumed: 8.468223e-05 0.2126998 0.5201815
```

ci.slope.prop.bs	<i>Confidence interval for a slope of a proportion in a single-factor design with a quantitative between-subjects factor</i>
------------------	--

Description

Computes a test statistic and an adjusted Wald confidence interval for the slope of proportions in a single-factor design with a quantitative between-subjects factor.

Usage

```
ci.slope.prop.bs(alpha, f, n, x)
```

Arguments

alpha	alpha level for 1-alpha confidence
f	vector of frequency counts of participants who have the attribute
n	vector of sample sizes
x	vector of quantitative factor values

Value

Returns a 1-row matrix. The columns are:

- Estimate - adjusted slope estimate
- SE - adjusted standard error
- z - z test statistic
- p - p-value
- LL - lower limit of the adjusted Wald confidence interval
- UL - upper limit of the adjusted Wald confidence interval

References

Price RM, Bonett DG (2004). "An improved confidence interval for a linear function of binomial proportions." *Computational Statistics & Data Analysis*, **45**(3), 449–456. ISSN 01679473, [doi:10.1016/S01679473\(03\)000070](https://doi.org/10.1016/S01679473(03)000070).

Examples

```
f <- c(14, 27, 38)
n <- c(100, 100, 100)
x <- c(10, 20, 40)
ci.slope.prop.bs(.05, f, n, x)

# Should return:
#   Estimate      SE      z      p      LL      UL
# 0.007542293 0.002016793 3.739746 0.000184206 0.003589452 0.01149513
```

ci.spcor	<i>Confidence interval for a semipartial correlation</i>
----------	--

Description

Computes a Fisher confidence interval for a population semipartial correlation. This function requires an (unadjusted) estimate of the squared multiple correlation in the full model that contains the predictor variable of interest plus all control variables. This function computes a modified Aloe-Becker confidence interval that uses $n - 3$ rather than n in the standard error and also uses a Fisher transformation of the semipartial correlation.

Usage

```
ci.spcor(alpha, cor, r2, n)
```

Arguments

alpha	alpha level for 1-alpha confidence
cor	estimated semipartial correlation
r2	estimated squared multiple correlation in full model
n	sample size

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated semipartial correlation
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Aloe AM, Becker BJ (2012). "An effect size for regression predictors in meta-analysis." *Journal of Educational and Behavioral Statistics*, **37**(2), 278–297. ISSN 1076-9986, doi:[10.3102/1076998610396901](https://doi.org/10.3102/1076998610396901).

Examples

```
ci.spcor(.05, .582, .699, 20)

# Should return:
# Estimate      SE      LL      UL
#    0.582 0.1374298 0.2525662 0.7905182
```

ci.spear	<i>Confidence interval for a Spearman correlation</i>
----------	---

Description

Computes a Fisher confidence interval for a population Spearman correlation.

Usage

```
ci.spear(alpha, y, x)
```

Arguments

alpha	alpha level for 1-alpha confidence
y	vector of y scores
x	vector of x scores (paired with y)

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated correlation
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Wright TA (2000). "Sample size requirements for estimating Pearson, Kendall and Spearman correlations." *Psychometrika*, **65**(1), 23–28. ISSN 0033-3123, doi:[10.1007/BF02294183](https://doi.org/10.1007/BF02294183).

Examples

```

y <- c(21, 4, 9, 12, 35, 18, 10, 22, 24, 1, 6, 8, 13, 16, 19)
x <- c(67, 28, 30, 28, 52, 40, 25, 37, 44, 10, 14, 20, 28, 40, 51)
ci.spear(.05, y, x)

# Should return:
# Estimate      SE      LL      UL
# 0.8699639 0.08241326 0.5840951 0.9638297

```

ci.spear2

Confidence interval for a 2-group Spearman correlation difference

Description

Computes a confidence interval for a difference in population Spearman correlations in a 2-group design.

Usage

```
ci.spear2(alpha, cor1, cor2, n1, n2)
```

Arguments

alpha	alpha level for 1-alpha confidence
cor1	estimated Spearman correlation for group 1
cor2	estimated Spearman correlation for group 2
n1	sample size for group 1
n2	sample size for group 2

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated correlation difference
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Wright TA (2000). "Sample size requirements for estimating Pearson, Kendall and Spearman correlations." *Psychometrika*, **65**(1), 23–28. ISSN 0033-3123, doi:[10.1007/BF02294183](https://doi.org/10.1007/BF02294183).

Zou GY (2007). "Toward using confidence intervals to compare correlations." *Psychological Methods*, **12**(4), 399–413. ISSN 1939-1463, doi:[10.1037/1082989X.12.4.399](https://doi.org/10.1037/1082989X.12.4.399).

Examples

```
ci.spear2(.05, .54, .48, 180, 200)

# Should return:
# Estimate      SE      LL      UL
#      0.06 0.08124926 -0.1003977 0.2185085
```

ci.stdmean.ps	<i>Confidence interval for a paired-samples standardized mean difference</i>
---------------	--

Description

Computes confidence intervals for a population standardized mean difference in a paired-samples design. A square root unweighted variance standardizer and single measurement standard deviation standardizers are used. Equality of variances is not assumed.

Usage

```
ci.stdmean.ps(alpha, m1, m2, sd1, sd2, cor, n)
```

Arguments

alpha	alpha level for 1-alpha confidence
m1	estimated mean of measurement 1
m2	estimated mean of measurement 2
sd1	estimated standard deviation of measurement 1
sd2	estimated standard deviation of measurement 2
cor	estimated correlation between measurements
n	sample size

Value

Returns a 3-row matrix. The columns are:

- Estimate - estimated standardized mean difference
- adj Estimate - bias adjusted standardized mean difference estimate
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG (2008). "Confidence intervals for standardized linear contrasts of means." *Psychological Methods*, **13**(2), 99–109. ISSN 1939-1463, doi:10.1037/1082989X.13.2.99.

Examples

```
ci.stdmean.ps(.05, 110.4, 102.1, 15.3, 14.6, .75, 25)

# Should return:
#
#           Estimate  adj Estimate      SE      LL      UL
# Unweighted standardizer:  0.5550319    0.5433457  0.1609934  0.2394905  0.8705732
# Measurement 1 standardizer: 0.5424837    0.5253526  0.1615500  0.2258515  0.8591158
# Measurement 2 standardizer: 0.5684932    0.5505407  0.1692955  0.2366800  0.9003063
```

ci.stdmean.strat	<i>Confidence interval for a 2-group standardized mean difference with stratified sampling</i>
------------------	--

Description

Computes confidence intervals for a population standardized mean difference in a 2-group non-experimental design with stratified random sampling (a random sample of a specified size from each subpopulation) using a square root weighted variance standardizer or single group standard deviation standardizer. Equality of variances is not assumed.

Usage

```
ci.stdmean.strat(alpha, m1, m2, sd1, sd2, n1, n2, p1)
```

Arguments

alpha	alpha level for 1-alpha confidence
m1	estimated mean for group 1
m2	estimated mean for group 2
sd1	estimated standard deviation for group 1
sd2	estimated standard deviation for group 2
n1	sample size for group 1
n2	sample size for group 2
p1	proportion of total population in subpopulation 1

Value

Returns a 3-row matrix. The columns are:

- Estimate - estimated standardized mean difference
- adj Estimate - bias adjusted standardized mean difference estimate
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG (2020). "Point-biserial correlation: Interval estimation, hypothesis testing, meta-analysis, and sample size determination." *British Journal of Mathematical and Statistical Psychology*, **73**(S1), 113–144. ISSN 0007-1102, doi:10.1111/bmsp.12189.

Examples

```
ci.stdmean.strat(.05, 33.2, 30.8, 10.5, 11.2, 200, 200, .533)

# Should return:
#               Estimate  adj Estimate      SE      LL      UL
# Weighted standardizer: 0.2215549    0.2211371 0.10052057 0.02453817 0.4185716
# Group 1 standardizer: 0.2285714    0.2277089 0.10427785 0.02419059 0.4329523
# Group 2 standardizer: 0.2142857    0.2277089 0.09776049 0.02267868 0.4058927
```

ci.stdmean1

Confidence interval for a single standardized mean

Description

Computes a confidence interval for a population standardized mean difference from a hypothesized value. If the hypothesized value is set to 0, the reciprocals of the confidence interval endpoints gives a confidence interval for the coefficient of variation.

Usage

```
ci.stdmean1(alpha, m, sd, n, h)
```

Arguments

alpha	alpha level for 1-alpha confidence
m	estimated mean
sd	estimated standard deviation
n	sample size
h	hypothesized value

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimated standardized mean difference
- adj Estimate - bias adjusted standardized mean difference estimate
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG (2008). "Confidence intervals for standardized linear contrasts of means." *Psychological Methods*, **13**(2), 99–109. ISSN 1939-1463, doi:10.1037/1082989X.13.2.99.

Examples

```
ci.stdmean1(.05, 24.5, 3.65, 40, 20)

# Should return:
# Estimate  adj Estimate      SE      LL      UL
# 1.232877    1.209015  0.2124335  0.8165146  1.649239
```

ci.stdmean2

Confidence interval for a 2-group standardized mean difference

Description

Computes confidence intervals for a population standardized mean difference. Unweighted, weighted, and single group variance standardizers are used. The square root weighted variance standardizer is recommended in 2-group nonexperimental designs with simple random sampling. The square root unweighted variance standardizer is recommended in 2-group experimental designs. The single group standard deviation standardizer can be used with experimental or nonexperimental designs. Equality of variances is not assumed.

Usage

```
ci.stdmean2(alpha, m1, m2, sd1, sd2, n1, n2)
```

Arguments

alpha	alpha level for 1-alpha confidence
m1	estimated mean for group 1
m2	estimated mean for group 2
sd1	estimated standard deviation for group 1

sd2 estimated standard deviation for group 2
 n1 sample size for group 1
 n2 sample size for group 2

Value

Returns a 4-row matrix. The columns are:

- Estimate - estimated standardized mean difference
- adj Estimate - bias adjusted standardized mean difference estimate
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG (2008). “Confidence intervals for standardized linear contrasts of means.” *Psychological Methods*, **13**(2), 99–109. ISSN 1939-1463, [doi:10.1037/1082989X.13.2.99](https://doi.org/10.1037/1082989X.13.2.99).

Examples

```
ci.stdmean2(.05, 35.1, 26.7, 7.32, 6.98, 30, 30)

# Should return:
#
# Unweighted standardizer: 1.174493    1.159240 0.2844012 0.6170771 1.731909
# Weighted standardizer:    1.174493    1.159240 0.2802826 0.6251494 1.723837
# Group 1 standardizer:    1.147541    1.117605 0.2975582 0.5643375 1.730744
# Group 2 standardizer:    1.203438    1.172044 0.3120525 0.5918268 1.815050
```

ci.tetra

Confidence interval for a tetrachoric correlation

Description

Computes a confidence interval for an approximation to the tetrachoric correlation. This function requires the frequency counts from a 2 x 2 contingency table for two dichotomous variables. This measure of association assumes both of the dichotomous variables are artificially dichotomous. An approximate standard error is recovered from the confidence interval.

Usage

```
ci.tetra(alpha, f00, f01, f10, f11)
```

Arguments

alpha	alpha level for 1-alpha confidence
f00	number of participants with y = 0 and x = 0
f01	number of participants with y = 0 and x = 1
f10	number of participants with y = 1 and x = 0
f11	number of participants with y = 1 and x = 1

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimate of tetrachoric approximation
- SE - recovered standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Price RM (2005). "Inferential methods for the tetrachoric correlation coefficient." *Journal of Educational and Behavioral Statistics*, **30**(2), 213–225. ISSN 1076-9986, doi:[10.3102/10769986030002213](https://doi.org/10.3102/10769986030002213).

Examples

```
ci.tetra(.05, 46, 15, 54, 85)

# Should return:
# Estimate      SE      LL      UL
# 0.5135167 0.09301703 0.3102345 0.6748546
```

ci.theil

Theil-Sen estimate and confidence interval for slope

Description

Computes a Theil-Sen estimate and distribution-free confidence interval for the slope of a simple linear regression model. An approximate standard error is recovered from the confidence interval.

Usage

```
ci.theil(alpha, y, x)
```

Arguments

alpha	alpha level for 1-alpha confidence
y	vector of response variable scores
x	vector of predictor variable scores (paired with y)

Value

Returns a 1-row matrix. The columns are:

- Estimate - Theil-Sen estimate of population slope
- SE - recovered standard error
- LL - lower limit of confidence interval
- UL - upper limit of confidence interval

References

Hollander M, Wolf DA (1999). *Nonparametric Statistical Methods*. Wiley.

Examples

```
y <- c(21, 4, 9, 12, 35, 18, 10, 22, 24, 1, 6, 8, 13, 16, 19)
x <- c(67, 28, 30, 28, 52, 40, 25, 37, 44, 10, 14, 20, 28, 40, 51)
ci.theil(.05, y, x)

# Should return:
# Estimate      SE      LL      UL
#      0.5 0.1085927 0.3243243 0.75
```

ci.tukey

*Tukey-Kramer confidence intervals for all pairwise mean differences
in a between-subjects design*

Description

Computes heteroscedastic Tukey-Kramer (also known as Games-Howell) confidence intervals for all pairwise comparisons of population means using estimated means, estimated standard deviations, and samples sizes as input. A Satterthwaite adjustment to the degrees of freedom is used to improve the accuracy of the confidence intervals.

Usage

```
ci.tukey(alpha, m, sd, n)
```

Arguments

alpha	alpha level for simultaneous 1-alpha confidence
m	vector of estimated group means
sd	vector of estimated group standard deviations
n	vector of sample sizes

Value

Returns a matrix with the number of rows equal to the number of pairwise comparisons. The columns are:

- Estimate - estimated mean difference
- SE - standard error
- t - t test statistic
- df - degrees of freedom
- p - p-value
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Games PA, Howell JF (1976). "Pairwise multiple comparison procedures with unequal N's and/or variances: A Monte Carlo study." *Journal of Educational Statistics*, 1(2), 113. ISSN 03629791, doi:10.2307/1164979.

Examples

```
m <- c(12.86, 17.57, 26.29, 30.21)
sd <- c(13.185, 12.995, 14.773, 15.145)
n <- c(20, 20, 20, 20)
ci.tukey(.05, m, sd, n)

# Should return:
#   Estimate      SE      t      df      p      LL      UL
# 1 2    -4.71  4.139530 -1.1378102  37.99200 0.668806358 -15.83085  6.4108517
# 1 3   -13.43  4.427673 -3.0331960  37.51894 0.021765570 -25.33172 -1.5282764
# 1 4   -17.35  4.490074 -3.8640790  37.29278 0.002333937 -29.42281 -5.2771918
# 2 3    -8.72  4.399497 -1.9820446  37.39179 0.212906199 -20.54783  3.1078269
# 2 4   -12.64  4.462292 -2.8326248  37.14275 0.035716267 -24.64034 -0.6396589
# 3 4    -3.92  4.730817 -0.8286096  37.97652 0.840551420 -16.62958  8.7895768
```

ci.var.upper	<i>Upper confidence limit of variance</i>
--------------	---

Description

Computes an upper limit for a population variance using an estimated variance from a sample of size n in a prior study. The upper limit can be used as a variance planning value in sample size functions that require a variance planning value.

Usage

```
ci.var.upper(alpha, var, n)
```

Arguments

alpha	alpha value for 1-alpha confidence (one-sided)
var	estimated variance
n	sample size

Value

Returns an upper limit (UL) variance planning value

Examples

```
ci.var.upper(.25, 15, 60)

# Should return:
#      UL
# 17.23264
```

ci.yule	<i>Confidence intervals for generalized Yule coefficients</i>
---------	---

Description

Computes confidence intervals for four generalized Yule measures of association (Yule Q, Yule Y, Digby H, and Bonett-Price Y*) using a transformation of a confidence interval for an odds ratio with .5 added to each cell frequency. This function requires the frequency counts from a 2 x 2 contingency table for two dichotomous variables. Digby H is sometimes used as a crude approximation to the tetrachoric correlation. Yule Y is equal to the phi coefficient only when all marginal frequencies are equal. Bonett-Price Y* is a better approximation to the phi coefficient when the marginal frequencies are not equal.

Usage

```
ci.yule(alpha, f00, f01, f10, f11)
```

Arguments

alpha	alpha level for 1-alpha confidence
f00	number of participants with y = 0 and x = 0
f01	number of participants with y = 0 and x = 1
f10	number of participants with y = 1 and x = 0
f11	number of participants with y = 1 and x = 1

Value

Returns a 1-row matrix. The columns are:

- Estimate - estimate of generalized Yule coefficient
- SE - standard error
- LL - lower limit of the confidence interval
- UL - upper limit of the confidence interval

References

Bonett DG, Price RM (2007). "Statistical inference for generalized Yule coefficients in 2x2 contingency tables." *Sociological Methods & Research*, **35**(3), 429–446. ISSN 0049-1241, doi:[10.1177/0049124106292358](https://doi.org/10.1177/0049124106292358).

Examples

```
ci.yule(.05, 229, 28, 96, 24)

# Should return:
#   Estimate      SE      LL      UL
# Q: 0.3430670 0.13280379 0.06247099 0.5734020
# Y: 0.1769015 0.07290438 0.03126603 0.3151817
# H: 0.2619244 0.10514465 0.04687994 0.4537659
# Y*: 0.1311480 0.05457236 0.02307188 0.2361941
```

etasqr.adj	<i>Bias adjusts an eta-squared estimate</i>
------------	---

Description

Computes an approximate bias adjustment for eta-squared. This adjustment can be applied to eta-squared, partial-eta squared, and generalized eta-squared estimates.

Usage

```
etasqr.adj(etasqr, dfeffect, dferror)
```

Arguments

etasqr	unadjusted eta-square estimate
dfeffect	degrees of freedom for the effect
dferror	error degrees of freedom

Value

Returns a bias adjusted eta-squared estimate

Examples

```
etasqr.adj(.315, 2, 42)

# Should return:
# adj Eta-squared
#      0.282381
```

etasqr.gen.2way	<i>Generalized eta-squared estimates in a two-factor design</i>
-----------------	---

Description

Computes generalized eta-square estimates in a two-factor design where one or both factors are classification factors. If both factors are treatment factors, then partial eta-square estimates are typically recommended. Use the estimates from this function in the etasqr.adj function to obtain bias adjusted estimates.

Usage

```
etasqr.gen.2way(SSa, SSb, SSab, SSe)
```

Arguments

SSa	sum of squares for factor A
SSb	sum of squares for factor B
SSab	sum of squares for A x B interaction
SSE	error (within) sum of squares

Value

Returns a 3-row matrix. The columns are:

- A - estimate of eta-squared for factor A
- B - estimate of eta-squared for factor B
- AB - estimate of eta-squared for A x B interaction

Examples

```
etasqr.gen.2way(12.3, 15.6, 5.2, 7.9)

# Should return:
#
# A treatment, B classification:  0.300000 0.5435540 0.1811847
# A classification, B treatment:  0.484252 0.3804878 0.2047244
# A classification, B classification: 0.300000 0.3804878 0.1268293
```

iqv *Indices of qualitative variation*

Description

Computes the Shannon, Berger, and Simpson indices of qualitative variation.

Usage

```
iqv(f)
```

Arguments

f vector of multinomial frequency counts

Value

Returns estimates of the Shannon, Berger, and Simpson qualitative indices

Examples

```
f <- c(10, 46, 15, 3)
iqv(f)

# Should return:
# Simpson Berger Shannon
# 0.7367908 0.5045045 0.7
```

pi.score.ps	<i>Prediction interval for difference of scores in a 2-level within-subjects experiment</i>
-------------	---

Description

For a 2-level within-subjects experiment, this function computes a prediction interval for how the response variable score for one randomly selected person from the study population would differ under the two treatment conditions.

Usage

```
pi.score.ps(alpha, m1, m2, sd1, sd2, cor, n)
```

Arguments

alpha	alpha level for 1-alpha confidence
m1	estimated mean from group 1
m2	estimated mean from group 2
sd1	estimated standard deviation from group 1
sd2	estimated standard deviation from group 2
cor	estimated correlation of paired scores
n	sample size

Value

Returns a 1-row matrix. The columns are:

- Predicted - predicted difference in scores
- df - degrees of freedom
- LL - lower limit of the prediction interval
- UL - upper limit of the prediction interval

Examples

```
pi.score.ps(.05, 265.1, 208.6, 23.51, 19.94, .814, 30)

# Should return:
# Predicted df      LL      UL
#      56.5 29 28.05936 84.94064
```

pi.score1	<i>Prediction interval for one score</i>
-----------	--

Description

Computes a prediction interval for the response variable score of one randomly selected member from the study population.

Usage

```
pi.score1(alpha, m, sd, n)
```

Arguments

alpha	alpha level for 1-alpha confidence
m	estimated mean
sd	estimated standard deviation
n	sample size

Value

Returns a 1-row matrix. The columns are:

- Predicted - predicted score
- df - degrees of freedom
- LL - lower limit of the prediction interval
- UL - upper limit of the prediction interval

Examples

```
pi.score1(.05, 24.5, 3.65, 40)

# Should return:
# Predicted df      LL      UL
#      24.5 39 17.02546 31.97454
```

`pi.score2`*Prediction interval for a difference of scores in a 2-group experiment*

Description

For a 2-group experimental design, this function computes a prediction interval for how the response variable score for one randomly selected person from the study population would differ under the two treatment conditions. Both equal variance and unequal variance prediction intervals are computed.

Usage

```
pi.score2(alpha, m1, m2, sd1, sd2, n1, n2)
```

Arguments

<code>alpha</code>	alpha level for 1-alpha confidence
<code>m1</code>	estimated mean for group 1
<code>m2</code>	estimated mean for group 2
<code>sd1</code>	estimated standard deviation for group 1
<code>sd2</code>	estimated standard deviation for group 2
<code>n1</code>	sample size for group 1
<code>n2</code>	sample size for group 2

Value

Returns a 2-row matrix. The columns are:

- Predicted - predicted difference in scores
- df - degrees of freedom
- LL - lower limit of the prediction interval
- UL - upper limit of the prediction interval

References

Hahn GJ (1977). "A prediction interval on the difference between two future sample means and its application to a claim of product superiority." *Technometrics*, **19**(2), 131–134. ISSN 0040-1706, [doi:10.1080/00401706.1977.10489520](https://doi.org/10.1080/00401706.1977.10489520).

Examples

```
pi.score2(.05, 29.57, 18.35, 2.68, 1.92, 40, 45)

# Should return:
#               Predicted    df    LL    UL
# Equal Variances Assumed:    11.22 83.00000 4.650454 17.78955
# Equal Variances Not Assumed: 11.22 72.34319 4.603642 17.83636
```

```
pi.var.upper           Upper prediction limit for an estimated variance
```

Description

Computes an approximate upper prediction limit for the estimated variance in a future study for a planned sample size. The prediction limit uses a variance estimate from a prior study. The upper variance prediction limit is useful as a variance planning value for the sample size required to obtain a confidence interval with desired width. This strategy for specifying a variance planning value is useful in applications where the population variance in the prior study is assumed to be similar to the population variance in the planned study. This variance planning value can be used to revise the planned sample size in the future study.

Usage

```
pi.var.upper(alpha, var, n1, n2)
```

Arguments

alpha	alpha value for upper 1-alpha confidence
var	estimated variance from prior study
n1	sample size used to estimate variance
n2	planned sample size of future study

Value

Returns an upper prediction estimate (UL) of an estimated variance in a future study

Examples

```
pi.var.upper(.2, 15, 40, 100)

# Should return:
#           UL
# 18.78522
```

power.cor1 *Approximates the power of a correlation test for a planned sample size*

Description

Computes the approximate power of a Pearson or partial correlation test for a planned sample size. Set $s = 0$ for a Pearson correlation.

Usage

```
power.cor1(alpha, n, cor, h, s)
```

Arguments

alpha	alpha level for hypothesis test
n	planned sample size
cor	planning value of correlation
h	hypothesized value of correlation
s	number of control variables

Value

Returns the approximate power of the test

Examples

```
power.cor1(.05, 80, .3, 0, 0)

# Should return:
#   Power
# 0.7751932
```

power.cor2 *Approximates the power of a test for equal correlations in a 2-group design for planned sample sizes*

Description

Computes the approximate power of a test for equal population Pearson or partial correlations in a 2-group design for planned sample sizes. Set $s = 0$ for a Pearson correlation.

Usage

```
power.cor2(alpha, n1, n2, cor1, cor2, s)
```

Arguments

alpha	alpha level for hypothesis test
n1	planned sample size for group 1
n2	planned sample size for group 2
cor1	planning value of correlation for group 1
cor2	planning value of correlation for group 1
s	number of control variables

Value

Returns the approximate power of the test

Examples

```
power.cor2(.05, 200, 200, .4, .2, 0)

# Should return:
#   Power
# 0.5919517
```

power.lc.mean.bs	<i>Approximates the power of a test for a linear contrast of means for planned sample sizes in a between-subjects design</i>
------------------	--

Description

Computes the approximate power of a test for a linear contrast of population means for planned sample sizes in a between-subject design. The groups can be the factor levels of a single factor design or the combinations of factors in a factorial design. For a conservatively low power approximation, set the variance planning values to the largest values within their plausible ranges, and set the effect size to a minimally interesting value. The within-group variances can be unequal across groups and a Satterthwaite degree of freedom adjustment is used to improve the accuracy of the power approximation.

Usage

```
power.lc.mean.bs(alpha, n, var, es, v)
```

Arguments

alpha	alpha level for hypothesis test
n	vector of planned sample sizes
var	vector of within-group variance planning values
es	planning value of linear contrast of means
v	vector of contrast coefficients

Value

Returns the approximate power of the test

Examples

```
n <- c(20, 20, 20, 20)
var <- c(70, 70, 80, 80)
v <- c(.5, .5, -.5, -.5)
power.lc.mean.bs(.05, n, var, 5, v)

# Should return:
#   Power
# 0.7221139
```

power.mean.ps

Approximates the power of a paired-samples t-test for a planned sample size

Description

Computes the approximate power of a paired-samples t-test for a planned sample size. For a conservatively low power approximation, set the variance planning values to the largest values within their plausible ranges, set the correlation planning value to the smallest value within its plausible range, and set the effect size to a minimally interesting value. The variances of the two measurements can be unequal.

Usage

```
power.mean.ps(alpha, n, var1, var2, es, cor)
```

Arguments

alpha	alpha level for hypothesis test
n	planned sample size
var1	planning value of measurement 1 variance
var2	planning value of measurement 2 variance
es	planning value of mean difference
cor	planning value of correlation between measurements

Value

Returns the approximate power of the test

Examples

```
power.mean.ps(.05, 20, 10.0, 12.0, 2, .7)

# Should return:
#   Power
# 0.9074353
```

power.mean1	<i>Approximates the power of a one-sample t-test for a planned sample size</i>
-------------	--

Description

Computes the approximate power of a one-sample t-test for a planned sample size. For a conservatively low power approximation, set the variance planning value to the largest value within its plausible range, and set the effect size to a minimally interesting value.

Usage

```
power.mean1(alpha, n, var, es)
```

Arguments

alpha	alpha level for hypothesis test
n	planned sample size
var	planning value of response variable variance
es	planning value of mean minus hypothesized value

Value

Returns the approximate power of the test

Examples

```
power.mean1(.05, 15, 80.5, 7)

# Should return:
#   Power
# 0.8021661
```

power.mean2	<i>Approximates the power of a two-sample t-test for planned sample sizes</i>
-------------	---

Description

Computes the approximate power of a two-sample t-test for planned sample sizes. For a conservatively low power approximation, set the variance planning values to the largest values within their plausible ranges, and set the effect size to a minimally interesting value. The within-group variances can be unequal across groups and a Satterthwaite degree of freedom adjustment is used to improve the accuracy of the power approximation.

Usage

```
power.mean2(alpha, n1, n2, var1, var2, es)
```

Arguments

alpha	alpha level for hypothesis test
n1	planned sample size for group 1
n2	planned sample size for group 2
var1	planning value of within-group variance for group 1
var2	planning value of within-group variance for group 2
es	planning value of mean difference

Value

Returns the approximate power of the test

Examples

```
power.mean2(.05, 25, 25, 5.0, 6.0, 2)

# Should return:
#   Power
# 0.8398413
```

power.prop.ps	<i>Approximates the power of a paired-samples test of equal proportions for a planned sample size</i>
---------------	---

Description

Computes the approximate power of a test for equal population proportions in a paired-samples design (the McNemar test). This function requires planning values for both proportions and a phi coefficient that describes the correlation between the two dichotomous measurements. The proportion planning values can set to .5 for a conservatively low power estimate. The planning value for the proportion difference (effect size) could be set to the difference of the two proportion planning values or it could be set to a minimally interesting effect size. Set the phi correlation planning value to the smallest value within a plausible range for a conservatively low power estimate.

Usage

```
power.prop.ps(alpha, n, p1, p2, phi, es)
```

Arguments

alpha	alpha level for hypothesis test
n	planned sample size
p1	planning value of proportion for measurement 1
p2	planning value of proportion for measurement 2
phi	planning value of phi correlation
es	planning value of proportion difference

Value

Returns the approximate power of the test

Examples

```
power.prop.ps(.05, 45, .5, .5, .4, .2)

# Should return:
#   Power
# 0.6877652
```

power.prop1	<i>Approximates the power of a one-sample proportion test for a planned sample size</i>
-------------	---

Description

Computes the approximate power of a one-sample proportion test for a planned sample size. Set the proportion planning value to .5 for a conservatively low power estimate. The value of the effect size need not be based on the proportion planning value.

Usage

```
power.prop1(alpha, n, p, es)
```

Arguments

alpha	alpha level for hypothesis test
n	planned sample size
p	planning value of proportion
es	planning value of proportion minus hypothesized value

Value

Returns the approximate power of the test

Examples

```
power.prop1(.05, 40, .5, .2)

# Should return:
#   Power
# 0.715613
```

power.prop2	<i>Approximates the power of a two-sample proportion test for planned sample sizes</i>
-------------	--

Description

Computes the approximate power for a test of equal population proportions in a 2-group design for the planned sample sizes. This function requires planning values for both proportions. Set the proportion planning values to .5 for a conservatively low power estimate. The planning value for the proportion difference could be set to the difference of the two proportion planning values or it could be set to a minimally interesting effect size.

Usage

```
power.prop2(alpha, n1, n2, p1, p2, es)
```

Arguments

alpha	alpha level for hypothesis test
n1	planned sample size for group 1
n2	planned sample size for group 2
p1	planning value of proportion for group 1
p2	planning value of proportion for group 2
es	planning value of proportion difference

Value

Returns the approximate power of the test

Examples

```
power.prop2(.05, 60, 40, .5, .5, .2)

# Should return:
#   Power
# 0.4998515
```

random.sample	<i>Generate a random sample</i>
---------------	---------------------------------

Description

Generates a random sample of participant IDs without replacement.

Usage

```
random.sample(popsize, samsize)
```

Arguments

popsize	study population size
samsize	sample size

Value

Returns a vector of randomly generated participant IDs

Examples

```
random.sample(3000, 25)

# Should return:
# [1] 37 94 134 186 212 408 485 697 722 781 998 1055
# [13] 1182 1224 1273 1335 1452 1552 1783 1817 2149 2188 2437 2850 2936
```

random.y

Generate random sample of scores

Description

Generates a random sample of scores from a normal distribution with a specified population mean and standard deviation. This function is useful for generating hypothetical data for classroom demonstrations.

Usage

```
random.y(n, m, sd, min, max, dec)
```

Arguments

n	sample size
m	population mean of scores
sd	population standard deviation of scores
min	minimum allowable value
max	maximum allowable value
dec	number of decimal points

Value

Returns a vector of randomly generated scores.

Examples

```
random.y(10, 3.6, 2.8, 1, 7, 0)

# Should return:
# [1] 2 7 7 1 6 3 1 3 2 1
```

random.yx	<i>Generates random bivariate scores</i>
-----------	--

Description

Generates a random sample of y scores and x scores from a bivariate normal distributions with specified population means, standard deviations, and correlation. This function is useful for generating hypothetical data for classroom demonstrations.

Usage

```
random.yx(n, my, mx, sdy, sdx, cor, dec)
```

Arguments

n	sample size
my	population mean of y scores
mx	population mean of x scores
sdy	population standard deviation of y scores
sdx	population standard deviation of x scores
cor	population correlation between x and y
dec	number of decimal points

Value

Returns n pairs of y and x scores

Examples

```
random.yx(10, 50, 20, 4, 2, .5, 1)

# Should return:
#      y      x
# 1  50.3  21.6
# 2  52.0  21.6
# 3  53.0  22.7
# 4  46.9  21.3
# 5  56.3  23.8
# 6  50.4  20.3
# 7  44.6  19.9
# 8  49.9  18.3
# 9  49.4  18.5
# 10 42.3  20.2
```

randomize *Randomize a sample into groups*

Description

Randomly assigns a sample of participants into k groups.

Usage

```
randomize(n)
```

Arguments

n vector of sample sizes per group

Value

Returns a vector of randomly generated group assignments.

Examples

```
n <- c(10, 10, 5)
randomize(n)

# Should return:
# [1] 2 3 2 1 1 2 3 3 2 1 2 1 3 1 1 2 3 1 1 2 2 1 1 2 2
```

sim.ci.cor *Simulates confidence interval coverage probability for a Pearson correlation*

Description

Performs a computer simulation of confidence interval performance for a Pearson correlation. A bias adjustment is used to reduce the bias of the Fisher transformed Pearson correlation. Sample data can be generated from bivariate population distributions with five different marginal distributions. All distributions are scaled to have standard deviations of 1.0. Bivariate random data with specified marginal skewness and kurtosis are generated using the unonr function in the mnonr package.

Usage

```
sim.ci.cor(alpha, n, cor, dist1, dist2, rep)
```

Arguments

alpha	alpha level for 1-alpha confidence
n	sample size
cor	population Pearson correlation
dist1	type of distribution for variable 1 (1, 2, 3, 4, or 5)
dist2	type of distribution for variable 2 (1, 2, 3, 4, or 5) <ul style="list-style-type: none"> • 1 = Gaussian (skewness = 0 and excess kurtosis = 0) • 2 = platykurtic (skewness = 0 and excess kurtosis = -1.2) • 3 = leptokurtic (skewness = 0 and excess kurtosis = 6) • 4 = moderate skew (skewness = 1 and excess kurtosis = 1.5) • 5 = large skew (skewness = 2 and excess kurtosis = 6)
rep	number of Monte Carlo samples

Value

Returns a 1-row matrix. The columns are:

- Coverage - probability of confidence interval including population correlation
- Lower Error - probability of lower limit greater than population correlation
- Upper Error - probability of upper limit less than population correlation
- Ave CI Width - average confidence interval width

Examples

```
sim.ci.cor(.05, 30, .7, 4, 5, 1000)

# Should return (within sampling error):
# Coverage Lower Error Upper Error Ave CI Width
# [1,] 0.93815 0.05125 0.0106 0.7778518
```

sim.ci.mean.ps	<i>Simulates confidence interval coverage probability for a paired-samples mean difference</i>
----------------	--

Description

Performs a computer simulation of confidence interval performance for a mean difference in a paired-samples design. Sample data within each level of the within-subjects factor can be generated from bivariate population distributions with five different marginal distributions. All distributions are scaled to have standard deviations of 1.0 at level 1. Bivariate random data with specified marginal skewness and kurtosis are generated using the nonr function in the mnonr package.

Usage

```
sim.ci.mean.ps(alpha, n, sd.ratio, cor, dist1, dist2, rep)
```

Arguments

alpha	alpha level for 1-alpha confidence
n	sample size
sd.ratio	ratio of population standard deviations
cor	population correlation of paired observations
dist1	type of distribution at level 1 (1, 2, 3, 4, or 5)
dist2	type of distribution at level 2 (1, 2, 3, 4, or 5) <ul style="list-style-type: none"> • 1 = Gaussian (skewness = 0 and excess kurtosis = 0) • 2 = platykurtic (skewness = 0 and excess kurtosis = -1.2) • 3 = leptokurtic (skewness = 0 and excess kurtosis = 6) • 4 = moderate skew (skewness = 1 and excess kurtosis = 1.5) • 5 = large skew (skewness = 2 and excess kurtosis = 6)
rep	number of Monte Carlo samples

Value

Returns a 1-row matrix. The columns are:

- Coverage - probability of confidence interval including population mean difference
- Lower Error - probability of lower limit greater than population mean difference
- Upper Error - probability of upper limit less than population mean difference
- Ave CI Width - average confidence interval width

Examples

```
sim.ci.mean.ps(.05, 30, 1.5, .7, 4, 5, 1000)

# Should return (within sampling error):
# Coverage Lower Error Upper Error Ave CI Width
# 0.93815    0.05125    0.0106    0.7778518
```

`sim.ci.mean1`*Simulates confidence interval coverage probability for single mean*

Description

Performs a computer simulation of the confidence interval performance for a single mean. Sample data can be generated from five different population distributions. All distributions are scaled to have standard deviations of 1.0.

Usage

```
sim.ci.mean1(alpha, n, dist, rep)
```

Arguments

alpha	alpha level for 1-alpha confidence
n	sample size
dist	type of distribution (1, 2, 3, 4, or 5) <ul style="list-style-type: none">• 1 = Gaussian (skewness = 0 and excess kurtosis = 0)• 2 = platykurtic (skewness = 0 and excess kurtosis = -1.2)• 3 = leptokurtic (skewness = 0 and excess kurtosis = 6)• 4 = moderate skew (skewness = 1 and excess kurtosis = 1.5)• 5 = large skew (skewness = 2 and excess kurtosis = 6)
rep	number of Monte Carlo samples

Value

Returns a 1-row matrix. The columns are:

- Coverage - probability of confidence interval including population mean
- Lower Error - probability of lower limit greater than population mean
- Upper Error - probability of upper limit less than population mean
- Ave CI Width - average confidence interval width

Examples

```
sim.ci.mean1(.05, 40, 4, 1000)

# Should return (within sampling error):
# Coverage Lower Error Upper Error Ave CI Width
# 0.94722    0.01738    0.0354    0.6333067
```

sim.ci.mean2	<i>Simulates confidence interval coverage probability for a 2-group mean difference</i>
--------------	---

Description

Performs a computer simulation of separate variance and pooled variance confidence interval performance for a mean difference in a 2-group design. Sample data within each group can be generated from five different population distributions. All distributions are scaled to have a standard deviation of 1.0 in group 1.

Usage

```
sim.ci.mean2(alpha, n1, n2, sd.ratio, dist1, dist2, rep)
```

Arguments

alpha	alpha level for 1-alpha confidence
n1	sample size in group 1
n2	sample size in group 2
sd.ratio	ratio of population standard deviations (sd2/sd1)
dist1	type of distribution for group 1 (1, 2, 3, 4, or 5)
dist2	type of distribution for group 2 (1, 2, 3, 4, or 5) <ul style="list-style-type: none"> • 1 = Gaussian (skewness = 0 and excess kurtosis = 0) • 2 = platykurtic (skewness = 0 and excess kurtosis = -1.2) • 3 = leptokurtic (skewness = 0 and excess kurtosis = 6) • 4 = moderate skew (skewness = 1 and excess kurtosis = 1.5) • 5 = large skew (skewness = 2 and excess kurtosis = 6)
rep	number of Monte Carlo samples

Value

Returns a 1-row matrix. The columns are:

- Coverage - probability of confidence interval including population mean difference
- Lower Error - probability of lower limit greater than population mean difference
- Upper Error - probability of upper limit less than population mean difference
- Ave CI Width - average confidence interval width

Examples

```
sim.ci.mean2(.05, 30, 25, 1.5, 4, 5, 1000)

# Should return (within sampling error):
#
# Coverage Lower Error Upper Error Ave CI Width
# Equal Variances Assumed: 0.93986 0.04022 0.01992 1.344437
# Equal Variances Not Assumed: 0.94762 0.03862 0.01376 1.401305
```

sim.ci.median.ps	<i>Simulates confidence interval coverage probability for a median difference in a paired-samples design</i>
------------------	--

Description

Performs a computer simulation of confidence interval performance for a median difference in a paired-samples design. Sample data within each level of the within-subjects factor can be generated from bivariate population distributions with five different marginal distributions. All distributions are scaled to have standard deviations of 1.0 at level 1. Bivariate random data with specified marginal skewness and kurtosis are generated using the `unonr` function in the `mnonr` package.

Usage

```
sim.ci.median.ps(alpha, n, sd.ratio, cor, dist1, dist2, rep)
```

Arguments

alpha	alpha level for 1-alpha confidence
n	sample size
sd.ratio	ratio of population standard deviations
cor	population correlation of paired observations
dist1	type of distribution at level 1 (1, 2, 3, 4, or 5)
dist2	type of distribution at level 2 (1, 2, 3, 4, or 5)
	<ul style="list-style-type: none"> • 1 = Gaussian (skewness = 0 and excess kurtosis = 0) • 2 = platykurtic (skewness = 0 and excess kurtosis = -1.2) • 3 = leptokurtic (skewness = 0 and excess kurtosis = 6) • 4 = moderate skew (skewness = 1 and excess kurtosis = 1.5) • 5 = large skew (skewness = 2 and excess kurtosis = 6)
rep	number of Monte Carlo samples

Value

Returns a 1-row matrix. The columns are:

- Coverage - probability of confidence interval including population median difference
- Lower Error - probability of lower limit greater than population median difference
- Upper Error - probability of upper limit less than population median difference
- Ave CI Width - average confidence interval width

Examples

```
# Only 1000 reps because CRAN runs all examples and requires short execution time.
sim.ci.median.ps(.05, 30, 1.5, .7, 4, 3, 1000)

# Should return (within sampling error):
# Coverage Lower Error Upper Error Ave CI Width
# 0.961      0.026      0.013      0.9435462
```

sim.ci.median1

Simulates confidence interval coverage probability for single median

Description

Performs a computer simulation of the confidence interval performance for a single median. Sample data can be generated from five different population distributions. All distributions are scaled to have standard deviations of 1.0.

Usage

```
sim.ci.median1(alpha, n, dist, rep)
```

Arguments

alpha	alpha level for 1-alpha confidence
n	sample size
dist	type of distribution (1, 2, 3, 4, or 5) <ul style="list-style-type: none"> • 1 = Gaussian (skewness = 0 and excess kurtosis = 0) • 2 = platykurtic (skewness = 0 and excess kurtosis = -1.2) • 3 = leptokurtic (skewness = 0 and excess kurtosis = 6) • 4 = moderate skew (skewness = 1 and excess kurtosis = 1.5) • 5 = large skew (skewness = 2 and excess kurtosis = 6)
rep	number of Monte Carlo samples

Value

Returns a 1-row matrix. The columns are:

- Coverage - probability of confidence interval including population median
- Lower Error - probability of lower limit greater than population median
- Upper Error - probability of upper limit less than population median
- Ave CI Width - average confidence interval width

Examples

```
sim.ci.median1(.05, 20, 5, 1000)

# Should return (within sampling error):
# Coverage Lower Error Upper Error Ave CI Width
# 0.9589      0.0216      0.0195      0.9735528
```

sim.ci.median2	<i>Simulates confidence interval coverage probability for a median difference in a 2-group design</i>
----------------	---

Description

Performs a computer simulation of the confidence interval performance for a difference of medians in a 2-group design. Sample data for each group can be generated from five different population distributions. All distributions are scaled to have standard deviations of 1.0 in group 1.

Usage

```
sim.ci.median2(alpha, n1, n2, sd.ratio, dist1, dist2, rep)
```

Arguments

alpha	alpha level for 1-alpha confidence
n1	sample size for group 1
n2	sample size for group 2
sd.ratio	ratio of population standard deviations (sd2/sd1)
dist1	type of distribution for group 1 (1, 2, 3, 4, or 5)
dist2	type of distribution for group 2 (1, 2, 3, 4, or 5) <ul style="list-style-type: none"> • 1 = Gaussian (skewness = 0 and excess kurtosis = 0) • 2 = platykurtic (skewness = 0 and excess kurtosis = -1.2) • 3 = leptokurtic (skewness = 0 and excess kurtosis = 6) • 4 = moderate skew (skewness = 1 and excess kurtosis = 1.5) • 5 = large skew (skewness = 2 and excess kurtosis = 6)
rep	number of Monte Carlo samples

Value

Returns a 1-row matrix. The columns are:

- Coverage - Probability of confidence interval including population median difference
- Lower Error - Probability of lower limit greater than population median difference
- Upper Error - Probability of upper limit less than population median difference
- Ave CI Width - Average confidence interval width

Examples

```
sim.ci.median2(.05, 20, 20, 2, 5, 4, 5000)

# Should return (within sampling error):
# Coverage Lower Error Upper Error Ave CI Width
# 0.952      0.027      0.021      2.368914
```

sim.ci.spear	<i>Simulates confidence interval coverage probability for a Spearman correlation</i>
--------------	--

Description

Performs a computer simulation of confidence interval performance for a Spearman correlation. Sample data can be generated from bivariate population distributions with five different marginal distributions. All distributions are scaled to have standard deviations of 1.0. Bivariate random data with specified marginal skewness and kurtosis are generated using the `unonr` function in the `mnonr` package.

Usage

```
sim.ci.spear(alpha, n, cor, dist1, dist2, rep)
```

Arguments

alpha	alpha level for 1-alpha confidence
n	sample size
cor	population Spearman correlation
dist1	type of distribution for variable 1 (1, 2, 3, 4, or 5)
dist2	type of distribution for variable 2 (1, 2, 3, 4, or 5) <ul style="list-style-type: none"> • 1 = Gaussian (skewness = 0 and excess kurtosis = 0) • 2 = platykurtic (skewness = 0 and excess kurtosis = -1.2) • 3 = leptokurtic (skewness = 0 and excess kurtosis = 6) • 4 = moderate skew (skewness = 1 and excess kurtosis = 1.5) • 5 = large skew (skewness = 2 and excess kurtosis = 6)
rep	number of Monte Carlo samples

Value

Returns a 1-row matrix. The columns are:

- Coverage - probability of confidence interval including population correlation
- Lower Error - probability of lower limit greater than population correlation
- Upper Error - probability of upper limit less than population correlation
- Ave CI Width - average confidence interval width

Examples

```
sim.ci.spear(.05, 30, .7, 4, 5, 1000)

# Should return (within sampling error):
#      Coverage Lower Error Upper Error Ave CI Width
# [1,] 0.96235    0.01255    0.0251    0.4257299
```

sim.ci.stdmean.ps	<i>Simulates confidence interval coverage probability for a standardized mean difference in a paired-samples design</i>
-------------------	---

Description

Performs a computer simulation of confidence interval performance for two types of standardized mean differences in a paired-samples design. Sample data for each level of the within-subjects factor can be generated from five different population distributions. All distributions are scaled to have standard deviations of 1.0 at level 1.

Usage

```
sim.ci.stdmean.ps(alpha, n, sd.ratio, cor, dist1, dist2, d, rep)
```

Arguments

alpha	alpha level for 1-alpha confidence
n	sample size
sd.ratio	ratio of population standard deviations (sd2/sd1)
cor	correlation between paired measurements
dist1	type of distribution at level 1 (1, 2, 3, 4, or 5)
dist2	type of distribution at level 2 (1, 2, 3, 4, or 5) <ul style="list-style-type: none"> • 1 = Gaussian (skewness = 0 and excess kurtosis = 0) • 2 = platykurtic (skewness = 0 and excess kurtosis = -1.2) • 3 = leptokurtic (skewness = 0 and excess kurtosis = 6)

- 4 = moderate skew (skewness = 1 and excess kurtosis = 1.5)
 - 5 = large skew (skewness = 2 and excess kurtosis = 6)
- d population standardized mean difference
- rep number of Monte Carlo samples

Value

Returns a 1-row matrix. The columns are:

- Coverage - Probability of confidence interval including population std mean difference
- Lower Error - Probability of lower limit greater than population std mean difference
- Upper Error - Probability of upper limit less than population std mean difference
- Ave CI Width - Average confidence interval width

Examples

```
sim.ci.stdmean.ps(.05, 20, 1.5, .8, 4, 4, .5, 2000)

# Should return (within sampling error):
#           Coverage Lower Error Upper Error Ave CI Width Ave Est
# Unweighted Standardizer  0.9095      0.0555      0.035  0.7354865 0.5186796
# Level 1 Standardizer     0.9525      0.0255      0.022  0.9330036 0.5058198
```

sim.ci.stdmean2 *Simulates confidence interval coverage probability for a standardized mean difference in a 2-group design*

Description

Performs a computer simulation of confidence interval performance for two types of standardized mean differences in a 2-group design. Sample data for each group can be generated from five different population distributions. All distributions are scaled to have standard deviations of 1.0 in group 1.

Usage

```
sim.ci.stdmean2(alpha, n1, n2, sd.ratio, dist1, dist2, d, rep)
```

Arguments

alpha alpha level for 1-alpha confidence

n1 sample size for group 1

n2 sample size for group 2

sd.ratio ratio of population standard deviations (sd2/sd1)

dist1	type of distribution for group 1 (1, 2, 3, 4, or 5)
dist2	type of distribution for group 2 (1, 2, 3, 4, or 5) <ul style="list-style-type: none"> • 1 = Gaussian (skewness = 0 and excess kurtosis = 0) • 2 = platykurtic (skewness = 0 and excess kurtosis = -1.2) • 3 = leptokurtic (skewness = 0 and excess kurtosis = 6) • 4 = moderate skew (skewness = 1 and excess kurtosis = 1.5) • 5 = large skew (skewness = 2 and excess kurtosis = 6)
d	population standardized mean difference
rep	number of Monte Carlo samples

Value

Returns a 1-row matrix. The columns are:

- Coverage - Probability of confidence interval including population std mean difference
- Lower Error - Probability of lower limit greater than population std mean difference
- Upper Error - Probability of upper limit less than population std mean difference
- Ave CI Width - Average confidence interval width

Examples

```
sim.ci.stdmean2(.05, 20, 20, 1.5, 3, 4, .75, 5000)

# Should return (within sampling error):
#           Coverage Lower Error Upper Error Ave CI Width Ave Est
# Unweighted Standardizer  0.9058    0.0610    0.0332    1.342560 0.7838679
# Group 1 Standardizer    0.9450    0.0322    0.0228    1.827583 0.7862640
```

size.ci.agree *Sample size for a G-index confidence interval*

Description

Computes the sample size required to estimate a G-index of agreement for two dichotomous ratings with desired confidence interval precision. Set the G-index planning value to the smallest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.agree(alpha, G, w)
```

Arguments

alpha	alpha level for 1-alpha confidence
G	planning value of G-index
w	desired confidence interval width

Value

Returns the required sample size

Examples

```
size.ci.agree(.05, .8, .2)

# Should return:
# Sample size
#      139
```

size.ci.condmean	<i>Sample size for a conditional mean confidence interval</i>
------------------	---

Description

Computes the total sample size required to estimate a conditional mean of y at $x = x^*$ in a fixed- x simple linear regression model with desired confidence interval precision. In an experimental design, the total sample size would be allocated to the levels of the quantitative factor and it might be necessary to increase the total sample size to achieve equal sample sizes. Set the error variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.condmean(alpha, evar, xvar, diff, w)
```

Arguments

alpha	alpha level for 1-alpha confidence
evar	planning value of within group (error) variance
xvar	variance of fixed predictor variables
diff	difference between x^* and mean of x
w	desired confidence interval width

Value

Returns the required total sample size

Examples

```
size.ci.condmean(.05, 120, 125, 15, 5)

# Should return:
# Total sample size
#           210
```

`size.ci.cor`*Sample size for a Pearson or partial correlation confidence interval*

Description

Computes the sample size required to estimate a Pearson or partial correlation with desired confidence interval precision. Set $s = 0$ for a Pearson correlation. Set the correlation planning value to the smallest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.cor(alpha, cor, s, w)
```

Arguments

alpha	alpha level for 1-alpha confidence
cor	planning value of correlation
s	number of control variables
w	desired confidence interval width

Value

Returns the required sample size

References

Bonett DG, Wright TA (2000). "Sample size requirements for estimating Pearson, Kendall and Spearman correlations." *Psychometrika*, **65**(1), 23–28. ISSN 0033-3123, doi:[10.1007/BF02294183](https://doi.org/10.1007/BF02294183).

Examples

```
size.ci.cor(.05, .362, 0, .25)

# Should return:
# Sample size
#           188
```

size.ci.cronbach	<i>Sample size for a Cronbach reliability confidence interval</i>
------------------	---

Description

Computes the sample size required to estimate a Cronbach reliability with desired confidence interval precision.

Usage

```
size.ci.cronbach(alpha, rel, r, w)
```

Arguments

alpha	alpha value for 1-alpha confidence
rel	reliability planning value
r	number of measurements
w	desired confidence interval width

Value

Returns the required sample size

References

Bonett DG, Wright TA (2015). "Cronbach's alpha reliability: Interval estimation, hypothesis testing, and sample size planning." *Journal of Organizational Behavior*, **36**(1), 3–15. ISSN 08943796, [doi:10.1002/job.1960](https://doi.org/10.1002/job.1960).

Examples

```
size.ci.cronbach(.05, .85, 5, .1)

# Should return:
# Sample size
#           89
```

size.ci.cronbach2	<i>Sample size for a 2-group Cronbach reliability difference confidence interval</i>
-------------------	--

Description

Computes the sample size required to estimate a difference in population Cronbach reliability coefficients with desired precision in a 2-group design.

Usage

```
size.ci.cronbach2(alpha, rel1, rel2, r, w)
```

Arguments

alpha	alpha level for hypothesis test
rel1	group 1 reliability planning value
rel2	group 2 reliability planning value
r	number of measurements (items, raters)
w	desired confidence interval width

Value

Returns the required sample size for each group

References

Bonett DG, Wright TA (2015). "Cronbach's alpha reliability: Interval estimation, hypothesis testing, and sample size planning." *Journal of Organizational Behavior*, **36**(1), 3–15. ISSN 08943796, [doi:10.1002/job.1960](https://doi.org/10.1002/job.1960).

Examples

```
size.ci.cronbach2(.05, .85, .70, 8, .15)

# Should return:
# Sample size per group
#                180
```

size.ci.etasqr *Sample size for an eta-squared confidence interval*

Description

Computes the sample size required to estimate an eta-squared coefficient in a one-way ANOVA with desired confidence interval precision. Set the planning value of eta-squared to about 1/3 for a conservatively large sample size.

Usage

```
size.ci.etasqr(alpha, etasqr, groups, w)
```

Arguments

alpha	alpha level for 1-alpha confidence
etasqr	planning value of eta-squared
groups	number of groups
w	desired confidence interval width

Value

Returns the required sample size for each group group

Examples

```
size.ci.etasqr(.05, .333, 3, .2)

# Should return:
# Sample size per group
#                   63
```

size.ci.indirect *Sample size for an indirect effect confidence interval*

Description

Computes the approximate sample size required to estimate a standardized indirect effect in a simple mediation model. The direct effect of the independent (exogenous) variable on the response variable, controlling for the mediator variable, is assumed to be negligible.

Usage

```
size.ci.indirect(alpha, cor1, cor2, w)
```

Arguments

alpha	alpha level for 1-alpha confidence
cor1	planning value of correlation between the independent and mediator variables
cor2	planning value of correlation between the mediator and response variables
w	desired confidence interval width

Value

Returns the required sample size

Examples

```
size.ci.indirect(.05, .4, .5, .2)

# Should return:
# Sample size
#           106
```

size.ci.lc.ancova *Sample size for a linear contrast confidence interval in an ANCOVA*

Description

Computes the sample size for each group (assuming equal sample sizes) required to estimate a linear contrast of means in an ANCOVA model with desired confidence interval precision. In a nonexperimental design, the sample size is affected by the magnitude of covariate mean differences across groups. The covariate mean differences can be approximated by specifying the largest standardized covariate mean difference across all pairwise group differences and for all covariates. In an experiment, this standardized mean difference should be set to 0. Set the error variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.lc.ancova(alpha, evar, s, d, w, v)
```

Arguments

alpha	alpha level for 1-alpha confidence
evar	planning value of within group (error) variance
s	number of covariates
d	largest standardized mean difference for all covariates
w	desired confidence interval width
v	vector of between-subjects contrast coefficients

Value

Returns the required sample size for each group

Examples

```
v <- c(1, -1)
size.ci.lc.ancova(.05, 1.37, 1, 0, 1.5, v)

# Should return:
# Sample size per group
#                21
```

size.ci.lc.mean.bs	<i>Sample size for a between-subjects mean linear contrast confidence interval</i>
--------------------	--

Description

Computes the sample size in each group (assuming equal sample sizes) required to estimate a linear contrast of population means with desired confidence interval precision in a between-subjects design. Set the variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.lc.mean.bs(alpha, var, w, v)
```

Arguments

alpha	alpha level for 1-alpha confidence
var	planning value of average within-group variance
w	desired confidence interval width
v	vector of between-subjects contrast coefficients

Value

Returns the required sample size for each group

Examples

```
v <- c(.5, .5, -1)
size.ci.lc.mean.bs(.05, 5.62, 2.0, v)

# Should return:
# Sample size per group
#                34
```

size.ci.lc.mean.ws	<i>Sample size for a within-subjects mean linear contrast confidence interval</i>
--------------------	---

Description

Computes the sample size required to estimate a linear contrast of population means with desired confidence interval precision in a within-subjects design. Set the variance planning value to the largest value within a plausible range for a conservatively large sample size. Set the Pearson correlation planning value to the smallest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.lc.mean.ws(alpha, var, cor, w, q)
```

Arguments

alpha	alpha level for 1-alpha confidence
var	planning value of average variance of the measurements
cor	planning value of average correlation between measurements
w	desired confidence interval width
q	vector of within-subjects contrast coefficients

Value

Returns the required sample size

Examples

```
q <- c(.5, .5, -.5, -.5)
size.ci.lc.mean.ws(.05, 265, .8, 10, q)

# Should return:
# Sample size
#           11
```

size.ci.lc.prop.bs *Sample size for a between-subjects proportion linear contrast confidence interval*

Description

Computes the sample size in each group (assuming equal sample sizes) required to estimate a linear contrast of proportions with desired confidence interval precision in a between-subjects design. Set the proportion planning values to .5 for a conservatively large sample size.

Usage

```
size.ci.lc.prop.bs(alpha, p, w, v)
```

Arguments

alpha	alpha level for 1-alpha confidence
p	vector of proportion planning values
w	desired confidence interval width
v	vector of between-subjects contrast coefficients

Value

Returns the required sample size for each group

Examples

```
p <- c(.25, .30, .50, .50)
v <- c(.5, .5, -.5, -.5)
size.ci.lc.prop.bs(.05, p, .2, v)

# Should return:
# Sample size per group
#                   87
```

size.ci.lc.stdmean.bs *Sample size for a between-subjects standardized linear contrast of means confidence interval*

Description

Computes the sample size per group (assuming equal sample sizes) required to estimate two types of standardized linear contrasts of population means (unweighted average standardizer and single group standardizer) with desired confidence interval precision in a between-subjects design. Set the standardized linear contrast of means to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.lc.stdmean.bs(alpha, d, w, v)
```

Arguments

alpha	alpha level for 1-alpha confidence
d	planning value of standardized linear contrast of means
w	desired confidence interval width
v	vector of between-subjects contrast coefficients

Value

Returns the required sample size per group for each standardizer

References

Bonett DG (2009). “Estimating standardized linear contrasts of means with desired precision.” *Psychological Methods*, **14**(1), 1–5. ISSN 1939-1463, doi:[10.1037/a0014270](https://doi.org/10.1037/a0014270).

Examples

```
v <- c(.5, .5, -.5, -.5)
size.ci.lc.stdmean.bs(.05, 1, .6, v)

# Should return:
#               Sample size per group
# Unweighted standardizer:           49
# Single group standardizer:         65
```

size.ci.lc.stdmean.ws *Sample size for a within-subjects standardized linear contrast of means confidence interval*

Description

Computes the sample size required to estimate two types of standardized linear contrasts of population means (unweighted standardizer and single level standardizer) with desired confidence interval precision in a within-subjects design. For a conservatively large sample size, set the standardized linear contrast of means planning value to the largest value within a plausible range, and set the Pearson correlation planning value to the smallest value within a plausible range.

Usage

```
size.ci.lc.stdmean.ws(alpha, d, cor, w, q)
```

Arguments

alpha	alpha level for 1-alpha confidence
d	planning value of standardized linear contrast
cor	planning value of average correlation between measurements
w	desired confidence interval width
q	vector of within-subjects contrast coefficients

Value

Returns the required sample size for each standardizer

References

Bonett DG (2009). "Estimating standardized linear contrasts of means with desired precision." *Psychological Methods*, **14**(1), 1–5. ISSN 1939-1463, doi:10.1037/a0014270.

Examples

```
q <- c(.5, .5, -.5, -.5)
size.ci.lc.stdmean.ws(.05, 1, .7, .6, q)

# Should return:
#                Sample size
# Unweighted standardizer:      26
# Single level standardizer:    35
```

size.ci.mape1

Sample size for a mean absolute prediction error confidence interval

Description

Computes the sample size required to estimate a mean absolute prediction error for a general linear model with desired confidence interval precision. Setting $s = 0$ gives the sample size requirement for a mean absolute deviation in a one-group design. This function assumes that the prediction errors have a normal distribution.

Usage

```
size.ci.mape1(alpha, mape, s, w)
```

Arguments

alpha	alpha value for 1-alpha confidence
mape	mean absolute prediction error planning value
s	number of predictor variables
w	desired confidence interval width

Value

Returns the required sample size

Examples

```
size.ci.mapel(.05, 4.5, 5, 2)

# Should return:
# Sample size
#           57
```

size.ci.mean.ps	<i>Sample size for a paired-samples mean difference confidence interval</i>
-----------------	---

Description

Computes the sample size required to estimate a difference in population means with desired confidence interval precision in a paired-samples design. This function requires a planning value for the average of the variances for the two measurements. Set the Pearson correlation planning value to the smallest value within a plausible range for a conservatively large sample size. Set the variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.mean.ps(alpha, var, cor, w)
```

Arguments

alpha	alpha level for 1-alpha confidence
var	planning value of average variance of the two measurements
cor	planning value of correlation between measurements
w	desired confidence interval width

Value

Returns the required sample size

Examples

```
size.ci.mean.ps(.05, 265, .8, 10)

# Should return:
# Sample size
#           19
```

size.ci.mean1 *Sample size for a single mean confidence interval*

Description

Computes the sample size required to estimate a single population mean with desired confidence interval precision. Set the variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.mean1(alpha, var, w)
```

Arguments

alpha	alpha level for 1-alpha confidence
var	planning value of response variable variance
w	desired confidence interval width

Value

Returns the required sample size

Examples

```
size.ci.mean1(.05, 264.4, 10)

# Should return:
# Sample size
#           43
```

size.ci.mean2 *Sample size for a 2-group mean difference confidence interval*

Description

Computes the sample size for each group required to estimate a population mean difference with desired confidence interval precision in a 2-group design. Set $R = 1$ for equal sample sizes. Set the variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.mean2(alpha, var, w, R)
```

Arguments

alpha	alpha level for 1-alpha confidence
var	planning value of average within-group variance
w	desired confidence interval width
R	n2/n1 ratio

Value

Returns the required sample size for each group

Examples

```
size.ci.mean2(.05, 37.1, 5, 1)

# Should return:
# n1 n2
# 47 47
```

size.ci.pbcor

Sample size for a point-biserial correlation confidence interval

Description

Computes the sample size required to estimate a point-biserial correlation with desired confidence interval precision in a two-group nonexperimental design with simple random sampling. A two-group nonexperimental design implies two subpopulations (e.g., all boys and all girls in a school district). This function requires a planning value for the proportion of population members who belong to one of the two subpopulations. Set the correlation planning value to the smallest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.pbcor(alpha, cor, w, p)
```

Arguments

alpha	alpha level for 1-alpha confidence
cor	planning value of point-biserial correlation
w	desired confidence interval width
p	proportion of members in one of the two subpopulations

Value

Returns the required sample size

References

Bonett DG (2020). “Point-biserial correlation: Interval estimation, hypothesis testing, meta-analysis, and sample size determination.” *British Journal of Mathematical and Statistical Psychology*, **73**(S1), 113–144. ISSN 0007-1102, doi:10.1111/bmsp.12189.

Examples

```
size.ci.pbcpr(.05, .40, .25, .73)

# Should return:
# Sample size
#           168
```

size.ci.prop.ps	<i>Sample size for a paired-sample proportion difference confidence interval</i>
-----------------	--

Description

Computes the sample size required to estimate a proportion difference with desired confidence interval precision in a paired-samples design. Set the proportion planning values to .5 for a conservatively large sample size. Set the phi correlation planning value to the smallest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.prop.ps(alpha, p1, p2, phi, w)
```

Arguments

alpha	alpha level for 1-alpha confidence
p1	planning value of proportion for group 1
p2	planning value of proportion for group 2
phi	planning value of phi correlation
w	desired confidence interval width

Value

Returns the required sample size

Examples

```
size.ci.prop.ps(.05, .2, .3, .8, .1)

# Should return:
# Sample size
#           118
```

size.ci.prop1	<i>Sample size for a single proportion confidence interval</i>
---------------	--

Description

Computes the sample size required to estimate a single proportion with desired confidence interval precision. Set the proportion planning value to .5 for a conservatively large sample size.

Usage

```
size.ci.prop1(alpha, p, w)
```

Arguments

alpha	alpha level for 1-alpha confidence
p	planning value of proportion
w	desired confidence interval width

Value

Returns the required sample size

Examples

```
size.ci.prop1(.05, .4, .2)

# Should return:
# Sample size
#           93
```

 size.ci.prop2

Sample size for a 2-group proportion difference confidence interval

Description

Computes the sample size in each group (assuming equal sample sizes) required to estimate a difference of proportions with desired confidence interval precision in a 2-group design. Set the proportion planning values to .5 for a conservatively large sample size.

Usage

```
size.ci.prop2(alpha, p1, p2, w)
```

Arguments

alpha	alpha level for 1-alpha confidence
p1	planning value of proportion for group 1
p2	planning value of proportion for group 2
w	desired confidence interval width

Value

Returns the required sample size for each group

Examples

```
size.ci.prop2(.05, .4, .2, .15)

# Should return:
# Sample size per group
#                274
```

 size.ci.ratio.mean.ps *Sample size for a paired-samples mean ratio confidence interval*

Description

Computes the sample size required to estimate a ratio of population means with desired confidence interval precision in a paired-samples design. Set the correlation planning value to the smallest value within a plausible range for a conservatively large sample size. This function requires planning values for each mean and the sample size requirement is very sensitive to these planning values. Set the variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.ratio.mean.ps(alpha, var, m1, m2, cor, r)
```

Arguments

alpha	alpha level for 1-alpha confidence
var	planning value of average variance of the two measurements
m1	planning value of mean for measurement 1
m2	planning value of mean for measurement 2
cor	planning value for correlation between measurements
r	desired upper to lower confidence interval endpoint ratio

Value

Returns the required sample size

Examples

```
size.ci.ratio.mean.ps(.05, 400, 150, 100, .7, 1.2)

# Should return:
# Sample size
#           21
```

size.ci.ratio.mean2 *Sample size for a 2-group mean ratio confidence interval*

Description

Computes the sample size in each group required to estimate a ratio of population means with desired confidence interval precision in a 2-group design. This function requires planning values for each mean and the sample size requirement is very sensitive to these planning values. Set the variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.ratio.mean2(alpha, var, m1, m2, r, R)
```

Arguments

alpha	alpha level for 1-alpha confidence
var	planning value of average within-group variance
m1	planning value of mean for group 1
m2	planning value of mean for group 2
r	desired upper to lower confidence interval endpoint ratio
R	n2/n1 ratio

Value

Returns the required sample size for each group

Examples

```
size.ci.ratio.mean2(.05, .4, 3.5, 3.1, 1.2, 2)

# Should return:
# n1  n2
# 53 106
```

size.ci.ratio.prop.ps *Sample size for a paired-samples proportion ratio confidence interval*

Description

Computes the sample size required to estimate a ratio of proportions with desired confidence interval precision in a paired-samples design. Set the phi correlation planning value to the smallest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.ratio.prop.ps(alpha, p1, p2, phi, r)
```

Arguments

alpha	alpha level for 1-alpha confidence
p1	planning value of proportion for measurement 1
p2	planning value of proportion for measurement 2
phi	planning value of phi correlation
r	desired upper to lower confidence interval endpoint ratio

Value

Returns the required sample size

Examples

```
size.ci.ratio.prop.ps(.05, .4, .2, .7, 2)

# Should return:
# Sample size
#           67
```

size.ci.ratio.prop2 *Sample size for a 2-group proportion ratio confidence interval*

Description

Computes the sample size in each group (assuming equal sample sizes) required to estimate a ratio of proportions with desired confidence interval precision in a 2-group design.

Usage

```
size.ci.ratio.prop2(alpha, p1, p2, r)
```

Arguments

alpha	alpha level for 1-alpha confidence
p1	planning value of proportion for group 1
p2	planning value of proportion for group 2
r	desired upper to lower confidence interval endpoint ratio

Value

Returns the required sample size for each group

Examples

```
size.ci.ratio.prop2(.05, .2, .1, 2)

# Should return:
# Sample size per group
#           416
```

size.ci.rsqr *Sample size for a squared multiple correlation confidence interval*

Description

Computes the sample size required to estimate a squared multiple correlation in a random-x regression model with desired confidence interval precision. Set the planning value of the squared multiple correlation to 1/3 for a conservatively large sample size.

Usage

```
size.ci.rsqr(alpha, r2, s, w)
```

Arguments

alpha	alpha level for 1-alpha confidence
r2	planning value of squared multiple correlation
s	number of predictor variables in model
w	desired confidence interval width

Value

Returns the required sample size

Examples

```
size.ci.rsqr(.05, .25, 5, .2)

# Should return:
# Sample size
#           214
```

size.ci.second *Sample size for a second-stage confidence interval*

Description

Computes the second-stage sample size required to obtain desired confidence interval precision. This function can use either the total sample size for all groups in the first stage sample or a single group sample size in the first stage sample. If the total first-stage sample size is given, then the function computes the total sample size required in the second-stage sample. If a single group first-stage sample size is given, then the function computes the single-group sample size required in the second-stage sample. The second-stage sample is combined with the first-stage sample to obtain the desired confidence interval width.

Usage

```
size.ci.second(n0, w0, w)
```

Arguments

n0	first-stage sample size
w0	confidence interval width in first-stage sample
w	desired confidence interval width

Value

Returns the required sample size for the second-stage sample

Examples

```
size.ci.second(20, 5.3, 2.5)

# Should return:
# Second-stage sample size
#                70
```

```
size.ci.slope
```

Sample size for a slope confidence interval

Description

Computes the total sample size required to estimate a slope with desired confidence interval precision in a between-subjects design with a quantitative factor. In an experimental design, the total sample size would be allocated to the levels of the quantitative factor and it might be necessary to increase the total sample size to achieve equal sample sizes. Set the error variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.slope(alpha, evar, x, w)
```

Arguments

alpha	alpha level for 1-alpha confidence
evar	planning value of within group (error) variance
x	vector of x values of the quantitative factor
w	desired confidence interval width

Value

Returns the required total sample size

Examples

```
x <- c(2, 5, 8)
size.ci.slope(.05, 31.1, x, 1)

# Should return:
# Total sample size
#                83
```

size.ci.spear

Sample size for a Spearman correlation confidence interval

Description

Computes the sample size required to estimate a Spearman correlation with desired confidence interval precision. Set the correlation planning value to the smallest value within a plausible range for a conservatively large sample size.

Usage

```
size.ci.spear(alpha, cor, w)
```

Arguments

alpha	alpha level for 1-alpha confidence
cor	planning value of Spearman correlation
w	desired confidence interval width

Value

Returns the required sample size

References

Bonett DG, Wright TA (2000). "Sample size requirements for estimating Pearson, Kendall and Spearman correlations." *Psychometrika*, **65**(1), 23–28. ISSN 0033-3123, doi:[10.1007/BF02294183](https://doi.org/10.1007/BF02294183).

Examples

```
size.ci.spear(.05, .362, .25)

# Should return:
# Sample size
#           200
```

size.ci.stdmean.ps	<i>Sample size for a paired-samples standardized mean difference confidence interval</i>
--------------------	--

Description

Computes the sample size required to estimate two types of population standardized mean differences (unweighted standardizer and single group standardizer) with desired confidence interval precision in a paired-samples design. For a conservatively large sample size, set the standardized mean difference planning value to the largest value within a plausible range and set the Pearson correlation planning value to the smallest value within a plausible range.

Usage

```
size.ci.stdmean.ps(alpha, d, cor, w)
```

Arguments

alpha	alpha level for 1-alpha confidence
d	planning value of standardized mean difference
cor	planning value of correlation between measurements
w	desired confidence interval width

Value

Returns the required sample size for each standardizer

References

Bonett DG (2009). "Estimating standardized linear contrasts of means with desired precision." *Psychological Methods*, **14**(1), 1–5. ISSN 1939-1463, doi:[10.1037/a0014270](https://doi.org/10.1037/a0014270).

Examples

```
size.ci.stdmean.ps(.05, 1, .65, .6)

# Should return:
#                               Sample Size
# Unweighted standardizer:      46
# Single group standardizer:    52
```

size.ci.stdmean2	<i>Sample size for a 2-group standardized mean difference confidence interval</i>
------------------	---

Description

Computes the sample size per group required to estimate two types of population standardized mean differences (unweighted standardizer and single group standardizer) with desired confidence interval precision in a 2-group design. Set the standardized mean difference planning value to the largest value within a plausible range for a conservatively large sample size. Set $R = 1$ for equal sample sizes.

Usage

```
size.ci.stdmean2(alpha, d, w, R)
```

Arguments

alpha	alpha level for 1-alpha confidence
d	planning value of standardized mean difference
w	desired confidence interval width
R	n_2/n_1 ratio

Value

Returns the required sample size per group for each standardizer

References

Bonett DG (2009). "Estimating standardized linear contrasts of means with desired precision." *Psychological Methods*, **14**(1), 1–5. ISSN 1939-1463, doi:[10.1037/a0014270](https://doi.org/10.1037/a0014270).

Examples

```

size.ci.stdmean2(.05, .75, .5, 1)

# Should return:
#
#           n1  n2
# Unweighted standardizer:  132 132
# Single group standardizer: 141 141

```

```

size.equiv.mean.ps      Sample size for a paired-samples mean equivalence test

```

Description

Computes the sample size required to perform an equivalence test for the difference in population means with desired power in a paired-samples design. The value of h specifies a range of practical equivalence, $-h$ to h , for the difference in population means. The planning value for the absolute mean difference must be less than h . Equivalence tests often require a very large sample size. Equivalence tests usually use $2 \times \alpha$ rather than α (e.g., use $\alpha = .10$ rather than $\alpha = .05$). Set the Pearson correlation value to the smallest value within a plausible range, and set the variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```

size.equiv.mean.ps(alpha, pow, var, es, cor, h)

```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
var	planning value of average variance of the two measurements
es	planning value of mean difference
cor	planning value of the correlation between measurements
h	upper limit for range of practical equivalence

Value

Returns the required sample size

Examples

```

size.equiv.mean.ps(.10, .85, 15, .5, .7, 1.5)

# Should return:
# Sample size
#           68

```

size.equiv.mean2	<i>Sample size for a 2-group mean equivalence test</i>
------------------	--

Description

Computes the sample size in each group (assuming equal sample sizes) required to perform an equivalence test for the difference in population means with desired power in a 2-group design. The value of h specifies a range of practical equivalence, $-h$ to h , for the difference in population means. The planning value for the absolute mean difference must be less than h . Equivalence tests often require a very large sample size. Equivalence tests usually use $2 \times \alpha$ rather than α (e.g., use $\alpha = .10$ rather than $\alpha = .05$). Set the variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.equiv.mean2(alpha, pow, var, es, h)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
var	planning value of average within-group variance
es	planning value of mean difference
h	upper limit for range of practical equivalence

Value

Returns the required sample size for each group

Examples

```
size.equiv.mean2(.10, .80, 15, 2, 4)

# Should return:
# Sample size per group
#           50
```

size.equiv.prop.ps *Sample size for a paired-samples proportion equivalence test*

Description

Computes the sample size required to perform an equivalence test for the difference in population proportions with desired power in a paired-samples design. The value of h specifies a range of practical equivalence, -h to h, for the difference in population proportions. The absolute difference in the proportion planning values must be less than h. Equivalence tests often require a very large sample size. Equivalence tests usually use $2 \times \alpha$ rather than α (e.g., use $\alpha = .10$ rather than $\alpha = .05$). This function sets the effect size equal to the difference in proportion planning values. Set the phi correlation planning value to the smallest value within a plausible range for a conservatively large sample size.

Usage

```
size.equiv.prop.ps(alpha, pow, p1, p2, phi, h)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
p1	planning value of proportion for measurement 1
p2	planning value of proportion for measurement 2
phi	planning value of phi correlation
h	upper limit for range of practical equivalence

Value

Returns the required sample size

Examples

```
size.equiv.prop.ps(.1, .8, .30, .35, .40, .15)

# Should return:
# Sample size
#           173
```

size.equiv.prop2	<i>Sample size for a 2-group proportion equivalence test</i>
------------------	--

Description

Computes the sample size in each group (assuming equal sample sizes) required to perform an equivalence test for the difference in population proportions with desired power in a 2-group design. The value of h specifies a range of practical equivalence, $-h$ to h , for the difference in population proportions. The absolute difference in the proportion planning values must be less than h . Equivalence tests often require a very large sample size. Equivalence tests usually use $2 \times \alpha$ rather than α (e.g., use $\alpha = .10$ rather than $\alpha = .05$).

Usage

```
size.equiv.prop2(alpha, pow, p1, p2, h)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
p1	planning value of proportion for group 1
p2	planning value of proportion for group 2
h	upper limit for range of practical equivalence

Value

Returns the required sample size for each group

Examples

```
size.equiv.prop2(.1, .8, .30, .35, .15)

# Should return:
# Sample size per group
#           288
```

size.interval.cor *Sample size for a finite interval test of a Pearson or partial correlation*

Description

Computes the sample size required to perform a finite interval test for a Pearson or a partial correlation with desired power. Set $s = 0$ for a Pearson correlation. The correlation planning value must be a value within the hypothesized finite interval.

Usage

```
size.interval.cor(alpha, pow, cor, s, h)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
cor	planning value of correlation
s	number of control variables
h	upper limit of hypothesized interval

Value

Returns the required sample size

Examples

```
size.interval.cor(.05, .8, .1, 0, .25)

# Should return:
# Sample size
#           360
```

size.supinf.mean.ps *Sample size for a paired-samples mean superiority or noninferiority test*

Description

Computes the sample size required to perform a superiority or noninferiority test for the difference in population means with desired power in a paired-samples design. For a superiority test, specify the upper limit (h) for the range of practical equivalence and specify an effect size (es) such that $es > h$. For a noninferiority test, specify the lower limit (-h) for the range of practical equivalence and specify an effect size such that $es > -h$. Set the Pearson correlation planning value to the smallest value within a plausible range, and set the variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.supinf.mean.ps(alpha, pow, var, es, cor, h)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
var	planning value of average variance of the two measurements
es	planning value of mean difference
cor	planning value of the correlation between measurements
h	upper or lower limit for range of practical equivalence

Value

Returns the required sample size

Examples

```
size.supinf.mean.ps(.05, .80, 225, 9, .75, 4)

# Should return:
# Sample size
#           38
```

size.supinf.mean2	<i>Sample size for a 2-group mean superiority or noninferiority test</i>
-------------------	--

Description

Computes the sample size in each group (assuming equal sample sizes) required to perform a superiority or noninferiority test for the difference in population means with desired power in a 2-group design. For a superiority test, specify the upper limit (h) for the range of practical equivalence and specify an effect size (es) such that $es > h$. For a noninferiority test, specify the lower limit (-h) for the range of practical equivalence and specify an effect size such that $es > -h$. Set the variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.supinf.mean2(alpha, pow, var, es, h)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
var	planning value of average within-group variance
es	planning value of mean difference
h	upper or lower limit for range of practical equivalence

Value

Returns the required sample size for each group

Examples

```
size.supinf.mean2(.05, .80, 225, 9, 4)

# Should return:
# Sample size per group
#           143
```

size.supinf.prop.ps *Sample size for a paired-samples superiority or inferiority test of proportions*

Description

Computes the sample size required to perform a superiority or inferiority test for the difference in population proportions with desired power in a paired-samples design. For a superiority test, specify the upper limit (h) for the range of practical equivalence and specify values of p1 and p2 such that $p1 - p2 > h$. For an inferiority test, specify the lower limit (-h) for the range of practical equivalence and specify values of p1 and p2 such that $p1 - p2 > -h$. This function sets the effect size equal to the difference in proportion planning values. Set the phi correlation planning value to the smallest value within a plausible range for a conservatively large sample size.

Usage

```
size.supinf.prop.ps(alpha, pow, p1, p2, phi, h)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
p1	planning value of proportion for measurement 1
p2	planning value of proportion for measurement 2
phi	planning value of phi correlation
h	lower or upper limit for range of practical equivalence

Value

Returns the required sample size

Examples

```
size.supinf.prop.ps(.05, .9, .35, .20, .45, .05)

# Should return:
# Sample size
#           227
```

size.supinf.prop2	<i>Sample size for a 2-group superiority or inferiority test of proportions</i>
-------------------	---

Description

Computes the sample size in each group (assuming equal sample sizes) required to perform a superiority or inferiority test for the difference in population proportions with desired power in a 2-group design. For a superiority test, specify the upper limit (h) for the range of practical equivalence and specify values of p1 and p2 such that $p1 - p2 > h$. For an inferiority test, specify the lower limit (-h) for the range of practical equivalence and specify values of p1 and p2 such that $p1 - p2 > -h$. This function sets the effect size equal to $p1 - p2$.

Usage

```
size.supinf.prop2(alpha, pow, p1, p2, h)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
p1	planning value of proportion for group 1
p2	planning value of proportion for group 2
h	lower or upper limit for range of practical equivalence

Value

Returns the required sample size for each group

Examples

```
size.supinf.prop2(.05, .9, .35, .20, .05)

# Should return:
# Sample size per group
#           408
```

size.test.cor

Sample size for a test of a Pearson or partial correlation

Description

Computes the sample size required to test a Pearson or a partial correlation with desired power. Set $s = 0$ for a Pearson correlation.

Usage

```
size.test.cor(alpha, pow, cor, s, h)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
cor	planning value of correlation
s	number of control variables
h	hypothesized value of correlation

Value

Returns the required sample size

Examples

```
size.test.cor(.05, .9, .45, 0, 0)

# Should return:
# Sample size
#           48
```

size.test.cor2	<i>Sample size for a test of equal Pearson or partial correlation in a 2-group design</i>
----------------	---

Description

Computes the sample size required to test equality of two Pearson or partial correlation with desired power in a 2-group design. Set $s = 0$ for a Pearson correlation.

Usage

```
size.test.cor2(alpha, pow, cor1, cor2, s)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
cor1	planning value of correlation
cor2	planning value of correlation
s	number of control variables

Value

Returns the required sample size for each group

Examples

```
size.test.cor2(.05, .8, .4, .2, 0)

# Should return:
# Sample size per group
#                325
```

size.test.cronbach	<i>Sample size to test a Cronbach reliability</i>
--------------------	---

Description

Computes the sample size required to test a Cronbach reliability with desired power.

Usage

```
size.test.cronbach(alpha, pow, rel, r, h)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
rel	reliability planning value
r	number of measurements
h	null hypothesis value of reliability

Value

Returns the required sample size

References

Bonett DG, Wright TA (2015). "Cronbach's alpha reliability: Interval estimation, hypothesis testing, and sample size planning." *Journal of Organizational Behavior*, **36**(1), 3–15. ISSN 08943796, doi:10.1002/job.1960.

Examples

```
size.test.cronbach(.05, .85, .80, 5, .7)

# Should return:
# Sample size
#           139
```

size.test.cronbach2 *Sample size to test equality of Cronbach reliability coefficients in a 2-group design*

Description

Computes the sample size required to test a difference in population Cronbach reliability coefficients with desired power in a 2-group design.

Usage

```
size.test.cronbach2(alpha, pow, rel1, rel2, r)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
rel1	group 1 reliability planning value
rel2	group 2 reliability planning value
r	number of measurements (items, raters)

Value

Returns the required sample size for each group

References

Bonett DG, Wright TA (2015). “Cronbach’s alpha reliability: Interval estimation, hypothesis testing, and sample size planning.” *Journal of Organizational Behavior*, **36**(1), 3–15. ISSN 08943796, doi:10.1002/job.1960.

Examples

```
size.test.cronbach2(.05, .80, .85, .70, 8)

# Should return:
# Sample size per group
#                77
```

size.test.lc.ancova *Sample size for a mean linear contrast test in an ANCOVA*

Description

Computes the sample size for each group (assuming equal sample sizes) required to test a linear contrast of means in an ANCOVA model with desired power. In a nonexperimental design, the sample size is affected by the magnitude of covariate mean differences across groups. The covariate mean differences can be approximated by specifying the largest standardized covariate mean difference across all pairwise comparisons and for all covariates. In an experiment, this standardized mean difference is set to 0. Set the error variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.test.lc.ancova(alpha, pow, evar, es, s, d, v)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
evar	planning value of within-group (error) variance
es	planning value of linear contrast
s	number of covariates
d	largest standardized mean difference for all covariates
v	vector of between-subjects contrast coefficients

Value

Returns the required sample size for each group

Examples

```
v <- c(.5, .5, -1)
size.test.lc.ancova(.05, .9, 1.37, .7, 1, 0, v)

# Should return:
# Sample size per group
#                47
```

size.test.lc.mean.bs *Sample size for a test of a between-subjects mean linear contrast*

Description

Computes the sample size in each group (assuming equal sample sizes) required to test a linear contrast of population means with desired power in a between-subjects design. Set the variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.test.lc.mean.bs(alpha, pow, var, es, v)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
var	planning value of average within-group variance
es	planning value of linear contrast of means
v	vector of between-subjects contrast coefficients

Value

Returns the required sample size for each group

Examples

```
v <- c(1, -1, -1, 1)
size.test.lc.mean.bs(.05, .90, 27.5, 5, v)

# Should return:
# Sample size per group
#                47
```

size.test.lc.mean.ws *Sample size for a test of a within-subjects mean linear contrast*

Description

Computes the sample size required to test a linear contrast of population means with desired power in a within-subjects design. Set the average variance planning value to the largest value within a plausible range for a conservatively large sample size. Set the average correlation planning value to the smallest value within a plausible range for a conservatively large sample size.

Usage

```
size.test.lc.mean.ws(alpha, pow, var, es, cor, q)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
var	planning value of average variance of measurements
es	planning value of linear contrast of means
cor	planning value of average correlation between measurements
q	vector of with-subjects contrast coefficients

Value

Returns the required sample size

Examples

```
q <- c(.5, .5, -.5, -.5)
size.test.lc.mean.ws(.05, .90, 50.7, 2, .8, q)

# Should return:
# Sample size
#           29
```

size.test.lc.prop.bs *Sample size for a test of between-subjects proportion linear contrast*

Description

Computes the sample size in each group (assuming equal sample sizes) required to test a linear contrast of population proportions with desired power in a between-subjects design. This function requires planning values for all proportions. Set the proportion planning values to .5 for a conservatively large sample size. The planning value for the effect size (linear contrast of proportions) could be set equal to the linear contrast of proportion planning values or it could be set equal to a minimally interesting effect size.

Usage

```
size.test.lc.prop.bs(alpha, pow, p, es, v)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
p	vector of proportion planning values
es	planning value of proportion linear contrast
v	vector of between-subjects contrast coefficients

Value

Returns the required sample size for each group

Examples

```
p <- c(.25, .30, .50, .50)
v <- c(.5, .5, -.5, -.5)
size.test.lc.prop.bs(.05, .9, p, .15, v)

# Should return:
# Sample size per group
#           105
```

`size.test.mann`*Sample size for a Mann-Whitney test*

Description

Computes the sample size in each group (assuming equal sample sizes) required for the Mann-Whitney test with desired power. A planning value of the Mann-Whitney parameter is required. In a 2-group experiment, this parameter is the proportion of members in the population with scores that would be larger under treatment 1 than treatment 2. In a 2-group nonexperiment where participants are sampled from two subpopulations of sizes N1 and N2, the parameter is the proportion of all N1 x N2 pairs in which a member from subpopulation 1 has a larger score than a member from subpopulation 2.

Usage

```
size.test.mann(alpha, pow, p)
```

Arguments

<code>alpha</code>	alpha level for hypothesis test
<code>pow</code>	desired power
<code>p</code>	planning value of Mann-Whitney parameter

Value

Returns the required sample size for each group

References

Noether GE (1987). "Sample size determination for some common nonparametric tests." *Journal of the American Statistical Association*, **82**(398), 645–647. ISSN 0162-1459, doi:[10.1080/01621459.1987.10478478](https://doi.org/10.1080/01621459.1987.10478478).

Examples

```
size.test.mann(.05, .90, .3)

# Should return:
# Sample size per group
#                44
```

size.test.mean.ps *Sample size for a test of a paired-samples mean difference*

Description

Computes the sample size required to test a difference in population means with desired power in a paired-samples design. Set the Pearson correlation planning value to the smallest value within a plausible range, and set the variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.test.mean.ps(alpha, pow, var, es, cor)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
var	planning value of average variance of the two measurements
es	planning value of mean difference
cor	planning value of correlation

Value

Returns the required sample size

Examples

```
size.test.mean.ps(.05, .80, 1.25, .5, .75)

# Should return:
# Sample size
#           22
```

size.test.mean1 *Sample size for a test of a single mean*

Description

Computes the sample size required to test a single population mean with desired power in a 1-group design. Set the variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.test.mean1(alpha, pow, var, es)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
var	planning value of response variable variance
es	planning value of mean minus null hypothesis value

Value

Returns the required sample size

Examples

```
size.test.mean1(.05, .9, 80.5, 7)

# Should return:
# Sample size
#           20
```

size.test.mean2	<i>Sample size for a test of a 2-group mean difference</i>
-----------------	--

Description

Computes the sample size in each group required to test a difference in population means with desired power in a 2-group design. Set $R=1$ for equal sample sizes. Set the variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.test.mean2(alpha, pow, var, es, R)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
var	planning value of average within-group variance
es	planning value of mean difference
R	n_2/n_1 ratio

Value

Returns the required sample size for each group

Examples

```
size.test.mean2(.05, .95, 100, 10, 1)

# Should return:
# n1  n2
# 27  27
```

size.test.prop.ps *Sample size for a test of a paired-samples proportion difference*

Description

Computes the sample size required to test a difference in population proportions with desired power in a paired-samples design. This function requires planning values for both proportions and a phi coefficient that describes the correlation between the two dichotomous measurements. The proportion planning values can set to .5 for a conservatively large sample size. The planning value for the effect size (proportion difference) could be set equal to the difference of the two proportion planning values or it could be set equal to a minimally interesting effect size. Set the phi correlation planning value to the smallest value within a plausible range for a conservatively large sample size.

Usage

```
size.test.prop.ps(alpha, pow, p1, p2, phi, es)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
p1	planning value of proportion for measurement 1
p2	planning value of proportion for measurement 2
phi	planning value of phi correlation
es	planning value of proportion difference

Value

Returns the required sample size

Examples

```
size.test.prop.ps(.05, .80, .4, .3, .5, .1)

# Should return:
# Sample size
#           177
```

size.test.prop1	<i>Sample size for a test of a single proportion</i>
-----------------	--

Description

Computes the sample size required to test a single population proportion with desired power in a 1-group design. Set the proportion planning value to .5 for a conservatively large sample size. The value of the effect size (expected population proportion minus hypothesized value) need not be based on the proportion planning value.

Usage

```
size.test.prop1(alpha, pow, p, es)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
p	planning value of proportion
es	planning value of proportion minus null hypothesis value

Value

Returns the required sample size

Examples

```
size.test.prop1(.05, .9, .5, .2)

# Should return:
# Sample size
#           66
```

size.test.prop2	<i>Sample size for a test of a 2-group proportion difference</i>
-----------------	--

Description

Computes the sample size in each group required to test a difference in population proportions with desired power in a 2-group design. This function requires planning values for both proportions. Set the proportion planning values to .5 for a conservatively large sample size. The planning value for the effect size (proportion difference) could be set equal to the difference of the two proportion planning values or it could be set equal to a minimally interesting effect size.

Usage

```
size.test.prop2(alpha, pow, p1, p2, es)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
p1	planning value of proportion for group 1
p2	planning value of proportion for group 2
es	planning value of proportion difference

Value

Returns the required sample size for eachr group

Examples

```
size.test.prop2(.05, .8, .2, .4, .2)

# Should return:
# Sample size per group
#                79
```

size.test.sign.ps *Sample size for a paired-samples Sign test*

Description

Computes sample size required for a Sign test with desired power in a paired-samples design. A planning value of the paired-samples Sign test parameter is required. In a paired-samples experiment, this parameter is the proportion of members in the population with scores that would be larger under treatment 1 than treatment 2. In a paired-samples nonexperiment, this parameter is the proportion of members in the population with measurement 1 scores that are larger than their measurement 2 scores.

Usage

```
size.test.sign.ps(alpha, pow, p)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
p	planning value of proportion

Value

Returns the required sample size

Examples

```
size.test.sign.ps(.05, .90, .75)

# Should return:
# Sample size
#           32
```

size.test.sign1 *Sample size for a 1-sample Sign test*

Description

Computes the sample size required for a Sign test with desired power in a 1-sample design. A planning value of the 1-sample Sign test parameter value is required. This parameter is the proportion of members in the population with scores greater than the hypothesized value.

Usage

```
size.test.sign1(alpha, pow, p)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
p	planning value of proportion

Value

Returns the required sample size

Examples

```
size.test.sign1(.05, .90, .3)

# Should return:
# Sample size
#           56
```

size.test.slope	<i>Sample size for a test of a slope</i>
-----------------	--

Description

Computes the total sample size required to test a population slope with desired power in a between-subjects design with a quantitative factor. In an experimental design, the total sample size would be allocated to the levels of the quantitative factor and it might be necessary to use a larger total sample size to achieve equal sample sizes. Set the error variance planning value to the largest value within a plausible range for a conservatively large sample size.

Usage

```
size.test.slope(alpha, pow, evar, x, slope, h)
```

Arguments

alpha	alpha level for hypothesis test
pow	desired power
evar	planning value of within-group (error) variance
x	vector of x values of the quantitative factor
slope	planning value of slope
h	hypothesized value of slope

Value

Returns the required total sample size

Examples

```
x <- c(2, 5, 8)
size.test.slope(.05, .9, 31.1, x, .75, 0)

# Should return:
# Total sample size
#           100
```

slope.contrast	<i>Contrast coefficients for the slope of a quantitative factor</i>
----------------	---

Description

Computes the contrast coefficients to estimate the slope of a line in a single factor design with a quantitative factor.

Usage

```
slope.contrast(x)
```

Arguments

x vector of numeric factor levels

Value

Returns the vector of contrast coefficients

Examples

```
x <- c(25, 50, 75, 100)
slope.contrast(x)

# Should return:
#   Coefficient
# [1,]   -0.012
# [2,]   -0.004
# [3,]    0.004
# [4,]    0.012
```

spearmanbrown	<i>Computes the reliability of a scale with r2 measurements given the reliability of a scale with r1 measurements</i>
---------------	---

Description

Computes the reliability of a scale that is the sum or average of r2 parallel measurements given the reliability of a scale that is the sum or average of r1 parallel measurements. The "measurements" can be items, trials, raters, or occasions.

Usage

```
spearmanbrown(re1, r1, r2)
```

Arguments

re1	reliability of the sum or average of r1 measurements
r1	number of measurements in the original scale
r2	number of measurements in the new scale

Value

Returns the reliability of the sum or average of r2 measurements

Examples

```
spearmanbrown(.6, 10, 20)

# Should return:
# Reliability of r2 measurements
#                .75
```

test.anova1.bs	<i>Between-subjects F statistic and eta-squared from summary information</i>
----------------	--

Description

Computes the F statistic, p-value, eta-squared, and adjusted eta-squared for the main effect of Factor A in a one-way between-subjects ANOVA using the estimated group means, estimated group standard deviations, and group sample sizes.

Usage

```
test.anova1.bs(m, sd, n)
```

Arguments

m	vector of estimated group means
sd	vector of estimated group standard deviations
n	vector of group sample sizes

Value

Returns a 1-row matrix. The columns are:

- F - F statistic for test of null hypothesis
- dfA - degrees of freedom for between-subjects factor
- dfE - error degrees of freedom
- dfA - degrees of freedom for between-subjects factor
- p - p-value for F-test
- Eta-squared - estimate of eta-squared
- adj Eta-squared - a bias adjusted estimate of eta-squared

Examples

```
m <- c(12.4, 8.6, 10.5)
sd <- c(3.84, 3.12, 3.48)
n <- c(20, 20, 20)
test.anova1.bs(m, sd, n)

# Should return:
#      F dfA dfE      p Eta-squared  adj Eta-squared
# 5.919585  2  57 0.004614428  0.1719831  0.1429298
```

test.kurtosis

Computes p-value for test of excess kurtosis

Description

Computes a Monte Carlo p-value (250,000 replications) for the null hypothesis that the sample data come from a normal distribution. If the p-value is small (e.g., less than .05) and excess kurtosis is positive, then the normality assumption can be rejected due to leptokurtosis. If the p-value is small (e.g., less than .05) and excess kurtosis is negative, then the normality assumption can be rejected due to platykurtosis.

Usage

```
test.kurtosis(y)
```

Arguments

y vector of quantitative scores

Value

Returns a 1-row matrix. The columns are:

- Kurtosis - estimate of kurtosis coefficient
- Excess - estimate of excess kurtosis (kurtosis - 3)
- p - Monte Carlo two-sided p-value for test of zero excess kurtosis

Examples

```
y <- c(30, 20, 15, 10, 10, 60, 20, 25, 20, 30, 10, 5, 50, 40, 95)
test.kurtosis(y)

# Should return:
# Kurtosis Excess      p
# 4.8149  1.8149 0.0385
```

test.mono.mean.bs	<i>Test of a monotonic trend in means for an ordered between-subjects factor</i>
-------------------	--

Description

Computes simultaneous confidence intervals for all adjacent pairwise comparisons of population means using estimated group means, estimated group standard deviations, and samples sizes as input. Equal variances are not assumed. A Satterthwaite adjustment to the degrees of freedom is used to improve the accuracy of the confidence intervals. If one or more lower limits are greater than 0 and no upper limit is less than 0, then conclude that the population means are monotonic decreasing. If one or more upper limits are less than 0 and no lower limits are greater than 0, then conclude that the population means are monotonic increasing. Reject the hypothesis of a monotonic trend if any lower limit is greater than 0 and any upper limit is less than 0.

Usage

```
test.mono.mean.bs(alpha, m, sd, n)
```

Arguments

alpha	alpha level for simultaneous 1-alpha confidence
m	vector of estimated group means
sd	vector of estimated group standard deviations
n	vector of sample sizes

Value

Returns a matrix with the number of rows equal to the number of adjacent pairwise comparisons. The columns are:

- Estimate - estimated mean difference
- SE - standard error
- LL - one-sided lower limit of the confidence interval
- UL - one-sided upper limit of the confidence interval

Examples

```
m <- c(12.86, 24.57, 36.29, 53.21)
sd <- c(13.185, 12.995, 14.773, 15.145)
n <- c(20, 20, 20, 20)
test.mono.mean.bs(.05, m, sd, n)

# Should return:
#   Estimate      SE      LL      UL
# 1 2   -11.71  4.139530 -22.07803 -1.3419744
# 2 3   -11.72  4.399497 -22.74731 -0.6926939
# 3 4   -16.92  4.730817 -28.76921 -5.0707936
```

test.mono.prop.bs	<i>Test of monotonic trend in proportions for an ordered between-subjects factor</i>
-------------------	--

Description

Computes simultaneous confidence intervals for all adjacent pairwise comparisons of population proportions using group frequency counts and samples sizes as input. If one or more lower limits are greater than 0 and no upper limit is less than 0, then conclude that the population proportions are monotonic decreasing. If one or more upper limits are less than 0 and no lower limits are greater than 0, then conclude that the population proportions are monotonic increasing. Reject the hypothesis of a monotonic trend if any lower limit is greater than 0 and any upper limit is less than 0.

Usage

```
test.mono.prop.bs(alpha, f, n)
```

Arguments

alpha	alpha level for simultaneous 1-alpha confidence
f	vector of frequency counts of participants who have the attribute
n	vector of sample sizes

Value

Returns a matrix with the number of rows equal to the number of adjacent pairwise comparisons. The columns are:

- Estimate - estimated proportion difference
- SE - standard error
- LL - one-sided lower limit of the confidence interval
- UL - one-sided upper limit of the confidence interval

Examples

```
f <- c(67, 49, 30, 10)
n <- c(100, 100, 100, 100)
test.mono.prop.bs(.05, f, n)

# Should return:
#   Estimate      SE      LL      UL
# 1 2 0.1764706 0.06803446 0.01359747 0.3393437
# 2 3 0.1862745 0.06726135 0.02525219 0.3472968
# 3 4 0.1960784 0.05493010 0.06457688 0.3275800
```

test.prop.bs

Hypothesis test of equal proportions in a between-subjects design

Description

Computes a Pearson chi-square test for equal population proportions for a dichotomous response variable in a one-factor between-subjects design.

Usage

```
test.prop.bs(f, n)
```

Arguments

f vector of frequency counts of participants who have the attribute
n vector of sample sizes

Value

Returns a 1-row matrix. The columns are:

- Chi-square - chi-square test statistic
- df - degrees of freedom
- p - p-value

References

Fleiss JL, Paik MC (2003). *Statistical Methods for Rates and Proportions*, 3rd edition. Wiley.

Examples

```
f <- c(35, 30, 15)
n <- c(50, 50, 50)
test.prop.bs (f, n)

# Should return:
# Chi-square df          p
# 17.41071  2 0.0001656958
```

test.prop.ps

Hypothesis test for a paired-samples proportion difference

Description

Computes a continuity-corrected McNemar test for equality of proportions in a paired-samples design. This function requires the frequency counts from a 2 x 2 contingency table for two paired dichotomous measurements.

Usage

```
test.prop.ps(f00, f01, f10, f11)
```

Arguments

f00	number participants with y = 0 and x = 0
f01	number participants with y = 0 and x = 1
f10	number participants with y = 1 and x = 0
f11	number participants with y = 1 and x = 1

Value

Returns a 1-row matrix. The columns are:

- Estimate - ML estimate of proportion difference
- z - z test statistic
- p - p-value

References

Snedecor GW, Cochran WG (1989). *Statistical Methods*, 8th edition. ISU University Pres, Ames, Iowa.

Examples

```
test.prop.ps(156, 96, 68, 80)

# Should return:
# Estimate      z      p
#    0.07 2.108346 0.03500109
```

`test.prop1`*Hypothesis test for a single proportion*

Description

Computes a continuity-corrected z test for a single proportion in a 1-group design.

Usage

```
test.prop1(f, n, h)
```

Arguments

f	number of participants who have the attribute
n	sample size
h	population proportion under null hypothesis

Value

Returns a 1-row matrix. The columns are:

- Estimate - ML estimate of proportion
- z - z test statistic
- p - p-value

References

Snedecor GW, Cochran WG (1989). *Statistical Methods*, 8th edition. ISU University Pres, Ames, Iowa.

Examples

```
test.prop1(9, 20, .2)

# Should return:
# Estimate      z      p
#    0.45 2.515576 0.01188379
```

`test.prop2`*Hypothesis test for a 2-group proportion difference*

Description

Computes a continuity-corrected z test for a difference of proportions in a 2-group design.

Usage

```
test.prop2(f1, f2, n1, n2)
```

Arguments

f1	number of group 1 participants who have the attribute
f2	number of group 2 participants who have the attribute
n1	sample size for group 1
n2	sample size for group 2

Value

Returns a 1-row matrix. The columns are:

- Estimate - ML estimate of proportion difference
- z - z test statistic
- p - p-value

References

Snedecor GW, Cochran WG (1989). *Statistical Methods*, 8th edition. ISU University Pres, Ames, Iowa.

Examples

```
test.prop2(11, 26, 50, 50)

# Should return:
# Estimate      z      p
#    -0.3 2.899726 0.003734895
```

test.skew	<i>Computes p-value for test of skewness</i>
-----------	--

Description

Computes a Monte Carlo p-value (250,000 replications) for the null hypothesis that the sample data come from a normal distribution. If the p-value is small (e.g., less than .05) and the skewness estimate is positive, then the normality assumption can be rejected due to positive skewness. If the p-value is small (e.g., less than .05) and the skewness estimate is negative, then the normality assumption can be rejected due to negative skewness.

Usage

```
test.skew(y)
```

Arguments

y vector of quantitative scores

Value

Returns a 1-row matrix. The columns are:

- Skewness - estimate of skewness coefficient
- p - Monte Carlo two-sided p-value for test of zero skewness

Examples

```
y <- c(30, 20, 15, 10, 10, 60, 20, 25, 20, 30, 10, 5, 50, 40, 95)
test.skew(y)

# Should return:
# Skewness      p
# 1.5201 0.0067
```

Index

ci.2x2.mean.bs, 6
ci.2x2.mean.mixed, 7
ci.2x2.mean.ws, 8
ci.2x2.median.bs, 10
ci.2x2.median.mixed, 11
ci.2x2.median.ws, 12
ci.2x2.prop.bs, 13
ci.2x2.prop.mixed, 14
ci.2x2.stdmean.bs, 15
ci.2x2.stdmean.mixed, 17
ci.2x2.stdmean.ws, 18
ci.agree, 19
ci.agree.3rater, 20
ci.agree2, 21
ci.bayes.normal, 23
ci.bayes.prop1, 24
ci.biphi, 25
ci.cod1, 26
ci.cod2, 27
ci.condslope, 28
ci.condslope.log, 29
ci.cor, 30
ci.cor.dep, 31
ci.cor2, 32
ci.cor2.gen, 33
ci.cqv1, 34
ci.cramer, 35
ci.cronbach, 36
ci.cronbach2, 37
ci.cv1, 38
ci.etasqr, 39
ci.fisher, 40
ci.indirect, 41
ci.kappa, 42
ci.lc.gen.bs, 43
ci.lc.glm, 44
ci.lc.mean.bs, 45
ci.lc.median.bs, 46
ci.lc.prop.bs, 47
ci.lc.reg, 48
ci.lc.stdmean.bs, 49
ci.lc.stdmean.ws, 51
ci.mad1, 52
ci.mann, 53
ci.mape1, 54
ci.mape2, 55
ci.mean.ps, 56
ci.mean1, 57
ci.mean2, 58
ci.median.ps, 59
ci.median1, 60
ci.median2, 61
ci.oddsratio, 62
ci.pairs.prop.bs, 63
ci.pairs.prop1, 64
ci.pbcor, 65
ci.phi, 66
ci.popsiz, 67
ci.prop.ps, 68
ci.prop1, 69
ci.prop1.inv, 70
ci.prop2, 71
ci.prop2.inv, 72
ci.pv, 73
ci.random.anova1, 74
ci.ratio.cv2, 75
ci.ratio.mad.ps, 76
ci.ratio.mad2, 77
ci.ratio.mean.ps, 78
ci.ratio.mean2, 79
ci.ratio.median.ps, 80
ci.ratio.median2, 81
ci.ratio.prop.ps, 82
ci.ratio.prop2, 83
ci.ratio.sd2, 84
ci.rel2, 85
ci.reliability, 86
ci.rsqr, 87

ci.sign1, 88
ci.slope.mean.bs, 89
ci.slope.prop.bs, 90
ci.spcor, 91
ci.spear, 92
ci.spear2, 93
ci.stdmean.ps, 94
ci.stdmean.strat, 95
ci.stdmean1, 96
ci.stdmean2, 97
ci.tetra, 98
ci.theil, 99
ci.tukey, 100
ci.var.upper, 102
ci.yule, 102

etasqr.adj, 104
etasqr.gen.2way, 104

iqv, 105

pi.score.ps, 106
pi.score1, 107
pi.score2, 108
pi.var.upper, 109
power.cor1, 110
power.cor2, 110
power.lc.mean.bs, 111
power.mean.ps, 112
power.mean1, 113
power.mean2, 114
power.prop.ps, 115
power.prop1, 116
power.prop2, 116

random.sample, 117
random.y, 118
random.yx, 119
randomize, 120

sim.ci.cor, 120
sim.ci.mean.ps, 121
sim.ci.mean1, 123
sim.ci.mean2, 124
sim.ci.median.ps, 125
sim.ci.median1, 126
sim.ci.median2, 127
sim.ci.spear, 128
sim.ci.stdmean.ps, 129

sim.ci.stdmean2, 130
size.ci.agree, 131
size.ci.condmean, 132
size.ci.cor, 133
size.ci.cronbach, 134
size.ci.cronbach2, 135
size.ci.etasqr, 136
size.ci.indirect, 136
size.ci.lc.ancova, 137
size.ci.lc.mean.bs, 138
size.ci.lc.mean.ws, 139
size.ci.lc.prop.bs, 140
size.ci.lc.stdmean.bs, 140
size.ci.lc.stdmean.ws, 141
size.ci.mape1, 142
size.ci.mean.ps, 143
size.ci.mean1, 144
size.ci.mean2, 144
size.ci.pbcor, 145
size.ci.prop.ps, 146
size.ci.prop1, 147
size.ci.prop2, 148
size.ci.ratio.mean.ps, 148
size.ci.ratio.mean2, 149
size.ci.ratio.prop.ps, 150
size.ci.ratio.prop2, 151
size.ci.rsqr, 152
size.ci.second, 152
size.ci.slope, 153
size.ci.spear, 154
size.ci.stdmean.ps, 155
size.ci.stdmean2, 156
size.equiv.mean.ps, 157
size.equiv.mean2, 158
size.equiv.prop.ps, 159
size.equiv.prop2, 160
size.interval.cor, 161
size.supinf.mean.ps, 161
size.supinf.mean2, 162
size.supinf.prop.ps, 163
size.supinf.prop2, 164
size.test.cor, 165
size.test.cor2, 166
size.test.cronbach, 166
size.test.cronbach2, 167
size.test.lc.ancova, 168
size.test.lc.mean.bs, 169
size.test.lc.mean.ws, 170

size.test.lc.prop.bs, 171
size.test.mann, 172
size.test.mean.ps, 173
size.test.mean1, 173
size.test.mean2, 174
size.test.prop.ps, 175
size.test.prop1, 176
size.test.prop2, 177
size.test.sign.ps, 178
size.test.sign1, 178
size.test.slope, 179
slope.contrast, 180
spearmanbrown, 181

test.anova1.bs, 181
test.kurtosis, 182
test.mono.mean.bs, 183
test.mono.prop.bs, 184
test.prop.bs, 185
test.prop.ps, 186
test.prop1, 187
test.prop2, 188
test.skew, 189